

MultiCard – A Printing System for Terminals, Wires and Devices

Product Information

Weidmüller

MultiCard

Systemised marking 4
Description of material 6
Weidmüller tests and test procedures 7
Standards and regulations for markings 8

Terminal markers
Selection table 10
Dekafix 13
WS markers 15
ZS markers 16
WAD 19
Tag carriers 20
ELS 21
MultiFit 24
Cross-reference table 28

Wire and cable markers 42
SlimFix 44
SlimFix Clip 46
TM-I Insert tag 48
Transparent sleeves 50
ELS 53

Device markers 54
DMC 55
ESG-tags 56
SwitchMark SM 57
ClipCard CC 60

Printers 62
PrintJet PRO 63
MCP Plus 64
MCP Basic 65
MC-Mobilo 67

Software M-Print® PRO
68

Accessories
Cable ties 69

Appendix
74

System-based marking for optimized processes

For more than 25 years, the Weidmüller name has stood for innovative and mutually compatible marking and printing systems with all the necessary software and service. As a technological and market leader, we feel it is our duty to move with the times. Our products set standards and play a significant part in helping you to master increasingly complex production processes efficiently and reliably.

The PrintJet PRO is part of this unique concept that unites hardware, software and service that have been developed and synchronised to perfection, offering everything from a single source. All of the elements knit together, offering you all sorts of new options in terms of marking terminals, wires, cables and devices. For big companies or small, the system has just the right modules for your needs and can be fine-tuned to meet specific requirements.

Marker

Weidmüller has set new standards in its field with its MultiCard program. With a choice of 180 versions and the ongoing expansion of its portfolio, which already includes labels, shrinkable tubing and CableLine® markers, it caters for all possible needs. If necessary, we are happy to develop a customised solution for your specific needs too.

- A large selection of markers for connectors, cables, wires and devices
- Also available for terminals and components from other manufacturers
- Print is highly resistant to industrial environment
- We deliver blank, standard, or custom-printed markers according to your needs

Printer

The PrintJet PRO is a groundbreaking printer, setting new standards in terms of performance and innovation. Our range of printing systems also includes the THM Plus for shrinkable tubing and the SMark Laser for printing larger batches quickly and in top quality.

- The right printing system for any marker type
- Laser, ink-jet and thermal-transfer systems
- Very little maintenance and easy to operate
- Diverse range of connection possibilities

Software

Import, edit and manage your data with our software package that consists of modules catering for the entire field of application, from the CAD workplace to implementing cabinet components in close cooperation with leading CAE manufacturers.

- Data transfer from the leading CAE systems
- Import wizard with use of import filter
- Convenient and quick design by means of a wide range of automatic filling functions
- Work easier with individual templates for reoccurring processes

Service

We are here to help you with your requirements at all times, assisting you with everything from installation to training sessions and a whole host of different solutions such as preprinted markers. We break down barriers and are there for you, wherever you are in the world.

- Professional consulting for all marking and printing system questions
- Customized solutions which take your application into account
- Representatives throughout the world with trained specialists on-site
- Online software training via web conference tool

Materials

Material	Description
Polyamide	Polyamide (PA) is one of the most common commercial plastics. The advantages of this material are its very good electrical and mechanical properties, its flexibility and resistance to breakage. Furthermore, owing to its chemical structure, PA achieves good fire resistance even without the use of flame-retardant agents. **Temperature range: –40 °C to +100 °C**
PVC	Plasticised PVC is manufactured from polyvinyl chloride and softeners together with additives like stabilisers and lubricants. It is generally transparent but can be dyed any colour. PVC is resistant to corrosive salt solutions and the majority of acids and alkalis. Owing to its chemical structure, raw PVC resists ageing and is not attacked by oxygen or ozone **Temperature range: –30 °C to +80 °C**
Polypropylene	Polypropylene (PP) belongs to the polyolefins group of materials. These partially crystallised synthetic materials are distinguished by their good chemical resistance and good electrical properties. PP can be attacked by strongly oxidising chemicals. **Temperature range: –40 °C to +80 °C**
Stainless steel	SS 2348 corresponds to Al Si 316 and steel grade 1.4404. This acid-resistant steel contains at least 17 % chromium, 11 % nickel and 2 % molybdenum. The material exhibits good weathering resistance in salt-laden and moist atmospheres and does not corrode in the presence of acids. **Temperature range: –80 °C to +500 °C**
Hard PVC	Hard PVC is manufactured from polyvinyl chloride without plasticisers. This is the reason for its high mechanical strength, rigidity and hardness characteristics. In addition, high resistance to chemicals is further distinguishing feature. The absence of plasticisers in hard PVC ensures that the material ‘self-extinguishes’ once it is removed from the flames. **Temperature range: –30 °C to +80 °C**
POM	Polyacetal is also known as polyoxymethylene, abbreviated to POM. Its distinguishing characteristics include a high-degree of tensile strength, hardness and stiffness across a wide temperature range. **Temperature range: –40 °C to +80 °C**

Weidmüller tests and test procedures

Tests	Test conditions/requirements
Materials test	Flammability in accordance with UL94 Shore A hardness test A – ISO 868 Surface resistance – DIN IEC 60093
Ageing	All marker materials are tested for their ageing resistance.
Function test of PTFE and PVC wire insulation	Suitability of markers for installation at temperatures between –10 °C to +40 °C. Correct attachment test of the respective marker size for the smallest to the largest wire diameter. Test for symmetry of the marker on the wire
Vibration resistance on carrier	Vibration test, industry, in accordance with: DIN EN 60068-2-6, sinusoidal (3 axes, 10 cycles per axis, acceleration 5g, frequency 10-500 Hz, sweep rate 1 octave/minute) Weidmüller test specification – LPV 2272
Wipe resistance	Resistance of the print against the affects of hand perspiration, machine oil, water and ethanol. A slight alteration is permissible; however, clear identification (legibility) must be guaranteed. In the case of printing subject to VDE 0611 pt 4 (rating plate details), the wipe resistance against water and mineral spirits is to be tested for a period of 15 minutes. Standards: DIN VDE 0611-4 / Pt. 3.1.3 DIN EN 60947-1/ Pt. 5.1 DIN EN 60742, CEI 16-7 Weidmüller test specification – LPV 2166
Scratch resistance	No scratches may be visible on the base or the carrier following the fingernail test. A slight alteration is permissible; however, clear identification must be guaranteed. Weidmüller test specification – LPV 2165
UV light resistance	The function must be guaranteed. The print or colour of the product must be clearly recognisable. Standard: DIN EN ISO 4892-2; Weidmüller test specification – LPV 2216
Chemical resistance of the print	Weidmüller test specification – LPV 2167

Owing to the sheer number of possible applications and environmental influences such as moisture, radiation, gases or heat/cold to which the products can be exposed, Weidmüller accepts no liability for the suitability of products in all customer applications. Suitability tests for specific applications must therefore be carried out by the customer. However, Weidmüller will be happy to provide help and advice upon request.

Due to the different identification system available on the market, we wish to point out that Weidmüller does not guarantee industrial identification products if the Weidmüller components (markers – transparent sleeves – ink/toner/colour ink ribbons – printing systems) are combined with third-party products, unless Weidmüller has explicitly agreed for the purpose of an individual application.

Standards and regulations for markings

Safety, ease of maintenance and gain
Markers are not an end to themselves, but are a basic requirement for rapid and reliable maintenance as well as successful troubleshooting procedures. This is a particularly important under the aspect of product reliability legislation, because when damage occurs it is possible to quickly trace the possible cause. In addition, clear and unambiguous identification of electrical equipment and installations is binding for all. Standards requiring adherence are: DIN EN 60204-1 (VDE 0113 Part 1):1998-11 [1, 2] Electrical equipment of machines; Safety group standard, Type B1 in compliance with CEN classification) and DIN EN 61082-1:1995-05 [3] previously (DIN 40719-2 [4]). A further requirement: markings should be made of non-metallic materials and be resistant to oils, water, cleaning agents based on oils as well as UV radiation.

“Structured marking”
The standard DIN EN 61082-1 (VDE 0113 Part 1:1998-11 [1]) dictates that markings consist of four blocks for clear and unambiguous identification markings. If the circuit diagram lacks space, blocks not absolutely required for identification purposes can be left out. In this case, it is possible to alter the sequence of the blocks.



Identification block 1: “Installation”
Block 1 with the sign “=” denotes higher level assignment. This for marking the entire installation or system. The block is divided up into five sections, which generally contain two positions. One means of differentiation is the sequence of letters and digits. There are a total of max. ten positions possible. The marking begins from the left with the largest functional unit and ends on the right with the smallest.



Identification block 2: “Location of the electrical equipment”
Block 2 with the sign “+” allows for rapid localisation of the electrical equipment in larger installations. As a rule, the marking consists of letters or digits that describe the co-ordinates; they are generally divided up into six sections each with two positions (in section six there are as many as eight positions). In total, a max. of 18 positions are possible. The place of installation is to the left of the group mark, the position of installation is to the right.



For practical purposes, the installation and location markings can be made using the “ClipCard” device markers. The system consists of an identification system in MultiCard format as well as the card holder in an open design. The program is rounded off with a tag rail including transparent sleeves. The card holder has been designed to allow a wide variety of attachment options. The identification cards are supplied without markings. Of course, individual printing options are available.

Identification block 3: “Type and function”
All electrical equipment is given a type identification by the manufacturer. In addition, identification block 3 with the “-” sign is a distinguishing feature providing information about the type and function of the electrical equipment. Block 3A is labelled using letters. The item number 3B provides information to help distinguish between items of equipment, should there be multiples of the same type of equipment in service or the blocks 3A and 3C are missing. Consecutive numbers can be used. Finally, it is possible to identify the function of the electrical equipment with 3C.



Block 3: “Marking of electrical equipment”
Type, item number and function are differentiated. Electrical equipment identified as devices are, for example, indicator lights, contactor relays, miniature circuit-breaker, power supplies, relay couplers, terminal blocks, interface units, starting circuit breakers and all control devices.

Examples: “Electrical equipment block 3A”

Type of device	Classification letter	Example
Switch for heavy current	Q	Starting circuit breaker, disconnector, circuit-breaker
Contactor	K	Power contactor, contactor relay, relay coupler, timing relay
Protective equipment	F	Fusible links, miniature circuit-breaker, overvoltage protection, monitoring modules
Motors	M	Three-phase motor, DC motor
Transformer	U	AD converter, modules for converting an electrical quantity into a different quantity, for example, V – I, I – f switching modules
Connection elements	X	Terminal blocks, connectors, terminal boards, socket outlets, isolating plugs

Identification block 4: “Connection and wire designation”



Block 4 with sign “:” contains the connection and wire designation of the electrical equipment. These are laid down in standards. The companies supplying the equipment mark their devices during the manufacturing process with the corresponding designation.
Where no agreement has been reached with regard to designation or the designation is not customary in practical applications, the designation of the connection is numbered sequentially.

Direction designation (external – internal)
As well as providing a clear overview of the designations of the connection points, internal and external direction designations facilitate rapid troubleshooting tasks.
Wires connected to the terminal blocks are the most suitable for direction designations. Here the wire and cable markers show their worth with simple fixation onto the wire wire.



Literature
[1] DIN EN 60204-1 (VDE 0113 Part 1):1998-11 Safety of machinery – Electrical equipment of machines – Part1: General requirements. Berlin – Offenbach: VDE VERLAG (publishers) – available from www.vde-verlag.de.
[2] IEC 60204-1:2000-05 Safety of machinery – Electrical equipment of machines – Part 1: General requirements. Genf/Switzerland: Bureau Central de la Commission Electrotechnique Internationale – available from www.iec-normen.de.
[3] DIN EN 61082-1:1995-05 Preparation of documents used in electrotechnology – Part 1: General requirements. Berlin: Beuth – available from www.beuth.de.
[4] Z DIN 40719-2:1973-06 circuit documentation

Selection table

Designation	Terminal width	DEK	WS	ZS	SchT 7	SchT 9/4	SchT 14/6	WTS 3/4	WGB 5 / WAD 5	WGB 8 / WAD 8	WAD 12	WAD 27	ZGB 15 / ZGB 30	BZT 1	BZT 2	EM 8/30	Other
ADK 1	**6**	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
AKA 4	**6**	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
AKE 2.5/AKZ 2.5...	**5**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
AKE 2.5	**5.1**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
AKE 4	**7**	6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
AKZ 1.5...	**5**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
AKZ 1.5-2.5	**5.1**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
AKZ 4	**6.1**	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
AKZ 4.../AKB 4...	**6**	6	8/5	-	-	x	-	-	-	-	-	-	-	-	-	-	-
AL 1	**6.5**	6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ASK 1	**8**	8	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
AST 1-4/35	**6.2**	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
AST 5/35	**6.5**	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BZT ZVL 1.5	**5.08**	5	12/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
DK 4…	**6**	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
DKT 4…	**6**	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
DLA 2.5...	**6**	6	8/5	-	x	x	x	-	-	-	-	-	-	-	-	-	-
DLD 2.5...	**6**	6	8/5	-	x	x	x	-	-	-	-	-	-	-	-	-	-
DLI 2.5	**6**	6	8/5	-	x	x	x	-	-	-	-	-	-	-	-	-	-
EK 10	**10**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
EK 16	**12**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
EK 2.5…	**6**	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
EK 35…	**16**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
EK 4…	**6.5**	6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
EK 6/35	**8**	8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
EW 15	**9.5**	5	12/5	-	x	x	-	x	-	-	-	-	-	-	-	-	-
EW 15/2	**8**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
EW 35	**8.5**	5	8/5	-	-	-	-	x	-	-	-	-	-	-	-	-	-
EWK	**8.5**	5	8/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
EWK 1	**8.5**	5	8/5	-	-	-	-	x	-	-	-	-	-	-	-	-	-
EWK 2	**8.5**	5	8/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
IAK 1.5N 3L	**5**	5	10/5[2]	10/5	-	-	-	-	-	-	-	-	x	-	-	-	-
IDK 1.5N	**5**	5	10/5[2]	10/5	-	x[3]	-	-	-	-	-	-	-	-	-	-	-
IDK 1.5N/V	**5**	5	10/5[2]	10/5	-	-	-	-	-	-	-	-	x	-	-	-	-
IDU 1.5 N ...	**5**	5	10/5[2]	10/5	-	-	-	-	-	-	-	-	x	-	-	-	-
IEK 1.5N...	**5**	5	10/5[2]	10/5	-	-	-	-	-	-	-	-	x	-	-	-	-
IIK 1.5N...	**5**	5	10/5[2]	10/5	-	-	-	-	-	-	-	-	x	-	-	-	-
IPE 1.5N...	**5**	5	10/5[2]	10/5	-	-	-	-	-	-	-	-	x	-	-	-	-
ITR 1.5N...	**5**	5	10/5[2]	10/5	-	-	-	-	-	-	-	-	x	-	-	-	-
KDKS 1…	**8**	8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
KMVF…	**6**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
KSKM…	**13**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
KST…	**24-34**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
MAK 2.5/VLI 1.5...	**6**	6	8/5	-	x	x	x	-	-	-	-	-	x	-	-	-	-
NT…	**6-12**	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PDK 2.5/4	**5**	5	12/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PDL 4...	**5**	5	12/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PDU 16	**12**	-	10/12	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PDU 2.5/4...	**5**	5	12/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PDU 6/10...	**8**	8	10/8	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PEI 16	**12**	-	10/12	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PNT 16	**12**	-	10/12	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PNT 2.5/4	**5**	5	12/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PNT 6/10	**8**	8	10/8	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PPE 16	**12**	-	10/12	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PPE 2.5/4	**5**	5	12/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PPE 6/10	**8**	8	10/8	-	-	-	-	-	-	-	-	-	-	-	-	-	-
PTR 2.5/4…	**5.1**	5/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
RSF 1-3…	**8**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
SAK 10…	**10**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
SAK 16…	**12**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
SAK 2.5	**6.1**	6	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAK 2.5/35	**5**	5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAK 35…	**18**	5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAK 4…	**6.5**	6.5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAK 6…	**8**	8	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAK 95/35	**28**	5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAKA 10	**12**	5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAKB 10	**10**	5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAKC 10/35	**12**	6.5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAKC 4/35	**6.5**	6.5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAKD 2.5N	**5**	5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAKG…	**32-54**	5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAKH 35	**18**	6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
SAKH 4-10	**6.5-14**	5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAKK 10..	**11.5**	5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAKK 4..	**8**	6.5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAKR…	**6.5**	6.5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAKS….	**13-28**	5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
SAKT…	**8**	6.5	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-
VWGK 4…	**10**	5/5	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
VWGK 6…	**10**	5/5	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WDK 1.5/R 3.5...	**3.5**	3.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

1) = WS 10/6 Middle; 2) = WS 10/5 Middle; 3) = SnapMark

Designation	Terminal width	DEK	WS	ZS	SchT 7	SchT 9/4	SchT 14/6	WTS 3/4	WGB 5 / WAD 5	WGB 8 / WAD 8	WAD 12	WAD 27	ZGB 15 / ZGB 30	BZT 1	BZT 2	EM 8/30	Other
WDK 2.5 ...	**5**	5	8/5	-	-	x	-	-	-	-	-	-	x	-	-	-	-
WDK 2.5 800V	**6**	6	8/5	-	-	x	-	-	-	-	-	-	x	-	-	-	-
WDK 2.5/BLA R5.08	**5.08**	5	8/5	-	-	-	-	x	-	-	-	-	-	-	-	-	-
WDK 2.5/BLZ R5.08	**5.08**	5	8/5	-	-	-	-	x	-	-	-	-	-	-	-	-	-
WDK 2.5N...	**5**	5	8/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WDK 4N...	**5**	5	8/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WDL 2.5/...	**6**	6	8/5	-	-	-	-	x	-	-	-	-	x	-	-	-	-
WDT 1.5	**6.5**	6.5	8/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WDTR 2.5...	**6.2**	6	8/5	-	-	x	-	-	-	-	-	-	-	-	-	-	-
WDU (WPE) 120/150	**32**	5	10/5	-	-	-	-	x	-	-	-	x	-	-	-	-	-
WDU (WPE) 35 N	**16**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WDU (WPE) 70/95	**27**	5	12/5	-	-	-	-	x	-	-	-	x	-	-	-	-	-
WDU (WPE) 70N	**20.5**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WDU 1.5 LD/BLA	**5.08**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WDU 1.5/BLA	**5.08**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WDU 1.5/BLZ R7.62	**7.62**	5	-	-	-	-	-	-	-	-	-	-	x	-	-	-	-
WDU 1.5/BLZ/5.08	**5.08**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WDU 1.5/BLZ/LD/5.08	**5.08**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WDU 1.5/R 3.5...	**3.5**	3.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WDU 1.5/R/BLA	**5.08**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WDU 1.5/ZZ	**5**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WDU 10 SL	**10**	5	12/5	-	x	x	x	x	x	x	-	-	x	-	-	-	-
WDU 10...	**10**	5	12/5	-	x	x	x	x	x	x	-	-	x	-	-	-	-
WDU 16 (/ZA)	**12**	5	12/5	-	x	x	x	x	-	-	x	-	x	-	-	-	-
WDU 16 N	**12**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WDU 2.5 F	**5**	5	12/5	-	-	-	-	x	-	-	-	-	-	-	-	-	-
WDU 2.5 FF	**5**	5	12/5	-	x	-	-	x	-	-	-	-	-	-	-	-	-
WDU 2.5 N (WDU 1.5)	**5**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WDU 2.5 TC...	**5**	5	12/5	-	x	x	-	x	-	-	-	-	x	-	-	-	-
WDU 2.5...	**5**	5	12/5	-	x	x	x	x	x	-	-	-	x	-	-	-	-
WDU 2.5/1.5/ZZ	**5**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WDU 2.5/BLZ R7.62	**7.62**	5	-	-	-	-	-	-	-	-	-	-	x	-	-	-	-
WDU 240...	**36**	5	12/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WDU 35	**16**	5	12/5	-	x	x	x	x	-	-	x	-	x	-	-	-	-
WDU 4 ...	**6**	6	12/6	-	x	x	x	x	x	-	-	-	x	-	-	-	-
WDU 4N ...	**6**	6	12/6	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WDU 50N	**18.5**	5	12/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WDU 6 ...	**8**	8	12/8	-	x	x	x	x	x	x	-	-	x	-	-	-	-
WDU 95N	**27**	8	15/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WDUL 4	**6**	6	12/6	-	x	x	x	x	x	-	-	-	x	-	-	-	-
WEW 32/1	**12.2**	5	12/5	-	x	x	x	x	-	-	-	x	x	-	-	-	-
WEW 35/1	**12.2**	5	12/5	-	x	x	x	x	-	-	-	-	-	-	-	-	-
WEW 35/2	**8**	8	12/5	-	x	x	x	x	x	x	-	-	-	-	-	x	-
WF 10...	**35.6**	6	15/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WF 12...	**35.6**	6	15/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WF 5...	**13**	6	15/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WF 6...	**19.6**	6	15/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WF 8...	**24.6**	6	15/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WFF 120...	**42**	5	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WFF 185...	**55**	5	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WFF 300...	**55**	5	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WFF 35...	**27**	5	12/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WFF 70...	**32**	5	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WGK 10.../WGKV 10..	**10.1**	5/5	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WGK 16…	**12.1**	5/5	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WGK 25…/WGKV 25…	**15.1**	5/5	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WGK 4…/WGKV 4…	**8.1**	5/8	10/8	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WGK 50…	**18.8**	6/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WGK 95…	**25**	5/8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WMA 4...	**6**	6	12/6	-	x	x	x	x	x	-	-	-	x	-	-	-	-
WNT 10	**10**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WNT 16 N	**12**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WNT 2.5	**5**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WNT 35 N	**16**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WNT 4	**6**	6	12/6	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WNT 6	**8**	8	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WNT 70 N	**20.5**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WPDB…		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	LM MT3000 15x9 GE
WPE 1.5/R3.5	**3.5**	3.5	12/3.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WPE 1.5/ZZ	**5**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WPE 10...	**10**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WPE 120	**32**	8	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WPE 16	**12**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WPE 16 N	**12**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WPE 2.5 N (WPE 1.5)	**5**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WPE 2.5...	**5**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WPE 2.5/1.5/ZR	**5**	5	12/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WPE 35...	**16**	5	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WPE 4	**6**	6	12/6	-	x	x	x	x	-	-	-	-	x	-	-	-	-
WPE 4N	**6**	6	12/6	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WPE 50N	**18.5**	8	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WPE 6	**8**	8	12/5	-	x	x	x	x	-	-	-	-	x	-	-	-	-

Designation	Terminal width	DEK	WS	ZS	SchT 7	SchT 9/4	SchT 14/6	WTS 3/4	WGB 5 / WAD 5	WGB 8 / WAD 8	WAD 12	WAD 27	ZGB 15 / ZGB 30	BZT 1	BZT 2	EM 8/30	Other
WPE 95N/120N	**27**	8	15/5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WPO 4	**6**	6	10/6	-	-	-	-	-	-	-	-	-	x	-	-	-	-
WSI 25…	**18**	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	ESG 6/15
WSI 6...	**8**	8	12/5	-	-	-	-	x	-	-	-	-	x	-	-	-	-
WSI 6/2...	**12**	8	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WTD 6/1	**8**	8	12/5	-	-	-	-	x	-	-	-	-	x	-	-	-	-
WTL 35	**16**	-	12/6														-
WTL 4 ...	**6**	6	12/6	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WTL 6/1...	**8**	8	12/8	-	-	-	-	x	-	-	-	-	x	-	-	-	-
WTL 6/2	**8**	8	12/8	-	-	-	-	x	-	-	-	-	x	-	-	-	-
WTL 6/3...	**8**	8	12/8	-	-	-	-	x	-	-	-	-	x	-	-	-	-
WTQ 6/1	**8**	8	12/8	-	-	-	-	x	-	-	-	-	x	-	-	-	-
WTR 2.5 ...	**5**	5	12/5	-	-	-	-	x	-	-	-	-	x	-	-	-	-
WTR 35 E	**32**	-	12/6	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WTR 4...	**6**	6	12/6	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZAP/TW ZIA 1.5/...	**3.8**	3.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZDK 1.5...	**3.5**	3.5	12/3.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZDK 2.5...	**5**	5	12/5	15/5	-	-	-	x	-	-	-	-	x	-	-	-	-
ZDK 2.5-2...	**5**	5	10/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-
ZDK 2.5N…	**5.1**	5/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-	ZAD 9/4
ZDK 4/S/...	**6**	6	-	12/6	-	-	-	x	-	-	-	-	x	-	-	-	-
ZDK 6/S/...	**8**	8	-	-	-	-	-	x	-	-	-	-	x	-	-	-	-
ZDKPE 2.5	**5**	5	10/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-
ZDL 2.5/...	**5**	5	-	10/5	-	-	-	-	-	-	-	-	x	-	-	-	-
ZDLD 2.5-2...	**5**	5	-	10/5	-	-	-	-	-	-	-	-	x	-	-	-	-
ZDT 2.5 ...	**5**	5	10/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-
ZDTPE 2.5...	**5**	5	10/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-
ZDTR 2.5	**5**	5	12/5	15/5	-	-	-	x	-	-	-	-	x	-	-	-	-
ZDU (ZPE) 10	**10**	5	12/5	15/5	-	x	-	-	-	-	-	-	x	x	x	-	-
ZDU (ZPE) 10/S...	**10**	5	10/5	15/5	-	x	-	-	-	-	-	-	x	x	x	-	-
ZDU (ZPE) 16...	**12**	5	12/5	15/5	-	x	-	x	-	-	-	-	x	x	x	-	-
ZDU (ZPE) 16/S...	**12**	5	10/5	15/5	-	x	-	-	-	-	-	-	x	x	x	-	-
ZDU (ZPE) 2.5 ...	**5**	5	12/5	15/5	-	-	-	x	-	-	-	-	x	x	x	-	-
ZDU (ZPE) 2.5-2/...	**5**	5	12/5	15/5	-	-	-	x	-	-	-	-	x	-	-	-	-
ZDU (ZPE) 2.5N…	**5.1**	5/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-	ZAD 9/4
ZDU (ZPE) 35...	**16**	5	12/5	15/5	-	-	-	x	-	-	-	-	x	x	x	-	-
ZDU (ZPE) 4...	**6**	6	12/6	12/6	-	-	-	x	-	-	-	-	x	x	x	-	-
ZDU (ZPE) 4-2...	**6**	6	12/6	12/6	-	-	-	-	-	-	-	-	-	-	-	-	-
ZDU (ZPE) 6...	**8**	8	12/8	15/5	-	-	-	x	-	-	-	-	x	x	x	-	-
ZDU (ZPE) 6-2...	**8**	8	12/8	12/6	-	-	-	-	-	-	-	-	-	-	-	-	-
ZDU 1.5...	**3.5**	3.5	12/3.5	-	-	-	-	-	-	-	-	-	-	x	x	-	-
ZDUA (ZPEA) 2.5-2	**5**	5	8/5	15/5	-	-	-	x	-	-	-	-	x	-	-	-	-
ZDUA 2.5-2N	**5**	5	10/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-
ZDUB (ZPEB) 2.5-2/...	**5**	5	8/5	15/5	-	-	-	-	-	-	-	-	x	-	-	-	-
ZEI 16	**16**	5	12/5	15/5	-	-	-	x	-	-	-	-	x	-	-	-	-
ZEI 6	**10**	8	12/6	12/6	-	-	-	x	-	-	-	-	x	x	x	-	-
ZEW 35/2	**8**	8	-	-	-	-	-	-	-	-	-	-	-	-	-	x	-
ZIA 1.5 ...	**5.08**	5	8/5	15/5	-	-	-	x	-	-	-	-	x	-	-	-	-
ZMAK 2.5	**5**	5	10/5	15/5	-	-	-	-	-	-	-	-	x	-	-	-	-
ZNT 10/S	**10**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZNT 16/S	**12**	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZNT 2.5/S	**5**	5	10/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-
ZNT 4/S	**6**	6	10/6	12/6	-	-	-	-	-	-	-	-	-	-	-	-	-
ZNT 6/S	**8**	8	10/6	12/6	-	-	-	-	-	-	-	-	-	-	-	-	-
ZP 2.5...	**5.1**	5/5	10/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-
ZPE 16-2/1 AN	**12**	8	12/6	12/6	-	-	-	-	-	-	-	-	-	-	-	-	-
ZPV 1.5	**5.08**	5	12/5	15/5	-	x	x	x	-	-	-	-	x	-	-	-	-
ZRV 1.5...	**5**	5	8/5	10/5	-	x	x	x	-	-	-	-	x	-	-	-	-
ZSI 2.5...	**8**	8	12/5	15/5	-	-	-	x	-	-	-	-	x	-	-	-	-
ZSI 2.5/2...	**12**	5	12/5	15/5	-	-	-	x	-	-	-	-	x	-	-	-	-
ZSI 6-2/FC	**8**	6	12/6	12/6	-	-	-	-	-	-	-	-	-	-	-	-	-
ZT 2.5 ...	**5**	5	10/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-
ZTD 6	**8**	8	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZTL 6	**8**	8	12/6.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZTPE 2.5 ...	**5**	5	10/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-
ZTR 2.5...	**5**	5	12/5	15/5	-	-	-	x	-	-	-	-	x	-	-	-	-
ZTR 2.5-2...	**5**	5	14/5	10/5	-	-	-	-	-	-	-	-	-	-	-	-	-

DEK MultiCard

The Dekafix marker in MultiCard format is the universal marker for all kinds of connectors and also electronic modules from the Weidmüller product range. The blank DEK marker is ideal for flexible, fast printing in situ with our innovative labelling systems SMark-Laser, PrintJet, MCP Plus Plotter or MC-Mobilo. The system is particularly suitable for short sequences of numbers and is also available with special printing.

- In strips for fast installation
- Flexible, fast printing on site during installation
- Excellent printing quality thanks to the Weidmüller MultiCard printers
- Available in 6 widths
- Custom printing with the MC Laser also possible





Technical data

Material	Polyamide 66, halogen-free
UL 94 flammability rating	V2
Temperature range	–40 °C to 100 °C
Printing	black

Ordering data

Colour	Available in all colours of the international colour code; for MC on request ● brown ● red ● orange ● yellow ● green ● blue ● violet ● grey O white
Special printing	Specify special printing and colours per diskette, Excel file or using the M-Print® PRO software.
Minimum order quantity	1 pack
Notes on mounting	Mount in strips when the marker pitch (width) corresponds to the pitch of the terminals. For example, DEK 5 mm pitch for terminals with 5 mm pitch such as the WDU 2.5.
	Mount individual markers when the terminal pitch is larger than the marker pitch (width). For example, DEK 6.5 mount individually on WDU 6 terminals.

Dekafix - the universal marker for SAK series, W-series, Z-series, P-series and I-series plus WEICOS connectors and electronics devices.

Clamping width: 3.5 mm

Ordering data

DEK - blank

Type	Material colour	Length	Qty.	Order No.
DEK 5/3,5 MC	white	5 mm	500	**1755270000**

DEK - Custom printing

Type	Material colour	Length	Qty.	Order No.
DEK 5/3,5 MC	white	5 mm	100	**1767730000**

Clamping width: 5.0 mm

DEK - blank

Type	Material colour	Length	Qty.	Order No.
DEK 5/5 Plus MC	white	5 mm	1000	**1854490000**
DEK 5/5 Plus MC GE	yellow	5 mm	1000	**1907520000**
DEK 5/5 MC	white	5 mm	1000	**1609801044**
DEK 5/5 MC GE	yellow	5 mm	1000	**1609801687**
DEK 5/5 MC BL	blue	5 mm	1000	**1609801693**
DEK 5/5 MC GR	grey	5 mm	1000	**1609801691**
DEK 5/5 MC GN	green	5 mm	1000	**1609801688**
DEK 5/5 MC RT	red	5 mm	1000	**1609801686**

DEK - Custom printing

Type	Material colour	Length	Qty.	Order No.
DEK 5/5 MC	white	5 mm	200	**1609810000**
DEK 5/5 Plus MC	white	5 mm	200	**1854500000**

Clamping width: 6.0 / 6.5 mm

DEK - blank

Type	Material colour	Length	Qty.	Order No.
DEK 5/6 MC	white	5 mm	1000	**1609820000**
DEK 5/6 MC PLUS	white	5 mm	1000	**1011320000**
DEK 5/6,5 MC	white	5 mm	900	**1609840000**
DEK 5/6,5 PLUS MC n	white	5 mm	900	**1046340000**

DEK - Custom printing

Type	Material colour	Length	Qty.	Order No.
DEK 5/6 MC SDR	white	5 mm	200	**1609830000**
DEK 5/6 MC SDR PLUS	white	5 mm	200	**1038650000**
DEK 5/6,5 MC	white	5 mm	180	**1609850000**
DEK 5/6,5 PLUS MC n	white	5 mm	180	**1046360000**

Clamping width: 7.5 / 8.0 mm

DEK - blank

Type	Material colour	Length	Qty.	Order No.
DEK 5/7,5 MC	white	5 mm	320	**1720620000**
DEK 5/8 MC	white	5 mm	800	**1856740000**
DEK 5/8 PLUS MC n	white	5 mm	800	**1046350000**

DEK - Custom printing

Type	Material colour	Length	Qty.	Order No.
DEK 5/7,5 MC	white	5 mm	64	**1770490000**
DEK 5/8 MC	white	5 mm	160	**1856750000**
DEK 5/8 PLUS MC n	white	5 mm	160	**1046370000**

WS

WS markers are designed specifically for W series terminals. But thanks to their system compatibility, WS markers can also be used with the I series, Z series and P series. The generous size of these markers permit long characters strings and multiple-line printing.

WS markers are ideal for labelling where long, individual character strings are required. And the proven MultiCard format makes labelling possible with the SMark-Laser, PrintJet, MCP Plus Plotter or MC-Mobilo as well.

- Mount in strips or individually
- Markers in the proven MultiCard format
- Excellent printing quality thanks to the Weidmüller MultiCard printers



Technical data

Material	Polyamide 66, halogen-free
UL 94 flammability rating	V2
Temperature range	–40 °C to 100 °C
Printing	black

Bestellhinweis

Colour	Available in all colours of the international colour code; for MC on request ● brown ● red ● orange ● yellow ● green ● blue ● violet ● grey O white
Special printing	Specify special printing and colours per diskette, Excel file or using the M-Print® PRO software.
Minimum order quantity	1 pack
Notes on mounting	Mount in strips when the marker pitch (width) corresponds to the pitch of the terminals. For example, WS 10/6 = 6 mm pitch for terminals with 6 mm pitch such as the WDU 4.
	Mount individual markers when the terminal pitch is larger than the marker pitch (width). For example, WS 12/6.5 mount individually on WDU 6 terminals. Weidmüller markers with 5 mm pitch (width) are suitable for all widths of terminals.

ZS

ZS markers – in the proven MultiCard format – were specially developed for Z series terminals. They provide users with a large labelling area. Their unique hinged form means that cross-connectors, for example, are still readily accessible without having to remove the marker. Markers can be clipped on in strips to guarantee fast installation, but individual markers are easily separated.

- Hinged labelling area
- Mount in strips or individually
- Markers in the proven MultiCard format
- Flexible, fast printing on site during installation

Technical data

Material	Polyamide 66, halogen-free
UL 94 flammability rating	V2
Temperature range	–40 °C to 100 °C
Printing	black

Ordering data

Colour	white
Notes on mounting	height x width (pitch), e.g. ZS 10/5: 10 mm high, 5 mm wide = 5 mm pitch
Special printing	Specify special printing per diskette, Excel file or using the M-Print® PRO software.
Suitable printing systems	SMark-Laser, PrintJet, MCP Plus Plotter, MC-Mobilo
Minimum order quantity	1 pack

WS markers are perfect for the connectors of the W-series, I-series, P-series and Z-series. WS 10/5 and 10/6 Middle are fitted with a centre foot and can be used for the I-series. The ZS markers are specially conceived for the Z-series.



Clamping width: 3.5 mm

Ordering data

WS - blank

Type	Material colour	Length	Qty.	Order No.
WS 12/3,5 MC	white	12 mm	600	1778270000

WS - Custom printing

Type	Material colour	Length	Qty.	Order No.
WS 12/3,5 MC	white	12 mm	120	1778280000

Clamping width: 5.0 mm

WS - blank

Type	Material colour	Length	Qty.	Order No.
WS 8/5 MC	white	8 mm	720	1640740000
WS 8/5 MC GE	yellow	8 mm	720	1773521687
WS 8/5 MC RT	red	8 mm	720	1773521686
WS 8/5 MC BL	blue	8 mm	720	1773521693
WS 8/5 MC OR	orange	8 mm	720	1773521690
WS 8/5 PLUS MC	white	8 mm	600	1951870000
WS 10/5 MC	white	10 mm	720	1635000000
WS 10/5 MC GE	yellow	10 mm	720	1773531687
WS 10/5 MC Middle	white	10 mm	720	1792000000
WS 10/5 MC RT	red	10 mm	720	1773531686
WS 10/5 MC BL	blue	10 mm	720	1773531693
WS 10/5 PLUS MC	n white	10 mm	600	1046380000
WS 12/5 MC	white	12 mm	720	1609860000
WS 12/5 MC GE	yellow	12 mm	720	1773541687
WS 12/5 MC RT	red	12 mm	720	1773541686
WS 12/5 MC BL	blue	12 mm	720	1773541693
WS 12/5 MC OR	orange	12 mm	720	1773541690
WS 12/5 MC PLUS	white	12 mm	600	1927510000
WS 14/5 MC	white	14 mm	480	1768090000
WS 15/5 MC	white	15 mm	480	1609880000
WS 15/5 MC GE	yellow	15 mm	480	1773571687

WS - Custom printing

Type	Material colour	Length	Qty.	Order No.
WS 8/5 MC	white	8 mm	144	1640750000
WS 8/5 MC PLUS	white	8 mm	120	1038790000
WS 10/5 MC	white	10 mm	144	1635010000
WS 10/5 MC Middle	white	10 mm	144	1792010000
WS 10/5 PLUS MC	n white	10 mm	120	1046320000
WS 12/5 MC	white	12 mm	144	1609870000
WS 12/5 MC PLUS	white	12 mm	120	1927520000
WS 15/5 MC	white	15 mm	96	1609890000

Clamping width: 6.0 mm

WS - blank

Type	Material colour	Length	Qty.	Order No.
WS 8/6 PLUS MC	white	8 mm	600	1951880000
WS 10/6 MC	white	10 mm	600	1828450000
WS 10/6 MC Middle	white	10 mm	600	1818400000
WS 10/6 MC Middle GN	green	10 mm	600	1917420000
WS 10/6 MC Middle GE	yellow	10 mm	600	1917430000
WS 10/6 MC Middle RT	red	10 mm	600	1917440000
WS 10/6 MC Middle OR	orange	10 mm	600	1917410000
WS 10/6 PLUS MC	n white	10 mm	600	1046390000
WS 12/6 MC	white	12 mm	600	1609900000
WS 12/6 MC GE	yellow	12 mm	600	1773551687
WS 12/6 MC RT	red	12 mm	600	1773551686
WS 12/6 MC BL	blue	12 mm	600	1773551693
WS 12/6 MC OR	orange	12 mm	600	1773551690
WS 12/6 MC BR	brown	12 mm	600	1773551692
WS 12/6 MC VI	magenta	12 mm	600	1773551689
WS 12/6 MC PLUS	white	12 mm	600	1927530000

Terminal markers

WS markers are perfect for the connectors of the W-series, I-series, P-series and Z-series. WS 10/5 and 10/6 Middle are fitted with a centre foot and can be used for the I-series. The ZS markers are specially conceived for the Z-series.



Ordering data

WS - Custom printing

Type	Material colour	Length	Qty.	Order No.
WS 8/6 PLUS MC	white	8 mm	120	**1038820000**
WS 10/6 MC	white	10 mm	120	**1828460000**
WS 10/6 MC Middle	white	10 mm	120	**1818410000**
WS 10/6 PLUS MC n	white	10 mm	120	**1046330000**
WS 12/6 MC	white	12 mm	120	**1609910000**
WS 12/6 MC PLUS	white	12 mm	120	**1927540000**

Clamping width: 6.5 mm

WS - blank

Type	Material colour	Length	Qty.	Order No.
WS 12/6,5 MC	white	12 mm	540	**1609920000**
WS 12/6,5 MC GE	yellow	12 mm	540	**1773561687**
WS 12/6,5 MC RT	red	12 mm	540	**1773561686**
WS 12/6,5 MC BL	blue	12 mm	540	**1773561693**
WS 12/6,5 MC GN	green	12 mm	540	**1773561688**

WS - Custom printing

Type	Material colour	Length	Qty.	Order No.
WS 12/6,5 MC	white	12 mm	108	**1609930000**

Clamping width: 8.0 mm / 9,2 mm

WS - blank

Type	Material colour	Length	Qty.	Order No.
WS 10/8 MC	white	10 mm	420	**1905950000**
WS 12/8 MC	white	12 mm	420	**1906000000**
WS 7,8/9,2 PLUS MC	grey	7.8 mm	360	**1208970000**

WS - Custom printing

Type	Material colour	Length	Qty.	Order No.
WS 10/8 MC	white	10 mm	84	**1906030000**
WS 12/8 MC	white	12 mm	84	**1906010000**
WS 7,8/9,2 PLUS MC	grey	7.8 mm	72	**1270640000**

Clamping width: 12.0 / 15.0 mm

WS - blank

Type	Material colour	Length	Qty.	Order No.
WS 10/12 MC	white	10 mm	300	**1905970000**
WS 10/15 MC	white	10 mm	240	**1854090000**

WS - Custom printing

Type	Material colour	Length	Qty.	Order No.
WS 10/12 MC	white	10 mm	60	**1906060000**
WS 10/15 MC	white	10 mm	48	**1854100000**

Clamping width: 5.0 mm

ZS - blank

Type	Material colour	Length	Qty.	Order No.
ZS 10/5 MC	white	10 mm	480	**1610000000**
ZS 15/5 MC	white	15 mm	480	**1646630000**

ZS - Custom printing

Type	Material colour	Length	Qty.	Order No.
ZS 10/5 MC	white	10 mm	96	**1610010000**
ZS 15/5 MC	white	15 mm	96	**1646640000**

Clamping width: 6.0 mm

ZS - blank

Type	Material colour	Length	Qty.	Order No.
ZS 12/6 MC	white	12 mm	400	**1610020000**

ZS - Custom printing

Type	Material colour	Length	Qty.	Order No.
ZS 12/6 MC	white	12 mm	80	**1610030000**

Terminal marker WAD

- Top-quality and resistant printing with PrintJet printer
- WAD marker and cover for the terminals of the W-series and end brackets WEW 35/2 and ZEW 35/2
- Available as neutral marker, custom printing or with lightning flash
- Fast and easy assembling

The WAD-type markers can be printed by PrintJet printer. Colour printing with the PrintJet PRO, in particular, enables terminal strips to be labeled in a variety of noticeable manners.



Technical data

Material	Polyamide PA 66
Temperature range	–40° … +100 °C
Flammability rating	V2 according to UL 94
Suitable for	Feed-through terminal WDU 2.5, WDU 4, WDU 6 and WDU 10 End bracket WEW 35/2 and ZEW 35/2
Printable with	PrintJet and PrintJet PRO
Not printable with	SMark Laser and Plotter

Ordering data

Type	Colour	Qty.	Order No.
WAD 5 MC NE WS	white	48	**1112910000**
WAD 5 MC NE GE	yellow	48	**1112920000**
WAD 8 MC NE WS	white	48	**1112940000**
WAD 8 MC NE GE	yellow	48	**1112950000**
With lightning flash			
WAD 5 MC B GE/SW	yellow	48	**1120450000**
WAD 8 MC B GE/SW	yellow	48	**1120470000**
Custom printing			
WAD 5 MC SDR		12	**1112930000**
WAD 8 MC SDR		12	**1112970000**



This tag holder is specially conceived for the IDK 1.5N two-tier terminal of the I-series. The flexible hinge mechanism allows cross-connections to be connected or disconnected at little effort. It can be fitted with four DEK 5 tags or two WS 10/5 Middle connector markers.

Snap Mark

Technical specification

Material	Polyamide 66
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C
Material colour	white

Ordering data

Type	Length	Width	Qty	Order No.
Snap Mark I	23 mm	5 mm	50	**1805880000**

Accessories

Type	Length	Width	Qty	Order No.
DEK 5/5 MC	5 mm	5 mm	1000	**1609801044**
WS 10/5 MC middle	10 mm	5 mm	720	**1792000000**

The BZT tag carrier makes possible the clear labelling of the ZDU 2.5/4/6 and ZDUA terminal families. The BZT is used with the WS 10/5 terminal markers. By creating blocks of tag carriers, the ZA version offers the maximum stability.

BZT1 / BZT2

Technical specification

Material	Polyamide
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C
Material colour	beige

Ordering data

Type	Length	Width	Qty	Order No.
BZT 1	8 mm	5 mm	100	**1805490000**
BZT 1 ZA	8 mm	5 mm	100	**1805520000**
BZT 2	12 mm	5 mm	100	**1805480000**
BZT 2 ZA	12 mm	5 mm	100	**1805530000**

Accessories

Type	Length	Width	Qty	Order No.
WS 10/5 MC	10 mm	5 mm	720	**1635000000**



SchT 9/4 and SchT 14/6 are hinged group tag holders for single dekafix and WS tags, allowing easy access to the clamping screws.

SCHT 9/4 / SCHT 14/6

Technical specification

Material	Polyamide 66
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C
Material colour	beige

Ordering data

Type	Length	Width	Qty	Order No.
SCHT 14/6	44.3 mm	6 mm	20	**1269060000**
SCHT 9/4	32 mm	4 mm	20	**1278460000**

Accessories

Type	Length	Width	Qty	Order No.
DEK 5/5 MC	5 mm	5 mm	1000	**1609801044**
WS 12/5 MC	12 mm	5 mm	720	**1609860000**



The ELS-type MultiCard marker can be printed on with PrintJet, plotter or SMark printer. Colour printing with the PrintJet PRO, in particular, enables cables and terminal strips to be labelled in a variety of noticeable manners.

ELS insertion tag

Technical specification

Material	Polyamide PA 66
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C
Suitable for	ELS 6/30: WKM 8/30 (1631910000) and EM 8/30 (1806120000) ELS 7/40 : SchT5S (1631930000) ELS 16/40: SchT5 (0292460000) and WKM 18/43 (1610700000)

Ordering data

Type	Colour	Qty.	Order No.
blank			
ELS 6/30 MC NE WS	white	80	**1045570000**
ELS 6/30 MC NE GE	yellow	80	**1045580000**
ELS 7/40 MC NE WS	white	40	**1045640000**
ELS 7/40 MC NE GE	yellow	40	**1045650000**
ELS 16/40 MC NE WS	white	40	**1045620000**
ELS 16/40 MC NE GE	yellow	40	**1045630000**
Custom printing			
ELS 6/30 MC SDR		16	**1045660000**
ELS 7/40 MC SDR		8	**1045700000**
ELS 16/40 MC SDR		8	**1045690000**

The EM 8/30 end bracket marker is suitable for labelling the WEW 35/2 and ZEW 35/2 end brackets as well as marker carrier for W-series terminals. The EM 8/30 can be fitted with the ESO 7 and ESO 7P inlay tags. The pocket guarantees that the labelling is well protected against environmental influences.

EM 8/30

Technical specification

Material	Polypropylene
UL 94 flammability rating	HB
Min. temperature, continuous	-40 °C
Max. temperature, continuous	80 °C
Material colour	transparent

Ordering data

Type	Length	Width	Qty	Order No.
EM 8/30	30 mm	8 mm	50	**1806120000**

Accessories

Technical specification

ESO...P	= Polyester
ESO	= Paper

Type	Length	Width	No. per sheet	Qty	Order No.
ESO 7 white	27 mm	6.3 mm	240	10	**1607720000**
ESO 7 yellow	27 mm	6.3 mm	240	10	**1634780000**
ESO 7P white	27 mm	6.3 mm	240	10	**1670390000**
ESO 7P yellow	27 mm	6.3 mm	240	10	**1670400000**



WGB group marker carrier for single dekafix and WS tags. The WGB also covers the cross-connection channels.

Blank WAD covers for labelling with PrintJet, or a special printing for the W-series. Cross-connection channels are covered. Also available with lightning flash warning symbol to DIN 30600 (see page B.34).

WGB 5 / WGB 8 / WAD

Technical specification

Material	Polyamide 66
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C

Ordering data

Type	Length	Width	Material colour	Qty	Order No.
WGB 5	33.5 mm	5 mm	beige	50	**1050760000**
WGB 8	33.5 mm	7.7 mm	beige	50	**1050960000**
WAD 5 MC NE WS	33.5 mm	5 mm	white	48	**1112910000**
WAD 5 MC NE GE	33.5 mm	5 mm	yellow	48	**1112920000**
WAD 5 MC B GE/SW flash	33.5 mm	5 mm	yellow	48	**1120450000**
WAD 8 MC NE WS	33.5 mm	8 mm	white	48	**1112940000**
WAD 8 MC NE GE	33.5 mm	8 mm	yellow	48	**1112950000**
WAD 8 MC B GE/SW flash	33.5 mm	8 mm	yellow	48	**1120470000**
WAD 12	36.2 mm	12 mm	white	50	**1056260000**
WAD 12 lightning flash	36.2 mm	12 mm	yellow	50	**1055960000**
WAD 27	64 mm	27 mm	white	10	**1062960000**
WAD 27 lightning flash	64 mm	27 mm	yellow	10	**1062860000**

WAD Custom printing

Type	Length	Width	Material colour	Qty	Order No.
WAD 5 MC	33.5 mm	5 mm	white/yellow	12	**1112930000**
WAD 8 MC	33.5 mm	8 mm	white/yellow	12	**1112970000**

Accessories – WGB 5 / WGB 8

Type	Length	Width	Qty	Order No.
DEK 5/5 MC	5 mm	5 mm	1000	**1609801044**
DEK 5/30 MC	30 mm	5 mm	100	**1951920000**
DEK 5/30 MC SDR	5 mm	30 mm	40	**1025680000**
WS 12/5 MC	12 mm	5 mm	720	**1609860000**

The SCHT 5 & SCHT 5 S group marker carrier is clipped directly to the TS 32 DIN rail (G-rail) or the TS 35 DIN rail (top-hat rail). It is therefore possible to provide terminal strip labelling irrespective of the terminal and the type of terminal.

SchT 5 / SchT 5 S

Technical specification

Material	Polyamide 66
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C
Material colour	beige

Ordering data

Type	Length	Width	Qty	Order No.
SCHT 5	44.5 mm	19.5 mm	20	**0292460000**
SCHT 5 S	44.5 mm	9.5 mm	20	**1631930000**

Accessories

Technical specification

ESO...P	= Polyester
ESO	= Paper

Type	Length	Width	No. per sheet	Qty	Order No.
ESO 5 white	40 mm	16.5 mm	60	10	**1607710000**
ESO 5 yellow	40 mm	16.5 mm	60	10	**1631350000**
ESO 5P white	40 mm	16.5 mm	60	10	**1670370000**
ESO 5P yellow	40 mm	16.5 mm	60	10	**1670380000**
ESO 5 S white	40 mm	7 mm	140	10	**1631920000**
STR 5 F.SCHT 5	40 mm	16.5 mm	20	20	**0294000000**
STR 5 S. F.SCHT 5 S	40 mm	7 mm	20	20	**1631940000**
ELS 7/40 MC NE GE	40 mm	7 mm		40	**1045650000**
ELS 7/40 MC NE WS	40 mm	7 mm		40	**1045640000**
ELS 16/40 MC NE GE	40 mm	16 mm		40	**1045630000**
ELS 16/40 MC NE WS	40 mm	16 mm		40	**1045620000**

The SCHT 7 is a hinged group marker carrier for inlay tags which still allows easy access to the clamping screw. To equip with ESO 7, 4 tags of DEK 5/5 or 2 tags of WS 10/5 Middle.

SCHT 7

Technical specification

Material	Polyamide 66
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C
Material colour	white

Ordering data

Type	Length	Width	Qty	Order No.
SCHT 7	39.3 mm	8 mm	20	**0517960000**

Accessories

Technical specification

ESO...P	= Polyester
ESO	= Paper

Type	Length	Width	No. per sheet	Qty	Order No.
DEK 5/5 MC	5 mm	5 mm		1000	**1609801044**
ESO 7 white	27 mm	6.3 mm	240	10	**1607720000**
ESO 7 yellow	27 mm	6.3 mm	240	10	**1634780000**
ESO 7P white	27 mm	6.3 mm	240	10	**1670390000**
ESO 7P yellow	27 mm	6.3 mm	240	10	**1670400000**
STR 7 SCHT 7	27 mm	6.3 mm	20	20	**0515300000**
WS 10/5 MC middle	10 mm	5 mm		720	**1792000000**

MultiFit

MultiFit is Weidmüller's marker system for use with other makes of terminals with pitches of 4, 5, 6, 7.5, 8 and 10 mm.

- Blank markers ready for users to print with SMark-Laser, PrintJet, Plotter or MC-Mobilo
- Individually printed markers supplied based on customer CAE data or specifications
- One marker suitable for various terminal manufacturers



Technical data

Material	Polyamide 66, halogen-free
UL 94 flammability rating	V2
Temperature range	–40 °C to 100 °C
Printing	black

Ordering data

Colour	Available in all colours of the international colour code; for MC on request ● brown ● red ● orange ● yellow ● green ● blue ● violet ● grey O white
Special printing	Specify special printing and colours per diskette, Excel file or using the M-Print® PRO software.
Minimum order quantity	1 pack

Application options

	MF 8/5	MF 10/5 MF 10/6	MF 12/5	MF 5/4 MF 5/5 MF 5/6	MF-W 5/5 Mini	MF-W 9/4 MF-W 9/5 MF-W 9/6	MF-W 9/5 F MF-W 9/4.2 F MF-W 9/5.2 F MF-W 9/6.2 F
Wago	●		●		● Similar to the WagoMini WSB Type 248-...264-...	● Similar to the Wago WSB Type 209-...249-...	● Similar to the Wago WMB Type 793-...794-... For Wago TopJob S
Phoenix	●	●	●	● MF 5/5 Similar to the Phoenix Contact ZBF 5 MF 5/6 Similar to the Phoenix Contact ZBF 6 MF 5/4 Similar to the Phoenix ZBF 4			
Wieland	●	●	●				
Legrand	●	●	●		●	●	●
Entrelec	●	●	●		●		
Télémécanique	●	●	●				

	MF 10/8	MF 10/10	MF 4/5.2	MF 5/7.5	MF 10/5 MF 12/5	MF-SI	MF-WO	MFF
Siemens						●		
Phoenix	● ZB 8	● ZB 10	● BN-ZB 5.2	● BN-ZB 7.5				
Wieland								
Legrand								
Entrelec	●	●						
Woertz							●	
Adels RKW				● BZ 14				
Cabur					● Cabur			
Festo								●

● = OK

(Please select the marker according to the width of the terminal)

Please note:

The recommended applications given above do not release the user from his obligation to check the applicability in each individual application. The marker/terminal combination should in each case be chosen in such a way that either the marker pitch matches the terminal pitch, or the marker pitch is smaller than the terminal pitch.

Clamping width: 4.0 mm

Ordering data

MultiFit - blank

Type	Material colour	Length	Qty.	Order No.
MF 5/4 MC	white	5 mm	500	**1877690000**
MFF 9/4 MC	white	9 mm	500	**1877720000**
MF-W 9/4 MC	white	9 mm	500	**1877730000**
MF-W 9/4.2F MC	white	9 mm	500	**1011430000**

MultiFit - Custom printing

Type	Material colour	Length	Qty.	Order No.
MF 5/4 MC	white	5 mm	100	**1877670000**
MFF 9/4 MC	white	9 mm	100	**1877700000**
MF-W 9/4 MC	white	9 mm	100	**1877710000**
MF-W 9/4.2F MC	white	9 mm	100	**1038750000**

Clamping width: 5.0 mm

MultiFit - blank

Type	Material colour	Length	Qty.	Order No.
MF 4/5,2 MC	white	4 mm	500	**1907530000**
MF 5/5 MC	white	5 mm	500	**1816250000**
MF-W 5/5 MC Mini	white	5 mm	500	**1816240000**
MF-W 5/5 MC Mini GN	green	5 mm	500	**1924290000**
MF-W 5/5 MC Mini BL	Blue	5 mm	500	**1924270000**
MF-W 5/5 MC Mini GE	yellow	5 mm	500	**1924280000**
MF-W 5/5 MC Mini RT	red	5 mm	500	**1924260000**
MF-WO 5/5 MC	white	5 mm	400	**1716800000**
MF 8/5 MC	white	8 mm	600	**1677140000**
MF-SI 8/5 MC	white	8 mm	400	**1889180000**
MF-W 9/5 MC	white	9 mm	500	**1816270000**
MF-W 9/5F MC	white	9 mm	500	**1816280000**
MF-W 9/5.2F MC	white	9 mm	500	**1011410000**
MF-WO 9/5 MC	white	9 mm	400	**1716840000**
MF 10/5 MC	white	10 mm	600	**1677160000**
MF-SI 10/5 MC	white	10 mm	400	**1889190000**
MF 10/5 MC Cabur	white	10 mm	600	**1854510000**
MF 12/5 MC	white	12 mm	600	**1677180000**
MF-WO 12/5 MC	white	12 mm	400	**1692270000**
MF 12/5 MC Cabur	white	12 mm	600	**1854520000**

MultiFit - Custom printing

Type	Material colour	Length	Qty.	Order No.
MF 4/5.2 MC	white	4 mm	100	**1038690000**
MF 5/5 MC	white	5 mm	500	**1816320000**
MF-W 5/5 Mini MC	white	5 mm	500	**1816310000**
MF-WO 5/5 MC	white	5 mm	80	**1716810000**
MF 8/5 MC	white	8 mm	120	**1677150000**
MF-SI 8/5 MC	white	8 mm	80	**1886270000**
MF-W 9/5 MC	white	9 mm	500	**1816340000**
MF-W 9/5F MC	white	9 mm	500	**1816350000**
MF-WO 9/5 MC	white	9 mm	80	**1716850000**
MF-W 9/5.2F MC	white	9 mm	100	**1038760000**
MF 10/5 MC	white	10 mm	120	**1677170000**
MF-SI 10/5 MC	white	10 mm	80	**1889170000**
MF 10/5 MC CABUR	white	10 mm	120	**1038660000**
MF 12/5 MC	white	12 mm	120	**1677190000**
MF-WO 12/5 MC	white	12 mm	80	**1692280000**
MF 12/5 MC CABUR	white	12 mm	120	**1038670000**

Clamping width: 6.0 mm

Ordering data

MultiFit - blank

Type	Material colour	Length	Qty.	Order No.
MF 5/6 MC	white	5 mm	500	**1816260000**
MF-SI 8/6 MC	white	8 mm	320	**1889240000**
MF-W 9/6 MC	white	9 mm	500	**1816290000**
MF-W 9/6.2F MC	white	9 mm	500	**1011420000**
MF-WO 9/6 MC	white	9 mm	400	**1716820000**
MF 10/6 MC	white	10 mm	600	**1677220000**
MFF 10/6 MC	white	10 mm	600	**1856780000**
MF-SI 10/6 MC	white	10 mm	320	**1889260000**
MF-WO 12/6 MC	white	12 mm	400	**1692290000**

MultiFit - Custom printing

Type	Material colour	Length	Qty.	Order No.
MF 5/6 MC	white	5 mm	500	**1816330000**
MF-SI 8/6 MC	white	8 mm	64	**1889230000**
MF-W 9/6 MC	white	9 mm	500	**1816360000**
MF-WO 9/6 MC	white	9 mm	80	**1716830000**
MF-W 9/6.2F MC	white	9 mm	100	**1038770000**
MF 10/6 MC	white	10 mm	120	**1677230000**
MFF 10/6 MC	white	10 mm	120	**1856790000**
MF-SI 10/6 MC	white	10 mm	64	**1889250000**
MF-WO 12/6 MC	white	12 mm	80	**1692300000**

Clamping width: 6.5 / 7.5 mm

MultiFit - blank

Type	Material colour	Length	Qty.	Order No.
MF 5/ 7,5 MC	white	5	320	**1877680000**
MF-SI 7/5-6,5 MC	white	7	320	**1889780000**
MF-SI 10/5-6,5 MC	white	10	320	**1889800000**

MultiFit - Custom printing

Type	Material colour	Length	Qty.	Order No.
MF 5/7,5 MC	white	5	64	**1877660000**
MF-SI 7/5-6,5 MC	white	7	64	**1889770000**
MF-SI 10/5-6,5 MC	white	10	64	**1889790000**

Clamping width: 8.0 / 10.0 mm

MultiFit - blank

Type	Material colour	Length	Qty.	Order No.
MF 5/10 MC	white	5	250	**1954050000**
MF 10/8 MC	white	10	350	**1868440000**
MF 10/10 MC	white	10	200	**1856760000**

MultiFit - Custom printing

Type	Material colour	Length	Qty.	Order No.
MF 5/10 MC	white	5	50	**1038730000**
MF 10/8 MC	white	10	70	**1868430000**
MF 10/10 MC	white	10	40	**1856770000**

Clamping width: 12 mm

MultiFit - blank

Type	Material colour	Length	Qty.	Order No.
MF 5/12 MC	white	5	250	**1250090000**

MultiFit - Custom printing

Type	Material colour	Length	Qty.	Order No.
MF 5/12 MC	white	5	50	**1250080000**

Cross-reference table

Phoenix

	MF 5/4	MF 5/5	MF 8/5	MF 10/5	MF 12/5	MF 5/6	MF 10/6	MF 10/8	MF 10/10	MF 5/7,5	MF 4/5,2
AKG 16…							X				
AKG 35…							X				
AKG 4			X	X	X						
DFK 4…							X				
DFK 5…							X				
DIK 1,5…						X	X				
DIKD 1,5…						X	X				
DLK.. 2,5…						X	X				
DOK 1,5…						X	X				
DT 6/2,5-DREH…									X		
DTI 2,5 …		X	X	X							
DTI 4 …						X	X				
DTI 6 …								X			
DTME.. 6 …								X			
DTN 2,5 …		X	X	X							
DTN 4 …						X	X				
DTN 6 …								X			
EC-E…		X									
GE 10…									X		
GE 35…									X		
GTF 76/…									X		
HDFK 10								X			
HDFK 16									X		
HDFK 25									X		
HDFK 4							X				
HDFK 50/…									X		
HDFK 95									X		
HV M5/…									X		
HV M6/…									X		
HV M8/…									X		
HV M10/…									X		
HV M12/…											
IL…						X					
IB…						X					
MKB …											X
MBK 2,5/E…											X
MBK 3…											X
MBK 3/E-Z…		X	X	X	X						
MBK 5…											X
MBK 5/E-…											X
MBK 5/E-Z…						X	X				
MBK 6/E…								X			
MBKKB 2,5…		X	X	X	X						
MSB 2,5 …		X									
MSDB 2,5 …		X									
MSBV 2,5 …		X									
MSDBV 2,5 …		X									
MSLKG 2,5										X	
MSLKG 5										X	
MSLKG 6								X			
MT 1,5…	X										
MTK …		X	X	X	X						
MTKD-…									X		
MTTB 1,5…	X										
MZB 1,5….		X									
MZDB 1,5….		X									
MZFK 1,5…		X									
MZFKK 1,5 …		X									
MZFKKB 1,5		X									
OTTA 2,5								X			
OTTA 25									X		
OTTA 6…									X		
PCVK 4-7,62 …						X	X				
PIK 4-…						X	X				
PIK 6-…								X			
PIT 2,5 …		X									
PITTB 2,5 …		X									
PITTBS 2,5 …		X									
PIT 2,5-3 …		X									
PIT 2,5-PE/../..		X									
PP-H 2,5/…		X									
PVB…							X				
QP 1,5/..		X									
QTC 1,5 …		X	X	X							
QTC 2,5 …						X	X				
QTC 2,5-HE..I …						X					
QTCS 1,5 …		X	X	X							
QTCS 2,5 …						X	X				

	MF 5/4	MF 5/5	MF 8/5	MF 10/5	MF 12/5	MF 5/6	MF 10/6	MF 10/8	MF 10/10	MF 5/7,5	MF 4/5,2
QTCU 1,5 …		X	X	X							
QTCU 2,5 …						X	X				
QTTCB 1,5 …		X									
QTTCBS 1,5 …		X									
RT 3…									X		
RT 5…									X		
RT 8…									X		
RTO 3…									X		
RTO 5…									X		
RTO 8…									X		
RV 8-TP …							X				
RVS 10-TP…							X				
SC 2,5…		X									
SC 4…						X					
SGSK 6								X			
SP 2,5/…		X									
SP.. 2,5/…		X									
SP 4/…						X					
SLKK 5…						X	X				
SRDK 6								X			
SRTK 6								X			
SSL 2,5		X									
ST 1,5…	X										
ST 2,5….		X	X								
ST 2,5-3…		X									
ST 2,5-PCB…		X									
ST 2,5-PE/../..		X									
ST 2,5-4…		X									
ST 4….						X					
ST 4-PE/…						X					
ST 4-HE..I…						X					
ST 4-FSI/C …								X			
ST 4-PCB…						X					
ST 6 …						X					
ST 10 …						X					
ST 16 …						X					
ST 35 …						X					
STI 10…		X									
STI 16…						X					
STI 2,5…		X	X	X							
STI 2,5-PE/../..		X	X	X	X						
STI 2,5-L …		X	X	X	X						
STI 4…						X	X				
STIO 2,5/3-…		X									
STIO-IN 2,5/3…		X									
STIO 2,5/4-…						X					
STIO-IN 2,5/4…						X					
STME .. 6 …								X			
STN 10									X		
STN 16						X					
STN 2,5		X									
STN 35									X		
STN 4						X					
STS 2,5…		X	X	X	X						
STS 4…						X	X				
STS 6…								X			
STTB 1,5…	X										
STTB 2,5…		X									
STTB 4…						X					
STTBS 2,5 …		X	X	X							
STTBS 4-…						X	X				
STU 2,5-TWIN …		X	X								
STU 4-TWIN …						X					
STU 10/ …						X					
STU 35/ …						X					
STTBU 4 …						X					
TCP…		X									
TMC…							X				
TMCP-CONNECT-LR							X				
TMCP-SOCKET-M							X				
TRK 4 (pitch 7.5)										X	
TT-STTB-…							X				
UDK 3…		X	X	X	X						
UDK 4…						X	X				
UDK 4-MTK						X	X				
UDK 5-MTK						X	X				
UDMTK 5….						X	X				
UGSK 6								X			

Individual mounting is required if the terminal pitch is larger than the marker.

Phoenix

	MF 5/4	MF 5/5	MF 8/5	MF 10/5	MF 12/5	MF 5/6	MF 10/6	MF 10/8	MF 10/10	MF 5/7,5	MF 4/5,2
UGSK/S								X			
UHK 4-FS…						X	X				
UHV 150-…									X		
UHV 240-…									X		
UHV 25-…									X		
UHV 50-…									X		
UHV 95-…									X		
UIK 16…									X		
UIK 35…									X		
UISLKG 16…									X		
UISLKG 35…									X		
UK 1,5 N…	X										
UK 10 N									X		
UK 10,3-… HESI…									X		
UK 10-DRHESI…							X				
UK 16 N									X		
UK 2,5 N		X	X	X	X						
UK 3 N		X	X	X	X						
UK 35									X		
UK 35 N…									X		
UK 4…						X	X				
UK 5 N						X	X				
UK 5-HESI								X			
UK 5-MTK…						X	X				
UK 6 N								X			
UK 6,3-HESI									X		
UK 6-FSI/C…								X			
UKB 4 …							X				
UKH 150 …									X		
UKH 240 …									X		
UKH 50 …									X		
UKH 95 …									X		
UKK 3…		X	X	X	X						
UKK 4-FS…						X	X				
UKK 5…						X	X				
UKKB 3…		X	X	X	X						
UKKB 5…						X	X				
UKKB 10									X		
UKKB 10/2,5		X	X	X	X				X		
UKN 10 N…									X		
UKN 16 N…									X		
UKN 2,5…						X	X				
UKN 35…									X		
UKN 5…						X	X				
UKN 6 N…								X			
UK-SI								X			
URDK 6								X			
URKN									X		
URKN/S								X			
URTK 6								X			
URTK/S								X			
URTK/S-BEN …								X			
URTK/SP								X			
URTK/SS						X	X				
URTKD/SP								X			
UP 4/…						X					
UPBV 2,5/…		X									
UPBV 4/…						X					
UPCV3K …						X	X				
USED 16									X		
USED 27									X		
USEN 14									X		
USEN 18									X		
USIG…									X		
USK 4-FS…						X	X				
USKLG 1,5 N	X										
USKLG 10 N…									X		
USKLG 16 N…									X		
USKLG 2,5 N…		X	X	X	X						
USKLG 3…		X	X	X	X						
USKLG 35									X		
USLKG 35 N									X		
USKLG 5…						X	X				
USKLG 50									X		
USKLG 6 N…								X			
USKLG 95									X		
UT 10 …									X		
UT 16 …									X		

	MF 5/4	MF 5/5	MF 8/5	MF 10/5	MF 12/5	MF 5/6	MF 10/6	MF 10/8	MF 10/10	MF 5/7,5	MF 4/5,2
UT 35 …									X		
UT 2,5 …			X	X	X						
UT 4 …							X				
UT 4-HEDI …						X	X				
UT 4-HESI …						X	X				
UT 4-PE/…						X	X				
UTME .. 6 …								X			
UTTB 2,5-…		X	X	X	X						
UTTB 4-…						X	X				
UT 6 …								X			
UT 6-TMC M…									X		
UTI 16 …									X		
UTI 35 …									X		
UTN 2,5		X	X	X	X						
UTN 4						X	X				
UTN 6								X			
UTN 10									X		
UTN 16									X		
UTN 35									X		
UVKB 4-FS…						X	X				
VBSN 4							X				
VBST 4-FS...						X	X				
VKK 4-FS						X	X				
VIOK 1,5…						X	X				
W 80/…							X				
ZDIK 1,5…		X									
ZDMTK 2,5…						X					
ZFK 6-DREHSI…						X					
ZFKK 2,5-MT…		X									
ZGSK 4								X			
ZPV 1,5/2,5		X	X	X	X						
ZRTK 4								X			
ZRV 8						X	X				
ZVIOK 1,5…		X									

Individual mounting is required if the terminal pitch is larger than the marker.

WAGO

	MF-W 9/4	MF-W 5/5 mini	MF-W 9/5	MF-W 9/5 F	MF-W 9/6
Feed-through terminals					
264-701/704/706		X			
264-711/714/716		X			
264-721/724/726		X			
264-731/734/736		X			
264-120/125/220/225		X			
279-101/104	X				
279-604/621	X				
279-626/826	X				
279-681…686	X				
279-831…836	X				
279-901…906	X				
279-989…995	X				
280-101/104	X				
280-601/602		X	X	X	
280-603/633/634		X	X	X	
280-604/621/826/626		X	X	X	
280-641/651/654		X	X	X	
280-646/656/946		X	X	X	
280-653/671/672		X	X	X	
280-681/684/650		X	X	X	
280-830…835		X	X	X	
280-901…906		X	X	X	
280-989…995		X	X	X	
280-996…999		X	X	X	
280-691		X	X	X	
281-101/104					X
281-601/604					X
281-631/651					X
281-652…654					X
281-663/664/668					X
281-678/681/684					X
281-901/902/904					X
281-992..994/998/691					X
282-101/104					X
282-601/604					X
282-681/682/684					X
282-901/902/904					X
282-992/993/691					X
283-101/104					X
283-601/604					X
283-671/672/674					X
283-901/902/904					X
283-992/998/691					X
284-101/104					X
284-601/604					X
284-621/624					X
284-681/682/684					X
284-691/992/993					X
284-901/902/904					X
285-194/195					X
285-601/604/607					X
285-634/635		X			X
285-691					X
285-992/995					X
290-861/864/867		X	X	X	
780-601/602/604			X	X	
780-631/651/654			X	X	
780-992/993			X	X	
781-601/604					X
781-631/651					X
781-992/993					X
782-601/604					X
782-992					X
783-601/604					X
783-992					X
784-601/604					X
784-992					X
785-601/604/613					X
792-… all		X			
812-140			X	X	X
859-…all		X			
870-681/682/684		X		X	
870-831/832/834		X		X	
870-901/902/904		X		X	
870-911/912/914		X		X	
880-661/662/664		X	X	X	

	MF-W 9/4	MF-W 5/5 mini	MF-W 9/5	MF-W 9/5 F	MF-W 9/6
880-681/682/684		X	X	X	
880-831/832/834		X	X	X	
880-901/902/904		X	X	X	
880-961/964/962		X	X	X	
Protective earth terminals					
264-727		X			
264-737		X			
279-687	X				
279-837	X				
279-907	X				
280-107		X	X	X	
280-607		X	X	X	
280-637		X	X	X	
280-677		X	X	X	
280-687		X	X	X	
280-837		X	X	X	
280-907		X	X	X	
281-107					X
281-607					X
281-637					X
281-657					X
281-687					X
281-907					X
282-107					X
282-607					X
282-687					X
282-907					X
283-607					X
283-609					X
283-677					X
283-907					X
284-107					X
284-607					X
284-687					X
284-907					X
285-197					X
285-607		X			X
285-637		X			X
780-607			X	X	
780-637			X	X	
780-637					X
781-607					X
782-607					X
783-607					X
784-607					X
785-607					
870-687		X		X	
870-837		X		X	
870-907		X		X	
870-917		X		X	
880-687		X	X	X	
880-837		X	X	X	
880-907		X	X	X	
Fuse terminals					
282-698					X
282-696					X
281-611/612/616/622					X
281-624/672					X
281-613/623					X
282-122					X
282-120					X
282-126					X
282-124					X
282-128					X
Two-tier terminals					
279-501/512/513	X				
279-504	X				
279-507	X				
279-508	X				
279-509	X				
279-517/527	X				
280-513		X	X	X	
280-517		X	X	X	
280-519/529		X	X	X	
280-520/530		X	X	X	

	MF-W 9/4	MF-W 5/5 mini	MF-W 9/5	MF-W 9/5 F	MF-W 9/6
280-521/525		X	X	X	
280-522/526		X	X	X	
280-523/533		X	X	X	
280-524/534		X	X	X	
280-527/537		X	X	X	
280-531		X	X	X	
280-532		X	X	X	
280-543		X	X	X	
281-619/629					X
281-620/630					X
870-101…104		X	X	X	
870-107		X	X	X	
870-108		X	X	X	
870-117/127		X	X	X	
870-501…504		X	X	X	
870-507		X	X	X	
870-508/509		X	X	X	
870-517/527		X	X	X	
870-531…534		X	X	X	
870-535/536		X	X	X	
870-537		X	X	X	
870-538/538		X	X	X	
870-826		X	X	X	
Three- and four-tier terminals					
280-549/551		X	X	X	
280-550		X	X	X	
280-552		X	X	X	
280-547/557/597		X	X	X	
280-548/558		X	X	X	
281-531/532					X
870-551/553		X		X	
870-556		X		X	
870-558/559/567/577		X		X	
870-557		X		X	
281-530					X
Routing and potential terminals					
727-… all					X
280-675			X		
Honeycomb elements					
726-… all			X		
Single terminals					
264-130/131		X			
264-230/231		X			
264-180/280		X			
Pluggable relays and bases					
286-… all	X				
786-… all	X				
788-… all			X		X
789-… all		X			
Multi-tier terminals					
775-641			X	X	
775-642/649			X	X	
775-646			X	X	
775-645			X	X	
777-641					X
777-642					X
777-646					X
777-645					X
777-648					X
777-647					X
777-649					X
777-651					X
777-650					X
777-652					X
776-641					X
776-645/646					X
776-649/642					X
776-650/651					X
Disconnect test terminals					
280-612/614			X	X	
280-622/623/627			X	X	

The markers must be mounted individually when the terminal pitch is larger than 6.2 mm.

WAGO

	MF-W 9/4	MF-W 5/5 mini	MF-W 9/5	MF-W 9/5 F	MF-W 9/6
280-649/676/685/695			X	X	
280-683			X	X	
280-805/836/829/839			X	X	
280-868/870/876/879		X	X		
280-869/871/880		X	X		
280-874/881/883/885		X	X		
280-875/882/884		X	X		
280-912…914			X		
281-659/660					X
281-666					X
281-683					X
281-912					X
282-131					X
282-133					X
282-135					X
282-138…141					X
282-694/699					X
282-811/821		X			X
282-860					X
282-865					X
282-866/695/697					X
282-870					X
781-613/623					X
781-643/653					X
782-613/623					X
783-613/623					X
784-613/623					X

Initiator terminals

	MF-W 9/4	MF-W 5/5 mini	MF-W 9/5	MF-W 9/5 F	MF-W 9/6
270-560/564		X			
270-570/574		X			
270-572/577		X			
270-585/586		X			
280-553/560		X	X	X	
280-559		X	X	X	
280-561		X	X	X	
280-563		X	X	X	
280-564		X	X	X	
280-567		X	X	X	
280-570		X	X	X	
280-571		X	X	X	
280-573		X	X	X	
280-574		X	X	X	
280-577		X	X	X	
280-580		X	X	X	
280-582		X	X	X	
280-583		X	X	X	
280-584		X	X	X	
280-588		X	X	X	

Actuator terminals

	MF-W 9/4	MF-W 5/5 mini	MF-W 9/5	MF-W 9/5 F	MF-W 9/6
280-515		X	X	X	
280-554		X	X	X	
280-555		X	X	X	
280-556		X	X	X	
280-562		X	X	X	
280-565		X	X	X	
280-566		X	X	X	
280-568		X	X	X	
280-572		X	X	X	
280-575		X	X	X	
280-576		X	X	X	
280-578		X	X	X	
280-583		X	X	X	
280-585		X	X	X	
280-586		X	X	X	
280-592		X	X	X	
280-593		X	X	X	

Diode and LED terminals

	MF-W 9/4	MF-W 5/5 mini	MF-W 9/5	MF-W 9/5 F	MF-W 9/6
279-620	X				
279-623	X				
279-624	X				
279-673	X				
279-674	X				
279-809	X				
279-815	X				
279-915	X				
280-613			X	X	
280-615			X	X	
280-623			X	X	
280-624			X	X	
280-655			X	X	
280-658			X	X	
280-673			X	X	
280-809			X	X	
280-815			X	X	
280-915			X	X	
280-940			X	X	
280-941			X	X	
280-942			X	X	
280-943			X	X	
281-603					X
281-633					X
281-634					X
281-635					X
281-636					X
281-665					X
281-673					X
281-915					X
870-540		X	X	X	
870-541		X	X	X	
870-542		X	X	X	
870-543		X	X	X	
870-590		X	X	X	
870-593		X	X	X	
870-596		X	X	X	

X-Com system

	MF-W 9/4	MF-W 5/5 mini	MF-W 9/5	MF-W 9/5 F	MF-W 9/6
769-… all		X			

WAGO I/O modules TOPLON

	MF-W 5/5 mini	MF 5/10		ESG 8/11
750-… all	X	X		X

Wago TOPJOB S

	MF-W 9/4,2 F	MF-W 9/5,2 F	MF-W 9/6,2 F		
2001-12..	X				
2001-13..	X				
2001-14..	X				
2002-12..		X			
2002-13..		X			
2002-14..		X			
2002-16..		X			
2002-18..		X			
2002-22..		X			
2002-29..		X			
2002-32..		X			
2002-63..		X			
2002-64..		X			
2002-71..		X			
2003-76..		X			
2004-12..			X		
2004-13..			X		
2004-14..			X		
2005-76..			X		
2006-12..			X		
2006-13..			X		
2006-71..			X		
2010-12..			X		
2010-13..			X		
2016-12..			X		
2016-13..			X		
2016-71..			X		

The markers must be mounted individually when the terminal pitch is larger than 6.2 mm.

ABB-Stotz/ Entrelec

	MF-W 9/4	MF-W 9/5	MF-W 9/5 F	MF-W 9/6	MF-W 9/6.2 F	MF-W 5/5 mini	MF 10/5	MF 10/6	MF 10/8	MF 10/10
131 ET TM4…						x				
165 LT TM5…						x				
41 H LT…						x				
62 H…				x						
BADH				x						
BADL				x	x			x		
BADRL				x	x	x		x		
BAEH				x						
BAM…				x	x			x		
BAMH				x	x			x		
D 1,5/4…	x									
D 1,5/6…				x						
D 1,5/6…ADO…				x						
D 1,5/8…ADO				x						
D 1/5…ADO		x								
D 10/10…						x				
D 150/31…				x	x					
D 16/12…						x				
D 2,5/5.P…		x	x							
D 2,5/5…						x				
D 2,5/5…ADO		x								
D 2,5/6…						x				
D 2,5/8…						x				
D 2,5/8…ADO…				x						
D 240/36…				x	x					
D 35/16…						x				
D 4/6.P…				x	x			x		
D 4/6…						x				
D 4/6…ADO		x								
D 4/6…ADO				x						
D 4/8…				x						
D 4/8…ADO…				x						
D 6/10…				x	x			x	x	x
D 6/8.P				x	x				x	
D 6/8.ST…				x	x				x	
D 6/8…						x				
D 6/8…ADO…				x						
D 70/22…				x	x					
DB 1,5/6…						x				
DB 1/5…						x				
DB 2,5/5…						x				
DB 2,5/8…						x				
DB 4/6…						x				
DB 4/8…						x				
DF 6				x				x		
DH 1,5/6…						x				
DH 1/5…						x				
DH 2,5/5…						x				
DH 2,5/8…						x				
DH 4/6…						x				
DH 4/8…						x				
DL 10/17,5…						x				
DR 1,5/4…	x									
DR 1,5/5…						x				
DR 1,5/6…						x				
DR 1/5…						x				
DR 2,5/10…						x				
DR 2,5/5…						x				

	MF-W 9/4	MF-W 9/5	MF-W 9/5 F	MF-W 9/6	MF-W 9/6.2 F	MF-W 5/5 mini	MF 10/5	MF 10/6	MF 10/8	MF 10/10
DR 2,5/8…						x				
DR 4/6…						x				
DR 4/8…				x	x				x	
DR 4/8…ADO…						x				
DS 1,5/6…						x				
DS 1/5…						x				
DS 2,5/5…						x				
DS 2,5/8…						x				
DS 4/6…						x				
DS 4/8…						x				
HD 10/12…		x								
HD 120/30…		x								
HD 16/14…		x								
HD 185/36…		x								
HD 2,5/6…				x						
HD 35/16…		x								
HD 4/9…		x								
HD 6/14…				x						
HD 6/8…				x						
HD 6/9…				x						
HD 70/22…		x								
M 1,5/6…				x				x		
M 10/10…				x	x					x
M 10/16…				x	x			x	x	x
M 16/12.PE.N				x						
M 16/12…				x	x			x	x	x
M 2,5/6,5…						x				
M 2,5/6…						x				
M 35/16…				x	x			x	x	x
M 4/6…				x				x		
M 4/6…AP…				x						
M 4/7…				x	x			x		
M 4/8…				x	x				x	
M 6/12…				x						
M 6/13…				x						
M 6/8…				x	x				x	
M 70/22…				x	x			x	x	x
M 95/26…				x	x			x	x	x
MA 2,5/5…		x	x				x			
MB 10/10…				x	x					x
MB 10/12 SF….				x						
MB 10/22…		x								
MB 10/24…		x						X	X	X
MB 25/30…				x	x			x	x	x
MB 4/6…				x				x		
MB 6/8…				x	x				x	
MB 70/10…				x	x					x
ML 10/13…				x	x					x
MS 4/6…				x	x			x		
MS 6/8…				x	x				x	
MTC 6				x				x		
MU 10/13…				x	x					x
MU 10/14,5…				x	x					x
T 1,5/6…				x		X				
T 2,5/5…		x								
T 2,5/6…				x						
T 4/6…				x						

Wieland

	MF 8/5	MF 10/5	MF 12/5	MF 10/6
9700 A/5…	X	X	X	
9700 A/6…				X
9700 A/8…				X
9700 A/10…				X
9700 A/12…				X
9700 A/16…				X
9700 B…				X
9701 A/6…A/16				X
9708/2 …				X
9760 U…				X
9785 U…				X

	MF 8/5	MF 10/5	MF 12/5	MF 10/6
9786 U…				X
AKB…	X	X	X	
AKT…	X	X	X	
flare Move … (6,2mm)				X
Terminal adapter revos Basic	X	X	X	
Terminal adapter revos HD	X	X	X	
Terminal adapter revos Power	X	X	X	
RV2../…	X	X	X	
UET..	X	X	X	
WEB…	X	X	X	
WEF 1…				X

Individual mounting is required if the terminal pitch is larger than the marker.

Wieland

	MF 8/5	MF 10/5	MF 12/5	MF 10/6
WEG…	X	X	X	
WK 2,5…	X	X	X	
WK 2,5-4 KI…	X	X	X	
WK 2,5-4 KOI…	X	X	X	
WK 2,5-3 D…	X	X	X	
WK 2,5 U/D…	X	X	X	
WK 4…				X
WK 4 D…				X
WK 4 E…				X
WK 4/SI-D…				X
WK 4 TK…				X
WK 4 THSI …				X
WK 6…				X
WK 10/SI…				X
WKC 1 …	X	X		
WKC 2,5 …				X
WKC 1 TKG…	X	X		
WKC 2,5 TKG…				X
WKN 10…				X
WKN 16…				X
WKN 2,5 E…	X	X	X	
WKN 35…				X
WKN 4 …				X
WKN 70…				X
WK/3-6…				X
WK/4-8…				X
WKB 2,5…	X	X	X	
WKF 1,5 E…	X	X	X	
WKF 1,5 KOI…	X	X	X	
WKF 10...				X
WKF 16...				X
WKF 35…				X
WKF 2,5...	X	X	X	
WKF 2,5 D…	X	X	X	
WKF 2,5/M…	X	X	X	
WKF 4...				X
WKF 4 TK...				X
WKF 6...				X
WKFN 2,5…	X	X	X	
WKFN 2,5 E...	X	X	X	
WKFN 4…				X
WKFN 4 E…				X
WKI 10…				X
WKI 16…				X
WKI 35…				X
WKI 4…				X
WKIF 2,5 …	X	X	X	
WKM 2,5…	X	X	X	
WKMF 2,5../1,5	X	X	X	
WKM 4…				X

Cabur

	MF 10/5 Cabur	MF 12/5 Cabur
AFO.2…	X	X
CAM…	X	X
CBC.2… - CBC.35…	X	X
CBD.2… - CBD.70…	X	X
CBE.2…	X	
CBR.2…	X	X
CNT.16…	X	X
CNT.35…	X	X
CNT.6…	X	X
CVF.4…	X	X
DAS.4…	X	X
DBC.2…	X	
DSFA.4	X	
DSS.4…	X	
FDP.2…	X	X
FFS.4…	X	X
FPC.10…	X	X
FPL.10…	X	X
FVS.4…	X	X
MAC.6…	X	X
MPFA.4…	X	
MPS.2…	X	X
MPS.4…	X	X
NCS…	X	X
NCV…	X	X
PDF.2…	X	X
RFI.2…	X	
RN.2…	X	
RP.4…	X	
SCB.4…	X	X
SCB.6…	X	X
SFO.4…	X	X
SFR.4…	X	X
SFR.6…	X	X
TC/PO…	X	X
TDE.2…	X	X
TE.10…	X	X
TE.16…	X	X
TE.50…	X	X
TE.6…	X	X
TEC.10…	X	X
TEC.16…	X	X
TEC.35…	X	X
TEC.6…	X	X
TEC.70…	X	X
TED.4…	X	X
TEO.2…	X	X
TEO.4…	X	X
TLD.2…	X	X
TLE.2	X	X
TLS.2…	X	X
TR.2…	X	
TR.4…	X	X
VPC.2…	X	X

Individual mounting is required if the terminal pitch is larger than the marker.

Siemens

	MF-SI 8/5	MF-SI 10/5	MF-SI 8/6	MF-SI 10/6	MF-SI 7/5-6,5	MF-SI 10/5-6,5	MF 5/4	MF 5/5	MF 8/5	MF 10/5	MF 12/5	MF 5/6	MF 10/6	MF 10/8	MF 10/10
8WA1 011-0DG…			x	x											
8WA1 011-1BF…	x	x													
8WA1 011-1BG…			x	x											
8WA1 011-1BH…			x	x											
8WA1 011-1BK…			x	x											
8WA1 011-1BM…			x	x											
8WA1 011-1BP…			x	x											
8WA1 011-1DF…	x	x													
8WA1 011-1DG…			x	x											
8WA1 011-1DH…			x	x											
8WA1 011-1EE…			x	x											
8WA1 011-1EF…	x	x													
8WA1 011-1MH…			x	x											
8WA1 011-1NF…	x	x													
8WA1 011-1NG…			x	x											
8WA1 011-1NH…			x	x											
8WA1 011-1PF…	x	x													
8WA1 011-1PG…			x	x											
8WA1 011-1PH…			x	x											
8WA1 011-1PK…			x	x											
8WA1 011-1PM…			x	x											
8WA1 011-1SF…			x	x											
8WA1 011-2BG11					x	x									
8WA1 011-2DG11					x	x									
8WA1 011-3DF…	x	x													
8WA1 011-3DG…			x	x											
8WA1 011-3DH…			x	x											
8WA1 011-3JF…	x	x													
8WA1 011-6BG11					x	x									
8WA1 011-6DG11					x	x									
8WA1 011-6EG…					x	x									
8WA1 204			x	x											
8WA1 205			x	x											
8WA1 206			x	x											
8WA1 221	x	x													
8WA1 232			x	x											
8WA1 304			x	x											
8WA1 305			x	x											
8WA1 501	x	x													
8WA1 604			x	x											
8WA2 011-…NK23			x	x											
8WA2 011-1BF….	x	x													
8WA2 011-1BG…			x	x											
8WA2 011-1BH…			x	x											
8WA2 011-1BJ…			x	x											
8WA2 011-1BK…			x	x											
8WA2 011-1DF…	x	x													
8WA2 011-1DG…			x	x											
8WA2 011-1DH…			x	x											
8WA2 011-1DJ…			x	x											
8WA2 011-1DK…			x	x											
8WA2 011-1EF20	x	x													
8WA2 011-1LF20	x	x													
8WA2 011-1NG23			x	x											
8WA2 011-1NH23			x	x											
8WA2 011-1PF…	x	x													
8WA2 011-1PG…			x	x											
8WA2 011-1PH…			x	x											
8WA2 011-1PJ…			x	x											
8WA2 011-1PK…			x	x											
8WA2 011-2BG…			x	x											
8WA2 011-2DG…			x	x											
8WA2 011-3JG…			x	x											
8WA2 011-3JH23			x	x											
8WA2 011-3KE	x	x													
8WA2 011-6EG…			x	x											
8WA9 200			x	x											
8WH1 000-0AN…					x	x									
8WH1 000-0AQ…					x	x									
8WH1 000-0AS…					x	x									
8WH1 000-0AU…					x	x									
8WH1 000-0CN…					x	x									
8WH1 000-0CQ…					x	x									
8WH1 001-0…K…															x
8WH1 001-0…M…															x
8WH1 001-0BJ…															x
8WH1 001-0BJ…															x
8WH1 001-0BJ…															x

Individual mounting is required if the terminal pitch is larger than the marker.

Siemens

	MF-SI 8/5	MF-SI 10/5	MF-SI 8/6	MF-SI 10/6	MF-SI 7/5-6,5	MF-SI 10/5-6,5	MF 5/4	MF 5/5	MF 8/5	MF 10/5	MF 12/5	MF 5/6	MF 10/6	MF 10/8	MF 10/10
8WH1 060-0A…00					x	x									
8WH1 070-0A…					x	x									
8WH2 …-6AF…								x	x	x					
8WH2 …-6AG…												x	x		
8WH2 …-6CF…								x	x	x					
8WH2 …-6CG…												x	x		
8WH2 00...-0AE…							x								
8WH2 00...-0AF…								x	x	x					
8WH2 00...-0AG…												x	x		
8WH2 00...-0CE…							x								
8WH2 00...-0CF…								x	x	x					
8WH2 00...-0CG…												x	x		
8WH2 00…-0AH…														x	
8WH2 00…-0AJ…														x	
8WH2 00…-0AK…														x	
8WH2 00…-0AM…														x	
8WH2 00…-0CH…														x	
8WH2 000-1AG…														x	
8WH2 000-1BG…														x	
8WH2 000-1GG…												x	x		
8WH2 000-1HG…														x	
8WH2 000-1JG…												x	x		
8WH2 000-1MG…												x	x		
8WH2 000-1NG…														x	
8WH2 000-1RG…														x	
8WH2 003-5…F…								x	x						
8WH2 02…-0AE…							x								
8WH2 02…-0AF…								x	x						
8WH2 02…-0AG…												x	x		
8WH2 02…-0CE…							x								
8WH2 02…-0CF…								x	x						
8WH2 02…-0CG…												x	x		
8WH2 02…-4...F…								x	x						
8WH2 020-5…F…								x	x						
8WH2 03…-0...F…								x	x						
8WH2 04…-0...F…								x	x						
8WH2 040-4L…								x	x						
8WH2 103-...BF…								x	x	x					
8WH2 103-...BG…												x	x		
8WH2 50…-0…F…								x	x						
8WH2 50…-0…G…												x	x		
8WH2 50…-0…H…														x	
8WH2 50…-6...F…								x	x						
8WH2 520-0…F…								x	x						
8WH2 520-0…G…												x	x		
8WH3 00…-0…E…								x	x	x					
8WH3 00…-0…F…												x	x		
8WH3 000-6AE…								x	x	x					
8WH3 000-6AF…												x	x		
8WH3 000-6CF…												x	x		
8WH3 020-…E…								x							
8WH3 1…-2…E…								x	x	x					
8WH3 1…-2…F…												x	x		
8WH3 1…-3…E…								x	x	x					
8WH3 1…-3…F…												x	x		
8WH4 00...-0…F…								x	x	x					
8WH4 00...-0…G…												x	x		
8WH4 00...-0…H…														x	
8WH4 001-…F…									x	x					
8WH5 00...-0...F…								x	x	x					
8WH5 10...-...F…								x	x	x					
8WH5 100-…KG…												x	x		
8WH5 103-6...F…								x	x	x					
8WH5 12…-…MF…								x							
8WH9 040-1AB…								x							
8WH9 040-1BB…								x							
8WH9 040-1CB…								x							
8WH9 040-1DB…								x							
8WH9 040-1EB…								x							
8WH9 040-1FB…								x							
8WH9 050-0AB…															
8WH9 050-0LB…								x							
8WH9 050-1KB…												x			
8WH9 050-1LB…												x			
8WH9 050-1MB…												x			
8WH9 150-0CA00					x	x									

Beckhoff

	MF-W 5/5 mini	ESG 8/11	MF 5/10
I/O modules	X	X	X

Adels

	MF 5/7,5
RKV Transformer terminal	X

Individual mounting is required if the terminal pitch is larger than the marker.

Allen-Bradley

	MF-WO 5/5	MF-WO 9/5	MF-WO 12/5	MF-WO 9/6	MF-WO 12/6	DEK 5/3,5	DEK 5/5	DEK 5/6	DEK 5/8	WS 12/3,5	WS 8/5	WS 10/5	WS 10/5 m.	WS 12/5	WS 15/5	WS 10/6	WS 10/6 m.	WS 12/6	WS 12/6,5	Ws 12/6,5	ZS 10/5	ZS 12/6	ZS 15/5
1492-J10…							X												X				
1492-J16…							X												X				
1492-J2Q…							X							X									
1492-J3…							X							X									
1492-J35…							X												X				
1492-J3F…							X							X									
1492-J3P…							X							X									
1492-J3PTP…							X							X									
1492-J3TW…							X							X									
1492-J4…								X										X					
1492-J4M…								X										X					
1492-J50…							X												X				
1492-J6…									X										X				
1492-J70…							X												X				
1492-JC3…							X							X									
1492-JD3…							X				X												
1492-JD3C…							X				X												
1492-JD3DF…							X				X												
1492-JD3DR…							X				X												
1492-JD3F…							X				X												
1492-JD3P…							X						X										
1492-JD3PSS…							X						X										
1492-JD3PSSTP							X						X										
1492-JD3PTP…							X						X										
1492-JD3RB…							X				X												
1492-JD3RC001							X				X												
1492-JD3SS…							X				X												
1492-JDC3…							X							X									
1492-JDG3…							X				X												
1492-JDG3C…							X				X												
1492-JDG3P…							X						X										
1492-JDG3PSS…							X						X										
1492-JDG3PSSTP							X						X										
1492-JDG3PTP…							X						X										
1492-JG10…									X										X				
1492-JG16…									X										X				
1492-JG2Q…							X							X									
1492-JG3…							X							X									
1492-JG35…									X										X				
1492-JG3TW…							X							X									
1492-JG4…								X										X					
1492-JG50…									X										X				
1492-JG6…									X										X				
1492-JG70…									X										X				
1492-JKD3…							X							X									
1492-JKD3TP…							X							X									
1492-JPO…								X										X					
1492-JTC3…							X							X									
1492-K2…													X										
1492-K3…																	X						
1492-KG2…													X										
1492-KG3…																	X						
1492-KW2…													X										
1492-KW3…																	X						
1492-L10…									X									X					X
1492-L16…									X										X				X
1492-L16D…									X										X				X
1492-L2…						X				X													
1492-L2Q…						X				X													
1492-L2T…						X				X													
1492-L3…							X					X									X		
1492-L35…									X										X				X
1492-L3P…							X					X											
1492-L3Q…							X					X									X		
1492-L3QS…							X					X											
1492-L3T…							X					X									X		
1492-L4…								X								X						X	
1492-L4Q…								X								X						X	
1492-L4T…								X								X						X	
1492-L6…									X									X				X	
1492-L6T…									X									X				X	
1492-LC3…							X					X											
1492-LD2…						X				x													
1492-LD2C…						X				X													
1492-LD3…							X					X											
1492-LD3C…							X					X											
1492-LD4…								X								X							
1492-LD4C…								X								X							

The markers must be mounted individually when the terminal pitch is larger than 6 mm.

Allen-Bradley

	MF-WO 5/5	MF-WO 9/5	MF-WO 12/5	MF-WO 9/6	MF-WO 12/6	DEK 5/3,5	DEK 5/5	DEK 5/6	DEK 5/8	WS 12/3,5	WS 8/5	WS 10/5	WS 10/5 m.	WS 12/5	WS 15/5	WS 10/6	WS 10/6 m.	WS 12/6	WS 12/6,5	Ws 12/6,5	ZS 10/5	ZS 12/6	ZS 15/5
1492-LD4DF…								X								X							
1492-LD4DR…								X								X							
1492-LD4RB…								X								X							
1492-LD4SS…								X								X							
1492-LDAG3…							X					X											
1492-LDC3…							X					X											
1492-LDG2…						X				X													
1492-LDG3…							X					X											
1492-LDG3P…							X					X											
1492-LDG4…								X								X							
1492-LG10…									X									X					X
1492-LG16…									X										X				X
1492-LG2…						X				X													
1492-LG3…							X					X									X		X
1492-LG35…									X										X				X
1492-LG4…								X								X						X	
1492-LG6…									X									X				X	
1492-LKD3…							X					X											
1492-LM3…							X					X									X		
1492-LM3Q…							X					X									X		
1492-LMG3…							X					X									X		
1492-LMJ3…							X						X								X		
1492-LMJG3…							X						X								X		
1492-LMP3…							X					X									X		
1492-LMP3Q…							X					X									X		
1492-LS…							X																
1492-LTF3…							X						X										
1492-W16S…					X																		
1492-W3…			X																				
1492-W4…					X																		
1492-W4TW…				X																			
1492-W6…					X																		
1492-WFB4			X	X																			
1492-WG10S…					X																		
1492-WG16S…					X																		
1492-WG4…					X																		
1492-WG6…					X																		
1492-WM3…	X																						
1492-WM4…				X																			
1492-WMD…	X																						
1492-WMG…				X																			
1492-WR3…		X																					
1492-WTF3…		X																					
1492-WTS3…		X																					

Télémecanique

	MF 8/5	MF 10/5	MF 12/5	MF 10/6
AB1 AA135U…	X	X	X	
AB1 AA235U…				X
AB1 AATP135U…	X	X	X	
AB1 AATP235U…				X
AB1 AASC…				X
AB1 AASF…				X
AB1 AAET135UGR	X	X	X	
AB1 AAET235…				X
AB1 RR235U…	X	X	X	
AB1 RR435U…				X
AB1 RR635U2				X
AB1 RR1035U2				X
AB1 RR1635U2				X
AB1 RRTP235U…	X	X	X	
AB1 RRTP435U…				X
AB1 RRTP635U2				X
AB1 RRTP1035U2				X
AB1 RRTP1635U2				X
AB1 RRSC435UGR				X
AB1 RRSF435U				X
AB1 RRET…	X	X	X	
AB1 VV235U	X	X	X	

	MF 8/5	MF 10/5	MF 12/5	MF 10/6
AB1 VV435U				X
AB1 VV635U				X
AB1 VVN…				X
AB1 TP…				X
AB1 SC435U				X
AB1 FUSE435U				X
AB1 SF435U				X
AB1 D11435U				X
AB1 F…				X
AB1 E…				X
AB1 D…				X
AB1 TR…				X
AB1 NEN…				X
AB1 BB…				X
AB1 BC…				X
AB1 VV215	X	X	X	
AB1 VV415				X
AB1 TP215				X
AB1 BV10235U				X
AB1 DV10235U				X
AB1 BCP20235U				X

The markers must be mounted individually when the terminal pitch is larger than 6 mm.

Woertz

	MF-WO 5/5	MF-WO 9/5	MF-WO 12/5	MF-WO 9/6	MF-WO 12/6
2711…	X				
2759...	X				
2760…	X				
3410…					X
3424…					X
3426…					X
3427…					X
3428…					X
3429…					X
3430…				X	
3436/4…					X
3436…					X
3436/10…					X
3437…					X
3438…					X
3440…					X
3450…					X
3452…					X
3452/10…					X
3452/16…					X
3472…					X
3473...					X
3477…					X
30003…					X
30005…					X
30008…					X
30009…					X
30041…					X
30123…					X
30124…					X
30125…					X
30127…					X
30128…					X
30130…					X
30137…					X
30138…					X
30143…					X
30146…					X
30150…		X			
30168…					X
30172…					X
30176…					X
30191…					X
30195…					X
30197…					X
30200…					X
30228…					X
30290…					X
30291…					X
30400…	X				
30403…	X				
30430…				X	
30431…				X	
30432…				X	
30544/4…					X
30544/6…					X
30544/10…					X
30544/16…					X
30550…					X
30800…					X
30810…		X			
30840…					X
30841…					X
30842…					X
30843…					X
30844…					X
30860…		X			
30870…		X			
30880…		X			
30890…				X	
30891…				X	
30902…				X	
30903…		X			
30904…				X	
30930…				X	
30950…				X	
30951…				X	
30952…				X	

	MF-WO 5/5	MF-WO 9/5	MF-WO 12/5	MF-WO 9/6	MF-WO 12/6
30973…		X			
45124…	X				
45136…	X				
45140…	X				
45148…	X				
45156…	X				
45163…	X				
45165…	X				
45170…	X				
45179…	X				
45200…	X				
45217…	X				
45218…	X				
45219…	X				
45220…	X				
45235…	X				
45305T…	X				
45306T…	X				
45307T…	X				
45308T…	X				
45309T…	X				
45310T…	X				
45311T…	X				
45312T…	X				
45313T…	X				
45314T…	X				
45315T…	X				
45316T…	X				
45323T…	X				
45329T…	X				
45372T…	X				
45373T…	X				
45374T…	X				
45375T…	X				
45376T…	X				
45377T…	X				
45378T…	X				
45385T…	X				
45387T…	X				
45388T…	X				
45389T…	X				
45393T…	X				
45394T…	X				
45441T…	X				
45442T…	X				
45443T…	X				
45444T…	X				
45445T…	X				

	MF 8/5	MF 10/5	MF 10/6
393 03			X
393 04			X
393 05			X
393 07			X
393 60	X	X	
393 61			X
393 62			X
393 64			X
393 66			X
393 68			X
393 70			X
393 71	X	X	
393 72			X
393 73			X
393 74			X
393 76			X
393 78			X
393 81			X
393 82			X
394 00			X
394 02			X
396 01	X	X	
396 02	X	X	
396 03	X	X	
396 04			X
396 11	X	X	
396 12	X	X	
396 13	X	X	
396 14			X
396 21	X	X	
396 24			X
396 23	X	X	

Legrand

	MF 8/5	MF 10/5	MF 10/6
390 60	X	X	
390 61			X
390 62			X
390 64			X
390 66			X
390 68			X
390 70			X
390 77	X	X	
390 78			X
390 76			X
390 80			X
390 81			X
390 84			X
390 85			X
390 86			X
393 00	X	X	
393 01			X
393 02			X

Festo

	MFF 10/6	MFF 9/4	ESG 10/17	ESG 9/20	ESG-M 8/20	ESG-M 9/17
CPE	X					
MZBH	X					
MOZBH	X					
MEBH	X					
MOEBH	X					
JMN2H, MN2H						X
JMN2H, MN1H				X		
JMT2H/MT2H-...-4,0				X		
JMT2H, MT2H-...-7,0			X			
MVH, MOVH, MDH, MODH				X		
MHA1, MHP1		X				
CPV10/14	X					
CPV18				X		
CP-E16	X					
CP-A08	X					
MV-BZ Typ 02				X		
KMYZ	X					
Pneumatic elements and valve clusters					X	

Murr

	ESG-M 9/17	ESG-M 8/20	ESG 9/20	MF 10/5	MF 12/5
MASI	X				
MVP	X				
Cube67		X			
M8 distributor				X	
MVK		X			
Optocoupler					X
Miro-Series					X

Markers

	MF 5/4	MF 5/5	MF 8/5	MF 10/5	MF 12/5	MF 4/5,2	MF 5/6	MF 10/6	MF 5/7,5	MF 10/8	MF 10/10	MF 5/7,5	MF-W 9/4	MF-W 9/4.2 F	MF-W 5/5 mini	MF-W 9/5	MF-W 9/5 F	MF-W 9/5.2 F	MF-W 9/6	MF-W 9/6.2 F	MF-SI 8/5	MF-SI 10/5	MF-SI 8/6	MF-SI 10/6	MF-SI 7/5-6,5	MF-SI 10/5-6,5	MF-WO 5/5	MF-WO 9/5	MF-WO 12/5	MF-WO 9/6	MF-WO 12/6	MF 10/5 Cabur	MF 12/5 Cabur	ESG 5/10	ESG 9/20	ESG-M 9/17	ESG-M 8/20	MFF 9/4	MFF 10/6	ESG 10/17
Phoenix																																								
UC-TM 5			X	X	X																																			
UC-TM 6								X																																
UC-TM 8										X																														
UC-TM 10											X																													
UC-TM 12											X																													
UC-TM 16											X																													
UC-TMF 4	X																																							
UC-TMF 5		X																																						
UC-TMF 6							X																																	
ZBF 4	X																																							
ZBF 5		X																																						
ZBF 6							X																																	
ZB 5			X	X	X																																			
ZB 6								X																																
ZB 8										X																														
ZB 10											X																													
BN ZB 5,2						X																																		
BN ZB 7,5									X																															
WAGO																																								
209-… (4 mm)													X	X																										
793-… (5 mm)																X	X	X																						
793-… (6 mm)																			X	X																				
248-… (5 mm)															X																									
Woertz																																								
RB/5x5																											X													
RB/5x9																												X												
RB/5x12																													X											
RB/6x9																														X										
RB/6x12																															X									
Cabur																																X	X							
CNU/8																																								
ABB-Stotz / Entrelec																																								
RC55															X																									
RC410													X	X																										
RC510				X												X	X																							
RC610								X											X																					
RC810										X									X																					
Wieland																																								
9705 A/5…			X	X	X																																			
9705 A/6…								X																																
Télémecanique																																								
AB1-B5			X	X	X																																			
AB1-B6								X																																
Murr																																								
KPX 4/10	X																																							
KPX 5/10…				X																																				
KPX 6/10…								X																																
KPX 5/5-5 ZS		X																																						
KPX 6/5-6 ZS							X																																	
KWI / KLG / KET 5/10…				X																																				
KWI / KET 6/10…								X																																
KSI 5/7																									X															
KSI 5/10																										X														
KSI 5/7-5																					X																			
KSI 5/10-5																						X																		
KSI 6/7-5																							X																	
KSI 6/10-5																								X																
KAB 6/12																															X									
KAB 5/5,4-5																											X													
KAB 5/9-5																												X												
KAB 5/12-5																													X											
KAB 6/9-6																														X										
WGO 5/5-5															X																									
WGO 5/10-5																X			X																					
WGO 5/10-5 F																	X	X		X																				
TK 4,5-7,5									X																															
KS 5/10																																	X							
KES 20x8																																				X				
ABB 17-9																																			X					

Markers

	MF 5/4	MF 5/5	MF 8/5	MF 10/5	MF 12/5	MF 4/5,2	MF 5/6	MF 10/6	MF 5/7,5	MF 10/8	MF 10/10	MF 5/7,5	MF-W 9/4	MF-W 9/4.2 F	MF-W 5/5 mini	MF-W 9/5	MF-W 9/5 F	MF-W 9/5.2 F	MF-W 9/6	MF-W 9/6.2 F	MF-SI 8/5	MF-SI 10/5	MF-SI 8/6	MF-SI 10/6	MF-SI 7/5-6,5	MF-SI 10/5-6,5	MF-WO 5/5	MF-WO 9/5	MF-WO 12/5	MF-WO 9/6	MF-WO 12/6	MF 10/5 Cabur	MF 12/5 Cabur	ESG 5/10	ESG 9/20	ESG-M 9/17	ESG-M 8/20	MFF 9/4	MFF 10/6	ESG 10/17
Festo																																								
IBS-6x10																																							X	
MH-BZ-80X																																					X			
IBS-10x17																																								X
IBS-9x20																																			X					
IBS-8x20																																					X			
IBS-9x17																																				X				

Wire and cable markers



Weidmüller's range of wire and cable markers provides users with solutions for a wide variety of applications. The applications range from thin wires through to cables with large external diameters. Amongst others, the assortment includes combination systems with individual tags, transparent sleeves and markers that are fastened using cable ties.

Open and closed, printed or blank markers for individual printing are available.

Halogen-free and practically free of pollutants, Weidmüller's wire and cable markers comply with both European and inhouse standards of well-known system manufacturers. Systems are available for:

- Clip-on ready-to-use printed markers according to individual marking requirements
- Marking by digits from a standard set of characters
- Combination of individual pre-printed digits to form a character code
- Customer prints utilising one of the following options: SMark-Laser printer, PrintJet printer, laser printer, plotter, thermal transfer, Matrix printer or pen.

A sample selection is available in Weidmüller's sample bag of wire and cable markers: order no. **1640420000**.

Owing to the sheer number of possible applications and environmental influences such as moisture, radiation, gases or heat/cold to which the products can be exposed, Weidmüller accepts no liability for the suitability of products in all customer applications. Suitability tests for specific applications must therefore be carried out by the customer. However, Weidmüller will be happy to provide help and advice upon request.

Due to the different identification system available on the market, we wish to point out that Weidmüller does not guarantee industrial identification products if the Weidmüller components (markers – transparent sleeves – ink/toner/colour ink ribbons – printing systems) are combined with third-party products, unless Weidmüller has explicitly agreed for the purpose of an individual application.

Applications chart



* Non-binding reference values. Please take into consideration the external diameter of the insulation.

SlimFix

SlimFix are wire and cable markers featuring a space-saving design. The markers can also be attached to the wires after these have been installed. They are made from halogen-free material and fulfil V0/V2 flammability class requirements. SlimFix is an approved and listed marker for traffic engineering. Attaching even small markers is no problem when using the SF tool.

- Halogen-free material
- V0/V2 flammability class
- Approved and listed markers, includes traffic engineering
- Attach to conductor cross-sections greater than 16.0 mm² with cable ties
- Markers available in the proven MultiCard format
- Also available in flammability class V0. Contact Weidmüller for more information.

SFX

Application SFX S





SFX 10/23

SFX 14/23

SFX 9/24

Technical data

SF/SFX			
Material	Wemid / Polyamide		
Flammability class to UL94	V0/V2		
Temperature range	V0: –5 °C ... 120 °C/V2: –40 °C ... 100 °C		
Possible printing systems	SMark-Laser, PrintJet, Plotter MCP Plus oder MC-Mobilo		
Colour	Other colours on reques		
	● brown	● red	● orange
	● yellow,	● green	● blue
	● violet	● grey	O white
Notes on mounting	SF: Slide onto unconnected wires; attach to connected wires using SlimFix tool		
	SFX: Attach using cable ties		

Ordering data

Minimum order quantity	1 pack
Special printing	Specify special printing and colours per diskette, Excel file or using the M-Print® PRO software.

Simply slip on the marker...



...or use the special SF tool







SlimFix made from V2 material is a conductor and cable marker system with a space-saving design. The SF V2 made from halogen free material exhibits good mechanical and printing characteristics. Arial is the recommended font when using the PrintJet. The SF tool permits easy installation.

- halogen free material
- flammability rating V2
- SFX attached with cable ties (3.6 mm wide)

SF - blank

Technical specification

Material	Polyamide 66
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C

Selection table

Type	Cond. ext. Ø. (max.) mm	Cond. cross-section mm^2
SF 00	0.9 / 1.00 – 1.30	< 0.25
SF 0	1.20 – 1.60	0.25 – 0.50
SF 1	1.70 – 2.10	0.50 – 0.75
SF 2	2.20 – 2.90	0.75 – 1.50
SF 3	3.00 – 3.70	1.50 – 2.50
SF 4	3.60 – 6.00	2.50 – 4.00
SF 4.5	4.10 – 4.90	4.00 – 6.00
SF 5	4.80 – 7.40	6.00 – 10.00
SF 6	5.80 – 7.80	10.00 – 16.00
SFX	from 7.00	from 16.00

SFX only: max. width of cable tie = 3.60 mm

Ordering data

Type	Printing area	Length	Qty.	Order No. white	Order No. yellow	Order No. blue	Order No. red
SF 00/12	12x3.2 mm	12	400	**1919290000**	**1919260000**	**1919270000**	**1919280000**
SF 0/12	12x3.2 mm	12	400	**1919240000**	**1919210000**	**1919220000**	**1919230000**
SF 1/12	12x3.2 mm	12	400	**1919390000**	**1919340000**	**1919360000**	**1919320000**
SF 2/12	12x3.6 mm	12	400	**1919490000**	**1919470000**	**1919480000**	**1919460000**
SF 3/12	12x4.6 mm	12	320	**1919540000**	**1919520000**	**1919550000**	**1919530000**
SF 4/12	12x5.7 mm	12	128	**1919600000**	**1919580000**	**1919590000**	**1919570000**
SF 5/12	12x7.4 mm	12	160	**1919650000**	**1919620000**	**1919630000**	**1919640000**
SF 00/21	21x3.2 mm	21	400	**1918580000**	**1918560000**	**1918590000**	**1918570000**
SF 0/21	21x3.2 mm	21	400	**1918500000**	**1918480000**	**1918510000**	**1918490000**
SF 1/21	21x3.2 mm	21	400	**1918630000**	**1918610000**	**1918620000**	**1918600000**
SF 2/21	21x3.6 mm	21	400	**1918690000**	**1918660000**	**1918700000**	**1918670000**
SF 3/21	21x4.6 mm	21	320	**1918910000**	**1918890000**	**1918920000**	**1918900000**
SF 4/21	21x5.7 mm	21	192	**1919080000**	**1919060000**	**1919090000**	**1919070000**
SF 4,5/21	21x7.4 mm	21	96	**1919020000**	**1919000000**	**1919030000**	**1919010000**
SF 5/21	21x7.4 mm	21	160	**1919140000**	**1919120000**	**1919150000**	**1919130000**
SF 6/21	21x8.4 mm	21	160	**1919190000**	**1919170000**	**1919200000**	**1919180000**
SFX 10/23	23x5 mm	23	160	**1852390000**	**1852360000**	**1852400000**	**1852370000**
SFX 14/23	23x8.2 mm	23	160	**1852440000**	**1852410000**	**1852450000**	**1852420000**
SFX 9/24	23.9x9 mm	24	160	**1852490000**	**1852460000**	**1852500000**	**1852470000**
SFX 9/40 S n	8.5x40 mm	40	80	**1248760000**	**1248770000**	**1248790000**	**1248780000**
SFX 10/60 S n	9.5x60 mm	60	50	**1248810000**	**1248820000**	**1248840000**	**1248830000**
SFX 11/60	11x44 mm	60	60	**1860120000**	**1860150000**	**1051870000**	**1963650000**
SFX 30/60* n	30x45 mm	60	30	**1083230000**	**1083240000**		

*** Order No. for colour grey: 1083250000**

SF - Custom printing

Type	Printing area	Length	Qty.	Order No.
SF 00/12	12x3.2 mm	12	80	**1919300000**
SF 0/12	12x3.2 mm	12	80	**1919250000**
SF 1/12	12x3.2 mm	12	80	**1919420000**
SF 2/12	12x3.6 mm	12	80	**1919500000**
SF 3/12	12x4.6 mm	12	64	**1919510000**
SF 4/12	12x5.7 mm	12	32	**1919610000**
SF 5/12	12x7.4 mm	12	32	**1919660000**
SF 00/21	21x3.2 mm	21	80	**1918530000**
SF 0/21	21x3.2 mm	21	80	**1918470000**
SF 1/21	21x3.2 mm	21	80	**1918640000**
SF 2/21	21x3.6 mm	21	80	**1918650000**
SF 3/21	21x4.6 mm	21	64	**1918880000**
SF 4/21	21x5.7 mm	21	48	**1919050000**
SF 4,5/21	21x7.4 mm	21	32	**1918990000**
SF 5/21	21x7.4 mm	21	32	**1919110000**
SF 6/21	21x8.4 mm	21	32	**1919160000**
SFX 10/23	23x5 mm	23	32	**1852380000**
SFX 14/23	23x8.2 mm	24	32	**1852430000**
SFX 9/24	23.9x9 mm	24	32	**1852480000**
SFX 9/40 S n	8.5x40 mm	40	16	**1248740000**
SFX 10/60 S n	9.5x60 mm	60	10	**1248550000**
SFX 11/60	11x44 mm	60	12	**1860140000**
SFX 30/60 n	30x45 mm	60	30	**1083260000**

SF - accessory

Type	Qty.	Order No.
SF-Tool 00-6	10	**1950820000**
SF-Tool 1	10	**1782970000**
SF-Tool 2-3	10	**1782960000**
SF-Tool 4-5	10	**1782980000**
SF-Tool-Sortiment	1	**1770080000**

SlimFix Clip

The SlimFix Clip combines two advantages in one: its unique closure mechanism offers the reliability of a closed marker with ease of attaching an open marker. The Clip closure mechanism also allows quick, no fuss attachment of the markers after the wires have been installed. SlimFix Clip markers are suitable for wires and cables with external diameters up to 5 mm. Long sequences of characters are possible on the large marking surface – up to 30 mm.

- Halogen free, flammability class V2 material
- Rapid attachment without tools
- Five sizes for wire cross-sections from 0.5 – 10.0 mm²
- Available in lengths of 12, 21 and 30 mm
- Markers available in the proven MultiCard format
- Additional marking surface for precise assignment to projects
- Custom-printed markers supplied to your specifications
- Printing on the SFC 3 is not possible with the SMark Laser.
- Accessory plates must be used when printing on the SFC 2.5 and SFC 3 with the MCP Plus, MCP Basic and MC Mobilo (see right).





Technical data

Material	Polyamide 66, halogen-free
UL 94 flammability rating	V2
Temperature range	–40 °C to 100 °C

SFC 2.5 printing

MCP Plus / MCP Basic	Order No.
AP SF 4-6	1924310000
MC Mobilo	**Order No.**
AP SF 4-6	1924310000

SFC 3 printing

MCP Plus / MCP Basic	Order No.
AP SF 4-6	1924310000
Inlay SFC 3	1058090000
MC Mobilo	**Order No.**
AP SF 4-6	1802180000
Inlay SFC 3	1058090000

Ordering data

Type	Wire, ext. ø	Wire cross-section
SFC 0	1.5 - 2.5 mm	0.5 - 1.0 mm²
SFC 1	2.0 - 3.5 mm	0.75 - 2.5 mm²
SFC 2	2.5 - 5.0 mm	2.5 - 4.0 mm²
SFC 2,5	4.0 - 6.0 mm	4.0 - 10 mm²
SFC 3	3.5 - 7.0 mm	4.0 - 10 mm²
Colour	Available in all colours of the international colour code; for MC on request ● brown ● orange ● green ● violet ● grey	
Special printing	Specify special printing and colours per diskette, Excel file or using the M-Print® PRO software.	
Minimum order quantity	1 pack	

SFC - blank

Technical specification

Material	Polyamide
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C

Ordering data

Type	Printing area	Length	Qty.	Order No. white	Order No. yellow	Order No. blue	Order No. red
SFC 0/12	12x4.1 mm	12	200	**1813130000**	**1813160000**	**1813170000**	**1813150000**
SFC 1/12	12x4.1 mm	12	200	**1747320001**	**1747320004**	**1747320002**	**1747320003**
SFC 2/12	12x5.8 mm	12	120	**1758320001**	**1758320004**	**1758320002**	**1758320003**
SFC 2.5/12 n	12x5.8 mm	12	120	**1062000000**	**1062010000**	**1062030000**	**1062020000**
SFC 3/12	12x5 mm	12	80	**1025220000**	**1025230000**	**1025250000**	**1025240000**
SFC 0/21	21x4.1 mm	21	200	**1813190000**	**1813210000**	**1813220000**	**1813200000**
SFC 1/21	21x4.1 mm	21	200	**1779080001**	**1779080004**	**1779080002**	**1779080003**
SFC 2/21	21x5.8 mm	21	120	**1805810000**	**1805780000**	**1805770000**	**1805790000**
SFC 2.5/21 n	21x5.8 mm	21	120	**1062050000**	**1062070000**	**1062090000**	**1062080000**
SFC 3/21	21x5 mm	21	80	**1025260000**	**1025270000**	**1025300000**	**1025290000**
SFC 0/30	30x4.1 mm	30	150	**1813240000**	**1813260000**	**1813270000**	**1813250000**
SFC 1/30	30x4.1 mm	30	150	**1805760000**	**1805730000**	**1805720000**	**1805740000**
SFC 2/30	30x5.8 mm	30	90	**1805870000**	**1805830000**	**1805820000**	**1805850000**
SFC 3/30	30x5 mm	30	60	**1025310000**	**1025320000**	**1025340000**	**1025330000**

SFC - Custom printing

Type	Printing area	Length	Qty.	Order No.
SFC 0/12	12x4.1 mm	12	40	**1813180000**
SFC 1/12	12x4.1 mm	12	40	**1752720000**
SFC 2/12	12x5.8 mm	12	24	**1763480000**
SFC 2.5/12 n	12x5.8 mm	12	24	**1062040000**
SFC 3/12	12x5 mm	12	16	**1025550000**
SFC 0/21	21x4.1 mm	21	40	**1813230000**
SFC 1/21	21x4.1 mm	21	40	**1779090000**
SFC 2/21	21x5.8 mm	21	24	**1805800000**
SFC 2.5/21 n	21x5.8 mm	21	24	**1062110000**
SFC 3/21	21x5 mm	21	16	**1025560000**
SFC 0/30	30x4.1 mm	30	30	**1813280000**
SFC 1/30	30x4.1 mm	30	30	**1805750000**
SFC 2/30	30x5.8 mm	30	18	**1805860000**
SFC 3/30	30x5 mm	30	12	**1025570000**

TM-I

The special profile of the TM-I results in easy installation and secure marking. TM-I tags are compatible with many of the sleeves available on the market. Their MultiCard format means quick and convenient printing with the SMark-Laser, PrintJet, MCP Plus Plotter, MC-Mobilo or STI-S pen systems. Thanks to the project name panels on the MultiCards, the tags are easy to separate and mount. TM-I is an acknowledged and accredited marker for traffic engineering applications. Five different tag lengths are available for individual labelling with long character strings.

- Easily separated and mounted thanks to the project name panels
- Acknowledged and accredited marker for traffic engineering
- Fitting the sleeves first and inserting the labels later adds up to maximum flexibility
- Not suited for labelling with P-Ink or STI-S pen in connection with CLI T sleeves





Technical data

Material	Polyamide 66, halogen-free
UL 94 flammability rating	V2
Temperature range	–40 °C to 100 °C
Printing	black

Ordering data

Colour	Other colours on request ● brown ● red ● orange ● yellow ● green ● blue ● violet ● grey O white
Special printing	Specify special printing and colours per diskette, Excel file or using the M-Print® PRO software.
Minimum order quantity	1 pack



TM-I blank

Technical specification

Material	Polyamide 66
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C

Ordering data

Type	Length	Width	Material colour	Qty	Order No.
TM-I 12 BLANK WS	12 mm	4 mm	white	320	**1718411044**
TM-I 12 BLANK GE	12 mm	4 mm	yellow	320	**1718411687**
TM-I 12 BLANK BL	12 mm	4 mm	Blue	320	**1718411693**
TM-I 12 BLANK RT	12 mm	4 mm	red	320	**1718411686**
TM-I 12 BLANK GN	12 mm	4 mm	green	320	**1718411688**
TM-I 15 BLANK RT	15 mm	4 mm	white	400	**1609981044**
TM-I 15 BLANK BL	15 mm	4 mm	yellow	400	**1609981687**
TM-I 15 NEUTRAL	15 mm	4 mm	Blue	400	**1609981693**
TM-I 15 BLANK GN	15 mm	4 mm	red	400	**1609981686**
TM-I 15 BLANK GE	15 mm	4 mm	green	400	**1609981688**
TM-I 18 BLANK WS	18 mm	4 mm	white	320	**1718431044**
TM-I 18 BLANK GE	18 mm	4 mm	yellow	320	**1718431687**
TM-I 18 BLANK BL	18 mm	4 mm	Blue	320	**1718431693**
TM-I 18 BLANK RT	18 mm	4 mm	red	320	**1718431686**
TM-I 18 BLANK GN	18 mm	4 mm	green	320	**1718431688**
TM-I 20 BLANK RT	20 mm	4 mm	white	400	**1680411044**
TM-I 20 BLANK BL	20 mm	4 mm	yellow	400	**1680411687**
TM-I 20 NEUTRAL	20 mm	4 mm	Blue	400	**1680411693**
TM-I 20 BLANK GN	20 mm	4 mm	red	400	**1680411686**
TM-I 20 BLANK GE	20 mm	4 mm	green	400	**1680411688**
TM-I 30 MC BLANK WS	30 mm	4 mm	white	300	**1876390000**
TM-I 30 MC BLANK GE	30 mm	4 mm	yellow	300	**1876370000**
TM-I 30 MC BLANK BL	30 mm	4 mm	Blue	300	**1876400000**
TM-I 30 MC BLANK RT	30 mm	4 mm	red	300	**1876380000**

TM-I Custom printing

Technical specification

Material	Polyamide 66
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C
Material colour	To customer specification

Type	Length	Width	Qty	Order No.
TM-I 12 CUSTOM PRINT	12 mm	4 mm	64	**1718420000**
TM-I 15 CUSTOM PRINT	15 mm	4 mm	80	**1609990000**
TM-I 18 CUSTOM PRINT	18 mm	4 mm	64	**1718440000**
TM-I 20 CUSTOM PRINT	20 mm	4 mm	80	**1680420000**
TM-I 30 MC CUSTOM PRINT	30 mm	4 mm	60	**1876320000**

The TM/HF sleeve is free from halogens and essentially free from other hazardous substances. The sleeves are fitted with the TM-I 12 or TM-I 18. They are suitable for a wide range of cables and conductors. This system has proved particularly beneficial in transport engineering. The slim design guarantees a firm attachment to the cable.

- halogen free,
- slim design guarantees firm attachment to cable.
- TMX 18 fixed with cable ties (3.6 mm wide)

TM/HF - sleeve

Technical specification

Material	Polyethylene LD
UL 94 flammability rating	HB
Min. temperature, continuous	-20 °C
Max. temperature, continuous	80 °C
Material colour	transparent

Ordering data

Type	Length	Insulation O.D.	Cond. cross-section	Qty	Order No.
TM 0/12 HF/HB	12 mm	1.3-2.0 mm	0.22-0.5 mm²	1000	**1719760000**
TM 0/18 HF/HB	18 mm	1.3-2.0 mm	0.22-0.5 mm²	1000	**1719770000**
TM 1/12 HF/HB	12 mm	1.8-2.5 mm	0.5-1.5 mm²	1000	**1719780000**
TM 1/18 HF/HB	18 mm	1.8-2.5 mm	0.5-1.5 mm²	1000	**1719790000**
TM 2/12 HF/HB	12 mm	2.5-4.0 mm	0.75-2.5 mm²	1000	**1719800000**
TM 2/18 HF/HB	18 mm	2.5-4.0 mm	0.75-2.5 mm²	1000	**1719810000**
TM 3/12 HF/HB	12 mm	4.0-6.5 mm	2.5-6 mm²	500	**1719820000**
TM 3/18 HF/HB	18 mm	4.0-6.5 mm	2.5-6 mm²	500	**1719830000**
TM 4/12 HF/HB	12 mm	6.0-10.0 mm	10-35 mm²	500	**1719840000**
TM 4/18 HF/HB	18 mm	6.0-10.0 mm	10-35 mm²	500	**1719850000**
TM 5/12 HF/HB	12 mm	9.0-15.0 mm	25-70 mm²	200	**1719860000**
TM 5/18 HF/HB	18 mm	9.0-15.0 mm	25-70 mm²	200	**1719870000**
TM 6/12 HF/HB	12 mm	15.0-24.0 mm	35-150 mm²	200	**1719880000**
TM 6/18 HF/HB	18 mm	15.0-24.0 mm	35-150 mm²	200	**1719890000**
TMX 18 HF/HB	18 mm	10.0-317.0 mm	16-150 mm²	500	**1748820000**

The twin sleeves provide the option of marking a cable on both sides. The sleeves can be fitted with two TM-I 18 tags so that, for example, the input and output designations of a cable can be read off at one position. The transparent, halogen free sleeves can be used on cables with an outside diameter of 1.3 to 4.0 mm.

TM/HF - Twin - SLEEVE

Technical specification

Material	Polyethylene LD
UL 94 flammability rating	HB
Min. temperature, continuous	-20 °C
Max. temperature, continuous	80 °C
Material colour	transparent

Ordering data

Type	Length	Insulation O.D.	Cond. cross-section	Qty	Order No.
TM 0/18 TWIN HF/HB	18 mm	1.3-2.6 mm	0.22-1.5 mm²	500	**1891810000**
TM 1/18 TWIN HF/HB	18 mm	2.4-4.0 mm	1.5-2.5 mm²	500	**1891780000**

CLI T connector markers are high-quality, transparent sleeves in different lengths for labelling cables with a cross-section of 0.2 mm² to 75 mm². The TM-I series is suitable as an inlay tag.
- Larger cross-section per sleeve,
- Large range of applications thanks to special bellows profile with spring effect,
- easy to insert the TM-I tag into the sleeve pocket before or after connecting the conductor,
- available in five lengths.
- Not suitable for labelling with P-Ink ink or with an STI-S pen.

CLI T sleeve

Technical specification

Material	PVC
UL 94 flammability rating	V0
Min. temperature, continuous	-30 °C
Max. temperature, continuous	80 °C
Material colour	transparent

Ordering data

Type	Length	Insulation O.D.	Cond. cross-section	Qty	Order No.
CLI T 02-12	12 mm	1.3-3.0 mm	0.22-1.5 mm²	200	**1764060000**
CLI T 02-15	15 mm	1.3-3.0 mm	0.22-1.5 mm²	200	**1764070000**
CLI T 02-18	18 mm	1.3-3.0 mm	0.22-1.5 mm²	200	**1764140000**
CLI T 02-20	20 mm	1.3-3.0 mm	0.22-1.5 mm²	200	**1764150000**
CLI T 02-30	30 mm	1.3-3.0 mm	0.22-1.5 mm²	200	**1889580000**
CLI T 1-12	12 mm	2.5-5.0 mm	0.75-6 mm²	200	**1764190000**
CLI T 1-15	15 mm	2.5-5.0 mm	0.75-6 mm²	200	**1764200000**
CLI T 1-18	18 mm	2.5-5.0 mm	0.75-6 mm²	200	**1764210000**
CLI T 1-20	20 mm	2.5-5.0 mm	0.75-6 mm²	200	**1764220000**
CLI T 1-30	30 mm	2.5-5.0 mm	0.75-6 mm²	200	**1889560000**
CLI T 2-12	12 mm	4.0-10.0 mm	4-35 mm²	100	**1764230000**
CLI T 2-15	15 mm	4.0-10.0 mm	4-35 mm²	100	**1764240000**
CLI T 2-18	18 mm	4.0-10.0 mm	4-35 mm²	100	**1764250000**
CLI T 2-20	20 mm	4.0-10.0 mm	4-35 mm²	100	**1764260000**
CLI T 2-30	30 mm	4.0-10.0 mm	4-35 mm²	100	**1889570000**
CLI T 3-12	12 mm	8.0-16.0 mm	25-75 mm²	100	**1764270000**
CLI T 3-15	15 mm	8.0-16.0 mm	25-75 mm²	100	**1764280000**
CLI T 3-18	18 mm	8.0-16.0 mm	25-75 mm²	100	**1764290000**
CLI T 3-20	20 mm	8.0-16.0 mm	25-75 mm²	100	**1764300000**
CLI T 3-30	30 mm	8.0-16.0 mm	25-75 mm²	100	**1889550000**

CLI TM is the right sleeve for large conductor cross-sections. The transparent pocket on the sleeve protects the inlay tags against outside influences. The transparent CLI TM sleeve is fixed with cable ties. The marking is carried out with TM-I 18 and CLI F1 for CLI TM 10/33 or ESG 9/17 and CLI F2 for CLI TM 20/33. Both types of inlay tags make use of the established MultiCard format and can be easily printed with the SMark laser, PrintJet, MCP Plus plotter or MC-Mobilo. The CLI F 2/17.5 tag is suitable for the CLI TM 20/66.
- Secure attachment thanks to cable ties,
- Professional marking results with the Weidmüller labelling system for MultiCards

CLI TM

Technical specification

Material	PVC
UL 94 flammability rating	V0
Min. temperature, continuous	-30 °C
Max. temperature, continuous	60 °C
Material colour	transparent

Ordering data

Type	Length	Width	Qty	Order No.
CLI TM 10-33	33 mm	6 mm	100	**1763270000**
CLI TM 20-33	33 mm	11.3 mm	100	**1763280000**
CLI TM 20-66	66 mm	11.3 mm	50	**1763390000**

Accessories

Technical specification

Type	Length	Width	No. per sheet	Qty	Order No.
CLI F 1/20 WHITE/YELLOW	20 mm	4 mm	594	10	**1600740000**
CLI F 2/17.5 WHITE/YELLOW	17.5 mm	9 mm	352	10	**1764050000**
TM-I 18 MC	18 mm	4 mm		320	**1718431044**
ESG 9/17 MC white	9 mm	17 mm		200	**1724760000**



The range of TM sleeves is comprehensive and permits almost universal use: from thin conductors to cables with a large outside diameter, a wide range of applications is covered. The sleeves protect the printed inlay tags against external influences. TM sleeves also permit flexible installation. They are available in five different lengths (12, 15, 18, 20, 30 mm) and 11 sizes - one tag type for all sleeves.

- optimum protection for printed inlay tags,
- large range of applications for conductors and cables,
- one tag type for all cross-sections.
- TMX 30 fixed with cable-ties (width 4.6 mm)

TM - sleeve

Technical specification

Material	PVC
UL 94 flammability rating	V0
Min. temperature, continuous	-50 °C
Max. temperature, continuous	80 °C
Material colour	transparent

Ordering data

Type	Length	Insulation O.D.	Cond. cross-section	Qty	Order No.
TM 200/15 V0	15 mm	1.0-1.25 mm	0.22-1 mm²	1000	**1798650000**
TM 201/12 V0	12 mm	1.5-2.5 mm	0.25-1.5 mm²	1000	**1798640000**
TM 201/15 V0	15 mm	1.5-2.5 mm	0.25-1.5 mm²	1000	**1798620000**
TM 201/18 V0	18 mm	1.5-2.5 mm	0.25-1.5 mm²	1000	**1798600000**
TM 201/20 V0	20 mm	1.5-2.5 mm	0.25-1.5 mm²	1000	**1798580000**
TM 201/30 V0	30 mm	1.5-2.5 mm	0.25-1.5 mm²	500	**1874850000**
TM 202/12 V0	12 mm	2.0-4.0 mm	0.5-2.5 mm²	1000	**1798560000**
TM 202/15 V0	15 mm	2.0-4.0 mm	0.5-2.5 mm²	1000	**1798540000**
TM 202/18 V0	18 mm	2.0-4.0 mm	0.5-2.5 mm²	1000	**1798530000**
TM 202/20 V0	20 mm	2.0-4.0 mm	0.5-2.5 mm²	1000	**1798520000**
TM 202/30 V0	30 mm	2.0-4.0 mm	0.5-2.5 mm²	500	**1874760000**
TM 203/12 V0	12 mm	4.0-7.0 mm	2.5-10 mm²	500	**1798510000**
TM 203/15 V0	15 mm	4.0-7.0 mm	2.5-10 mm²	500	**1798490000**
TM 203/18 V0	18 mm	4.0-7.0 mm	2.5-10 mm²	500	**1798480000**
TM 203/20 V0	20 mm	4.0-7.0 mm	2.5-10 mm²	500	**1798470000**
TM 203/30 V0	30 mm	4.0-7.0 mm	2.5-10 mm²	200	**1874770000**
TM 204/12 V0	12 mm	6.0-10.0 mm	6-16 mm²	500	**1806180000**
TM 204/15 V0	15 mm	6.0-10.0 mm	6-16 mm²	500	**1806240000**
TM 204/18 V0	18 mm	6.0-10.0 mm	6-16 mm²	500	**1806300000**
TM 204/20 V0	20 mm	6.0-10.0 mm	6-16 mm²	500	**1806360000**
TM 204/30 V0	30 mm	6.0-10.0 mm	6-16 mm²	200	**1874780000**
TM 205/12 V0	12 mm	10.0-14.0 mm	16-35 mm²	200	**1806190000**
TM 205/15 V0	15 mm	10.0-14.0 mm	16-35 mm²	200	**1806250000**
TM 205/18 V0	18 mm	10.0-14.0 mm	16-35 mm²	200	**1806310000**
TM 205/20 V0	20 mm	10.0-14.0 mm	16-35 mm²	200	**1806370000**
TM 205/30 V0	30 mm	10.0-14.0 mm	16-35 mm²	200	**1874790000**
TM 206/12 V0	12 mm	14.0-22.0 mm	35-120 mm²	200	**1806200000**
TM 206/15 V0	15 mm	14.0-22.0 mm	35-120 mm²	200	**1806260000**
TM 206/18 V0	18 mm	14.0-22.0 mm	35-120 mm²	200	**1806320000**
TM 206/20 V0	20 mm	14.0-22.0 mm	35-120 mm²	200	**1806380000**
TM 206/30 V0	30 mm	14.0-22.0 mm	35-120 mm²	100	**1874800000**
TM 207/12 V0	12 mm	22.0-30.0 mm	120-240 mm²	50	**1806210000**
TM 207/15 V0	15 mm	22.0-30.0 mm	120-240 mm²	50	**1806270000**
TM 207/18 V0	18 mm	22.0-30.0 mm	120-240 mm²	50	**1806330000**
TM 207/20 V0	20 mm	22.0-30.0 mm	120-240 mm²	50	**1806390000**
TM 207/30 V0	30 mm	22.0-30.0 mm	120-240 mm²	50	**1874820000**
TM 208/12 V0	12 mm	30.0-35.0 mm	240-300 mm²	50	**1806220000**
TM 208/15 V0	15 mm	30.0-35.0 mm	240-300 mm²	50	**1806280000**
TM 208/18 V0	18 mm	30.0-35.0 mm	240-300 mm²	50	**1806340000**
TM 208/20 V0	20 mm	30.0-35.0 mm	240-300 mm²	50	**1806400000**
TM 208/30 V0	30 mm	30.0-35.0 mm	240-300 mm²	50	**1874830000**
TM 209/12 V0	12 mm	35.0-40.0 mm	300-500 mm²	50	**1806230000**
TM 209/15 V0	15 mm	35.0-40.0 mm	300-500 mm²	50	**1806290000**
TM 209/18 V0	18 mm	35.0-40.0 mm	300-500 mm²	50	**1806350000**
TM 209/20 V0	20 mm	35.0-40.0 mm	300-500 mm²	50	**1806410000**
TM 209/30 V0	30 mm	35.0-40.0 mm	300-500 mm²	50	**1874720000**
TMX 30 V0	30 mm	10.0-317.0 mm	16-150 mm²	400	**1866680000**



WKM is a marker for tough conditions, with a secure fixing on conductor or cable. The transparent pocket guarantees reliable protection of the labelling against outside influences. The fixing with cable ties permits virtually any size of conductor or cable to be marked. The WKM can be marked in many different ways, e.g. laser printer, dot-matrix printer or the STI pen, on paper or polyester labels.

- A multitude of labelling options,
- Flexible installation with cable ties for virtually any cross-section.

WKM

Technical specification

Material	Polypropylene
UL 94 flammability rating	HB
Min. temperature, continuous	-40 °C
Max. temperature, continuous	80 °C
Material colour	transparent

Ordering data

Type	Length	Width	Qty	Order No.
WKM 8/20	20 mm	8 mm	50	**1753490000**
WKM 8/30	30 mm	8 mm	50	**1631910000**
WKM 18/43	43 mm	18 mm	50	**1610700000**

Accessories

Technical specification

ESO...P	= Polyester
ESO	= Paper

Type	Length	Width	No. per sheet	Qty	Order No.
ESO 5 white	40 mm	16.5 mm	60	10	**1607710000**
ESO 5 yellow	40 mm	16.5 mm	60	10	**1631350000**
ESO 5P white	40 mm	16.5 mm	60	10	**1670370000**
ESO 7 white	27 mm	6.3 mm	240	10	**1607720000**
ESO 5P yellow	40 mm	16.5 mm	60	10	**1670380000**
ESO 7 yellow	27 mm	6.3 mm	240	10	**1634780000**
ESO 7P white	27 mm	6.3 mm	240	10	**1670390000**
ESO 7P yellow	27 mm	6.3 mm	240	10	**1670400000**
ESG 7/20 Sirius white	7 mm	20 mm		200	**1736181044**
ESG 7/20 Sirius turquoise	7 mm	20 mm		200	**1736181696**
ESO 8/20 white	20 mm	7 mm	342	10	**1919890000**
ESO 8/20 yellow	20 mm	7 mm	342	10	**1919900000**
ESO 8/20P white	20 mm	7 mm	342	10	**1919870000**
ESO 8/20P yellow	20 mm	7 mm	342	10	**1919880000**



The ELS-type MultiCard marker can be printed on with PrintJet, plotter or SMark printer. Colour printing with the PrintJet PRO, in particular, enables cables and terminal strips to be labelled in a variety of noticeable manners.

ELS insertion tag

Technical specification

Material	Polyamide PA 66
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C
Suitable for	ELS 6/30: WKM 8/30 (1631910000) ELS 16/40: WKM 18/43 (1610700000)

Ordering data

Type	Colour	Qty.	Order No.
blank			
ELS 6/30 MC NE WS	white	80	**1045570000**
ELS 6/30 MC NE GE	yellow	80	**1045580000**
ELS 16/40 MC NE WS	white	40	**1045620000**
ELS 16/40 MC NE GE	yellow	40	**1045630000**
Custom printing			
ELS 6/30 MC SDR		16	**1045660000**
ELS 16/40 MC SDR		8	**1045690000**

Markers for devices and installations

Device and installation markers round off the range of switchgear markers. By utilising Weidmüller's device markers, users comply with official regulations requiring marking of electrical equipment. Weidmüller offers corresponding markers for devices made by well-known manufactures. Mirroring their original counterparts, these tags are attached with the traditional adhesive or rapid clip-on techniques. By utilising the corresponding software and system-compatible printer or plotter system, users can print their own markings on these markers.

A samples bag containing a selection of device and installation markers is available under the order no. **1646370000**.



	DMC	ESG	SwitchMark	ClipCard
	DMC	ESG	SwitchMark	ClipCard
Cable ducts				●
Automatic switchgear	●	●	●	●
Contactors	●	●	●	
Electrical connections	●			●
Electrical devices	●			●
Machines			●	●
LED displays			●	
Keyboards			●	●
Lamps		●		
Murr valve plug		●		
Tubes				●
Circuit-breakers	●	●		
Relays	●	●		
Shelves				●
Switches		●	●	●
Control desk		●	●	●
Transformers	●	●		
Valves				●

The DMC markers are used for labelling switching devices or components. The marking surface (12 x 27 mm) is large enough to hold information about the device and its function. The markers are fastened to a wire or cable by means of a simple clip-on mechanism. A DMC marker can be fastened to conductors in the cross-section range of 0.5 – 10 mm². In combination with MultiCards, markers can be printed using a plotter, PrintJet, SMark printer or MC Mobilo.

DMC 12/27

A single tag size for cable cross-sections from 0.5–10 mm² means they are equally suitable for use on multi-core control lines as well as single core cables.

The large marking surface provides ample space for supplementary information.

Technical data

Material	Polyamide PA 66, halogen-free
Temperature range	–40 °C… +100 °C
UL94 flammability rating	V2
Marking surface	12 x 27 mm
Suitable for cable diameters	1.5 – 7.5 mm
And conductor cross-sections	0.5 – 10 mm²

Ordering data

Type	Colour	Qty.	Order No.
DMC 12/27 MC NE WS	white	50	**1016030000**
DMC 12/27 MC NE GE	yellow	50	**1018190000**
Custom printing			
DMC 12/27 SDR	white	10	**1038830000**

ESG is the well-established marker in MultiCard format for many well-known devices. This is a high-quality device marker with a high-contrast appearance.
- For devices from ABB, Siemens, Moeller and Télémécanique.
- For universal use - available in self-adhesive and clip-on forms.
- Ideal for clipping to tag rails for marking rows of circuit-breakers or other equipment.
- Please do not use self-adhesive Multicard markers together with the SMark.

ESG - blank

Technical specification

UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C
Material	Polyamide 66

Ordering data

Type	Application	Width/Length	Qty	Order No.
ESG 5/10 MC white	Turck/Beckhoff SAI distributo	10 mm/5 mm	400	**1919940000**
ESG 6/15 K MC yellow	self-adhesive	15 mm/6 mm	200	**1880130000**
ESG 6/15 MC Riders. white	Riderserie SCM/SRC	15 mm/6 mm	200	**1881280000**
ESG 6/15 K MC white	self-adhesive	15 mm/6 mm	200	**1880100000**
ESG 6/15 F MC NE WS n	Festo	15 mm/6 mm	200	**1136810000**
ESG 6/17 K MC yellow	self-adhesive	17 mm/6 mm	200	**1880110000**
ESG 6/17 K MC white	self-adhesive	17 mm/6 mm	200	**1880120000**
ESG 7/20 Sirius white	Siemens Sirius 3R/SCHS 3 u. 4	20 mm/7 mm	200	**1736181044**
ESG 7/20 Sirius yellow	Siemens Sirius 3R/SCHS 3 u. 4	20 mm/7 mm	200	**1736181687**
ESG 7/20 Sirius turquoise	Siemens Sirius 3R/SCHS 3 u. 4	20 mm/7 mm	200	**1736181696**
ESG 8/10 MC ASI white	Siemens AS interface	10 mm/8 mm	200	**1736190000**
ESG 8/11	BECKOFF/WAGO I/O MODULES	11 mm/8 mm	200	**1897570000**
ESG 8/13.5/43.3	WI SAI AKTIV UNIVERSAL	13.5 /43.3 mm/8 mm	5	**1912130000**
ESG 8/17 MC white	Télémécanique	17 mm/8 mm	200	**1674740000**
ESG 8/17 SCHS MC white	SCHS2	17 mm/8 mm	200	**1720610000**
ESG 8/17 Sys Pro M white	AEG/ABB-Stotz	17 mm/8 mm	200	**1755340000**
ESG 8/17 L MC white	Lumberg distributor	17 mm/8 mm	200	**1890470000**
ESG 8/19 MC white	AEG	19 mm/8 mm	200	**1652220000**
ESG-M 8/20 MC NE WS	Murr Cube67 & MVK MP	20 mm/8 mm	200	**1027290000**
ESG 9/6 MC white	WI SAI-Active series	6 mm/9 mm	400	**1888360000**
ESG 9/11K MC white	self-adhesive	11 mm/9 mm	200	**1857440000**
ESG 9/17 MC white	CLI TM sleeve	17 mm/9 mm	200	**1724760000**
ESG 9/17 K white	self-adhesive	17 mm/9 mm	200	**1674760000**
ESG 9/17 K yellow	self-adhesive	17 mm/9 mm	200	**1753500000**
ESG-M 9/17 MC NE WS	Murr MVP modules	17 mm/9 mm	200	**1027280000**
ESG 9/20 MC Universal white	Murr distr.+Festo CPV/CPI	20 mm/9 mm	200	**1856720000**
ESG 9/20 MC white w/o foot	TMC sleeve	20 mm/9 mm	200	**1770500000**
ESG 9/20 L MC white	Lumberg distributor	20 mm/9 mm	200	**1890460000**
ESG 9/20 L MC yellow	Lumberg distributor	20 mm/9 mm	200	**1010860000**
ESG 9/20 MC white	Siemens+Möller+WI SAI distributor	20 mm/9 mm	200	**1609940000**
ESG 9/20 MC yellow	Siemens+Möller+WI SAI distributor	20 mm/9 mm	200	**1766160000**
ESG 9/20 MC turquoise	Siemens+Möller+WI SAI distributor	20 mm/9 mm	200	**1866690000**
ESG 10/17 MC white	Allen Bradley/Festo MT	17 mm/10 mm	200	**1856700000**
ESG B&R X20 MC red	B&R X20 System	5 / 10 mm/2.5 mm	1120	**1001170001**
ESG B&R X20 MC orange	B&R X20 System	5 / 10 mm/2.5 mm	1120	**1001160001**
ESG B&R X20 MC white	B&R X20 System	5 / 10 mm/2.5 mm	1120	**1001140001**
ESG B&R X20 MC blue	B&R X20 System	5 / 10 mm/2.5 mm	1120	**1001150001**
ESG X20 10/7 MC red	B&R X20 System	7 mm/10 mm	240	**1026570000**
ESG X20 10/7 MC orange	B&R X20 System	7 mm/10 mm	240	**1026580000**
ESG X20 10/7 MC white	B&R X20 System	7 mm/10 mm	240	**1026550000**
ESG X20 10/7 MC blue	B&R X20 System	7 mm/10 mm	240	**1026560000**

ESG - Custom printing

Type	Width/Length	Qty	Order No.
ESG 5/10 MC	5 mm/10 mm	80	**1038840000**
ESG 6/15 K MC	15 mm/6 mm	40	**1880090000**
ESG 6/15 Riders.	15 mm/6 mm	40	**1881290000**
ESG 6/17 K MC	17 mm/6 mm	40	**1880080000**
ESG 8/11 MC	11 mm/8 mm	40	**1038850000**
ESG 8/13.5/43.3 SAI	13.5 /43.3 mm/8 mm	1	**1038860000**
ESG 8/17 Sys Pro M MC	17 mm/8 mm	40	**1755350000**
ESG 8/17 MC	17 mm/8 mm	40	**1674750000**
ESG 8/17 SCHS MC	17 mm/8 mm	40	**1766640000**
ESG 8/17 L MC	17 mm/8 mm	40	**1038870000**
ESG 8/19 MC	19 mm/8 mm	40	**1652230000**
ESG-M 8/20 MC	20 mm/8 mm	40	**1038910000**
ESG 9/11 K MC	11 mm/9 mm	40	**1857450000**
ESG 9/17 MC	17 mm/9 mm	40	**1770480000**
ESG 9/17 K MC	17 mm/9 mm	40	**1674770000**
ESG-M 9/17 MC	17 mm/9 mm	40	**1038920000**
ESG 9/20 Universal MC	20 mm/9 mm	40	**1856730000**
ESG 9/20 o. Foot MC	20 mm/9 mm	40	**1770510000**
ESG 9/20 MC	20 mm/9 mm	40	**1609950000**
ESG 10/17 MC	17 mm/10 mm	40	**1856710000**
ESG B&R X20 MC	5 /10 mm/2.5 mm	224	**1038890000**
ESG X20 10/7 MC	7 mm/10 mm	48	**1038930000**

ESG - accessory - tag carrier rail

Ordering data

Type	Application	Width/Length	Qty	Order No.
SCHS 1 black	ESO/protection strip	17 mm/1000 mm	1	**0138900000**
SCHS 2 self-adhesive black	ESG 8/17 SCH ; DEK ; WS	8 mm/1000 mm	1	**1720600000**
SCHS 2 black	ESG 8/17 SCH ; DEK ; WS	8 mm/1000 mm	1	**0337400000**
SCHS 3 self-adhesive black	ESG 7/20	10 mm/1000 mm	1	**1753480000**
SCHS 4 self-adhesive grey	ESG 7/20	10 mm/1000 mm	1	**1753460000**
STR SCHS 1 transparent		12.5 mm/500 mm	1	**0139200000**
ESO SCHS 1 white		12.5 mm/500 mm	1	**0139000000**

SM is a marker system for control and signalling devices. The tags clip into the holder or are fixed with the adhesive tape already attached. Individual tags can be created with the SMark-Laser, PrintJet, Plotter or MC-Mobilo marking systems.

- Produce your own markers quickly and suit your needs.
- No need to keep stocks of expensive standard tags.
- Hardwearing printing quality with the PrintJet as a substitute or engraving.
- We recommend the ETO SM protective film for extreme applications.
- Holders can be used for the Ø 22 mm push-buttons from Siemens, ABB, Moeller and Télémecanique.
- SM 18/9.5 K MC: Siemens, Type 3SB
- SM 19/42 K MC: ABB, Type ONFB72

SM - blank

Technical specification

Material	Polyamide 66, halogen-free
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C

Ordering data

Type	Length (mm)	Qty.	Order No.				
			white	silver	grey	red	yellow
SM 27/8 MC	8	80	**1699820000**	**1713680000**	**1079470000**		**1131870000**
SM 27/12.5 MC	12.5	80	**1699840000**	**1713700000**	**1079490000**		**1131860000**
SM 27/18 MC	18	80	**1699860000**	**1713740000**	**1014640000**	**1906110000**	**1131850000**
SM 27/27 MC	27	60	**1773220000**	**1773230000**	**1079510000**		**1131840000**

SM - blank - self-adhesive

Technical specification

Material	Polyamide 66, halogen-free
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C

Ordering data

Type	Length (mm)	Qty.	Order No.				
			white	silver	grey	red	yellow
SM 22/22 K MC	22	80	**1877570000**	**1877590000**	**1014650000**		**1131830000**
SM 27/8 K MC	8	80	**1812630000**	**1771930000**	**1079480000**		**1131820000**
SM 27/12.5 K MC	12.5	80	**1699880000**	**1713720000**	**1027830000**		**1131810000**
SM 27/18 K MC	18	80	**1707270000**	**1713760000**	**1073340000**	**1906120000**	**1915340000**
SM 27/27 K MC	27	60	**1783000000**	**1782990000**	**1079520000**		**1131800000**
SM 18/9.5 K MC n	9,5	200	**1248580000**		**1248610000**		**1248590000**
SM 19/42 K MC n	19	40	**1248620000**		**1248640000**		**1248630000**

SM is a marker system for control and signalling devices. The tags clip into the holder or are fixed with the adhesive tape already attached. Individual tags can be created with the SMark-Laser, PrintJet, Plotter or MC-Mobilo marking systems.

- Produce your own markers quickly and suit your needs.
- No need to keep stocks of expensive standard tags.
- Hardwearing printing quality with the PrintJet as a substitute or engraving.
- We recommend the ETO SM protective film for extreme applications.
- Holders can be used for the Ø 22 mm push-buttons from Siemens, ABB, Moeller and Télémecanique.
- SM 18/9.5 K MC: Siemens, Type 3SB
- SM 19/42 K MC: ABB, Type ONFB72

SM - Custom printing

Ordering data

Type	Length (mm)	Qty.	Order No.	Colour and print details
SM 27/8	8	80	**1699830000**	
SM 27/8 K	8	80	**1713690000**	
SM 27/12.5	12.5	80	**1699850000**	
SM 27/12.5 K	12.5	80	**1699890000**	
SM 27/18	18	80	**1699870000**	
SM 27/18 K	18	80	**1707280000**	
SM 22/22 K	22	80	**1877580000**	
SM 27/27	27	60	**1773240000**	
SM 27/27 K	27	60	**1783010000**	
SM 18/9.5 K MC n	9,5	40	**1248550000**	
SM 19/42 K MC n	19	8	**1248560000**	



SM - accessory - holder

Technical specification

Material	Polyamide 66, halogen-free
UL 94 flammability rating	V2
Min. temperature, continuous	-40 °C
Max. temperature, continuous	100 °C
Colour	black

Ordering data

Type	Length	width	Qty.	Order No.
SM-H 27/12.5	42 mm	27 mm	25	**1716640000**
SM-H 27/18	48 mm	27 mm	25	**1716630000**
SM-H 27/27	59 mm	27 mm	10	**1782710000**

SM - accessory - protective film

Technical specification

Material	Polyester film
UL 94 flammability rating	HB
Min. temperature, continuous	-20 °C
Max. temperature, continuous	80 °C
Colour	transparent

Ordering data

Type	Length	width	Labels per sheet	Qty.	Order No.
ETO SM 27/8	8 mm	27 mm	165	1	**1720570000**
ETO SM 27/12.5	12.5 mm	27 mm	100	1	**1720580000**
ETO SM 27/18	18 mm	27 mm	112	1	**1720590002**
ETO SM 22/22	22 mm	22 mm	117	1	**1880720000**
ETO SM 27/27	27 mm	27 mm	70	1	**1805840000**

ClipCard - CC DIA 30 MC

The CC DIA 30 MC is used for labelling hydraulic hoses, lights or indicators. M4 screws can be used for the variants with 4.2-mm holes or cables ties can also be used to mount. 3.2-mm blind rivets can be used with the variant that is fitted with 3.5-mm holes. According to DIN V VDE V 0108 part 100 from Jan. 2010, the safety lighting (as well as the junctions and branch-offs that make up the safety lighting system) must be marked in red or green so they can be easily and clearly identified. The distributor, circuit and lamp ID numbers must be attached next to the lamps.

ClipCard DIA blank

Technical data

Material	Polyamide 66, halogen-free
Flammability rating	V2
Temperature range	-40 °C … 100 °C

Ordering data

Type	Diameter (mm)	Hole (mm)	Qty.	Order No. white	grey	yellow
CC DIA 30/4.2 MC NE	30	4.2	60	**1248520000**	**1248540000**	**1248530000**
CC DIA 30/3.5 MC NE	30	3.5	60	**1266120000**	**1266140000**	**1266130000**

ClipCard DIA special print

Ordering data

Type	Diameter (mm)	Hole (mm)	Qty.	Order No. Colour and print details		
CC DIA 30/4.2 MC SDR	30	4.2	12	**1248470000**		
CC DIA 30/3.5 MC SDR	30	3.5	12	**1266150000**		

SwitchMark - SM 45/45-24 MC

The SM 45/45-24 MC can be used to label size-T0 rotary selector switches manufactured by Eaton Moeller.

SwitchMark blank

Technical data

Material	Polyamide 66, halogen-free
Flammability rating	V2
Temperature range	-40 °C … 100 °C

Ordering data

Type	Width x Length (mm)	Qty.	Order No. white	grey	yellow
SM 45/45-24 MC NE	45 x 45	20	**1248650000**	**1248670000**	**1248660000**

SwitchMark special print

Ordering data

Type	Width x Length (mm)	Qty.	Order No. Colour and print details		
SM 45/45-24 MC SDR	45 x 45	4	**1248570000**		

The ClipCard device markers in MultiCard format represent an alternative to engraving. The range is used to identify electrical installations and switchgear. Thanks to the established MultiCard format, labelling with SMark-Laser, PrintJet, Plotter and MC-Mobilo is possible.

- Hardwearing printing quality with the PrintJet as a substitute for engraving
- Universal fixing
- Holder (fixed with screws or cable ties)
- Tag rail (self-adhesive or screwed)
- Self-adhesive tags

Technical data

Material	Polyamide 66, halogen-free
Flammability classification toUL94	V2
Temperature range °C	–40 … 100
Temperature range °C	–40 … 60 (self-adhesive)
Approved air humidity	Max. 60 %, only for screwable tags

ClipCard, blank



Ordering data

Type		Width x Length (mm)	Qty.	Order No. white	silver	grey	red	yellow
CC 15/17 MC		15 x 17	80	1876570000	1876610000	1079530000		1131930000
CC 15/27 MC		15 x 27	80	1876770000	1876760000	1079550000		1131940000
CC 15/45 MC	n	45 x 15	40	1111210000		1111240000		1111230000
CC 15/49 MC		15 x 49	40	1877260000	1877240000	1079570000		1076970000
CC 15/60 MC		15 x 60	40	1877350000	1877340000	1072640000		1131960000
CC 30/60 MC		30 x 60	30	1934420000	1934400000	1072670000		1009320000
CC 85/54 MC	n	54 x 85	10	1138400000		1138420000		1138410000

ClipCard, blank, self-adhesive

Ordering data

Type		Width x Length (mm)	Qty.	Order No. white	silver	grey	red	yellow
CC 15/17 K MC		15 x 17	80	1876590000	1876580000	1079540000		1131920000
CC 15/27 K MC		15 x 27	80	1876640000	1876780000	1079560000		1131910000
CC 15/45 K MC	n	45 x 15	40	1111250000		1111270000		1111260000
CC 15/49 K MC		15 x 49	40	1877220000	1877270000	1079580000		1131970000
CC 15/60 K MC		15 x 60	40	1877310000	1877360000	1072650000		1131890000
CC 30/60 K MC		30 x 60	30	1934390000	1934330000	1072680000	1085430000	1078320000
CC 85/54 K MC	n	54 x 85	10	1138430000		1138450000		1138440000

Special print



Ordering data

Type		Width x Length (mm)	Qty.	Order No. Colour and print details
CC 15/17 MC		15 x 17	16	1876620000
CC 15/17 K MC		15 x 17	16	1876600000
CC 15/27 MC		15 x 27	16	1876630000
CC 15/27 K MC		15 x 27	16	1876750000
CC 15/45 MC	n	45 x 15	8	1111190000
CC 15/45 K MC	n	45 x 15	8	1111200000
CC 15/49 MC		15 x 49	8	1877200000
CC 15/49 K MC		15 x 49	8	1877230000
CC 15/60 MC		15 x 60	8	1877300000
CC 15/60 K MC		15 x 60	8	1877320000
CC 30/60 MC		30 x 60	6	1934410000
CC 30/60 K MC		30 x 60	6	1934370000
CC 85/54 MC	n	54 x 85	2	1138460000
CC 85/54 K MC	n	54 x 85	2	1138470000

ClipCard, with hole, blank

Ordering data

Type		Width x Length (mm)	Qty.	Order No. white	silver	grey	yellow
CC 15/60 O4MM MC		15 x 60	40	1057580000	1059990000		1131880000
CC 30/60 O4MM MC		30 x 60	30	1083150000		1083170000	1083160000
CC 85/54 O4MM MC	n	54 x 85	10	1248480000		1248510000	1248490000

ClipCard, with hole, special print

Ordering data

Type		Width x Length (mm)	Qty.	Order No. Colour and print details			
CC 15/60 O4MM MC		15 x 60	8	1060010000			
CC 30/60 O4MM MC		30 x 60	6	1083190000			
CC 85/54 O4MM MC	n	54 x 85	2	1248460000			

Holder

Ordering data

Type	Qty.	Order No. black		
CC-H 15/17	75	1790430000		
CC-H 15/27	45	1790410000		
CC-H 15/49	25	1790420000		
CC-H 15/60	25	1878910000		
CC-H 30/60	10	1934430000		

Protective sleeve for holder

Ordering data

Type	Qty.	Order No.		transparent	
STR CC 15/17	80			1888310000	
STR CC 15/27	80			1888290000	
STR CC 15/49	40			1888300000	
STR CC 15/60	40			1888280000	
STR CC 30/60	10			1934450000	

Protective foil

Ordering data

Type	Labels per sheet	Qty.	Order No.		transparent	
ETO CC 15/17	228	1			1880850000	
ETO CC 15/27	133	1			1880810000	
ETO CC 15/49	76	1			1880830000	
ETO CC 15/60	57	1			1880840000	
ETO CC 30/60	27	10			1934440000	

Tag rail

Ordering data

	Qty.	Order No. black	transparent	
CC-Rail 1000	1	1790150000		
CC-Rail 1000 transparent	1		1790160000	

Printing systems and software

The Weidmüller labelling systems are the quick and efficient way of producing markers for connectors, wires, cables and devices, plus labels for general use. The **M-Print® PRO** software enables users to mark electrical equipment quickly and simply. For professional and fast design, printing and ordering of your marking requirements. Borders, barcodes, graphics or photos can all be easily integrated. The multitude of data conversion routines presents you with fast and flexible options for data integration. The Weidmüller **PrintJet PRO**, **MCP Plus**, **MCP Basic**, **MC-Mobilo** printers plus those of the ThermoMark series can be used for printing.

The **PrintJet PRO** is the reference model in industrial marking for high-resolution printing and maximum wipe and scratch resistance. The **MCP Plus** plotter provides you with good flexibility because with its positioning frame it can handle more than 180 different types of marker in the MultiCard format. The **MC-Mobilo** is the ideal printer for labelling on site without a PC and a mains power supply, directly during installation work. The printers of the ThermoMark series are ideal for printing labels and/or shrinkable sleeves in excellent quality.



	Printer			
Type of marker	**PrintJet PRO**	**MCP Plus**	**MCP Basic**	**MC Mobilo**
Technical data				
Technology	Inkjet process	Plotting technique	Plotting technique	Plotting technique
Voltage	AC 230 V or AC 115 V	AC 230/AC 115 V	AC 230/AC 115 V	AC 230/AC 115 V
Printing resolution	1.200 dpi			
Interfaces	USB, LAN	Parallel Centronics, USB	USB	RS 232
Network interface card	●			
Terminal markers				
DEK/WS/ZS/MF	●	●	●	●
ELS	●	●	●	●
WAD	●			
Cable and wire markers				
SF/SFX/SFC	●	●	●	●
TM-I	●	●	●	●
ELS	●	●	●	●
Device markers				
DMC	●	●	●	●
ESG	●	●	●	●
SM/CC	●	●	●	●

PrintJet PRO

The **PrintJet PRO** inkjet printer prints markers for electric connectivity. These markers can be used for clear equipment identification on devices, cables and connectors. The labelling makes servicing, maintenance and troubleshooting much easier. Water-based ink is used for the black or spot colour printing. The print is crystal clear and resistant to environmental influences.
The **PrintJet PRO** prints plastic markers in **MultiCard** format. In combination with the user-friendly **M-Print® PRO** software and the attached loader, the printer becomes an essential part of the production.The inkjet process being used, the subsequent fusing, as well as the printer cartridge and ink have all been specially adapted by Weidmüller for industrial use. The printer has excellent long-term use capabilities, thanks to its integrated loader.

- Top-quality, resistant printing
- Spot colour print
- Perfect for constant use
- Integrated loader for 20 MultiCards
- Ideal for large quantities
- The display shows all relevant information
- Flexible connection options, from LAN ports to USB ports

Technical data

PrintJet PRO	
Type	PrintJet PRO
Application	Prints MultiCard markers
Technology	Inkjet process
Print quality	600 / 1.200 dpi
Printer drivers	Windows® 2000/XP/VISTA/7
Print software	M-Print® PRO
System requirements	Windows® 2000/XP/VISTA/7
Feed	Integrated loader
Fusing	Thermal fusing
Interface	USB, LAN
Power supply	AC 230 V or AC 115 V
Location	Office conditions
Ambient temperature	20° to 35 °C
Dimensions (L x W x H)	1060 x 500 x 310 mm
Weight	33 kg
Cartridge system	Ink cartridge, CMYK (up to 1.000.000 characters, Arial font size 6)
Scope of supply	PrintJet PRO, power cable, printer drivers, manuals (CD), Ink tank starter set colour, USB cable, M-Print® PRO software

Ordering data

PrintJet PRO

Type		**Order No.**
PrintJet PRO 115V		**1024050000**
PrintJet PRO 230V		**1001180001**
Accessories		
PJ PRO TNTK INK SET COL	Ink tank starter set, colour	**1027110000**
PJ PRO TNTK INK K	● Ink tank Black	**1027040000**
PJ PRO TNTK INK C	● Ink tank Cyan	**1027050000**
PJ PRO TNTK INK M	● Ink tank Magenta	**1027060000**
PJ PRO TNTK INK Y	● Ink tank Yellow	**1027070000**
PJ PRO TNAW	waste pad	**1024140000**
Ink tank PrintJet II		**1858920000**
Clean Unit PrintJet II		**1858950000**
Ink tank PrintJet		**1797460000**
Clean Unit PrintJet		**4062150000**

MCP Plus

The plotter **MCP Plus** complements the Weimüller MultiCard concept. It is suitable for smaller quantities of markers and when only part of a MultiCard is to be printed on. The special positioning frame for five MultiCards increases productivity by 20 % over comparable systems. With the positioning frame for SlimFix markers sizes 4 to 6, printing on more than 160 MultiCard types for terminals, cables, wires and equipment is possible. Labels are printed with the MCP-Label positioning frame. Suitable for use with the Weidmüller **M-Print® PRO** software.

- 2 positioning frames for more than 160 MultiCard types
- MultiCards easily fitted into the frame
- Easy to use with partly used MultiCards
- Automatic pen activation function
- Safe storage of the plotter pens



Technical data

Type	MCP Plus
Application	printing of MultiCard markers and labels
Technology	plotting technique
Print software	M-Print® PRO
System requirements	Windows 2000/XP/VISTA/7
Interface	Parallel Centronics / USB
Power supply	230/115 V AC
Feed	manual
Location	office conditions
Ambient temperature	10 °C – 35 °C
Dimensions (L x W x H)	660 x 440 x 125 mm
Weight	approx. 8 kg
Scope of supply	MCP Plus with Centronics cable, USB cable, power pack (100-240 V AC/50-60 Hz), Euro and US plugs, MultiCard positioning frame, 0.25 P-Ink plotter pen, printer driver, M-Print® PRO software and manual

Ordering data

MCP Plus

Type	Order No.
MCP Plus plotter set	**1925000000**

MCP Basic

The **MCP Basic** plotter is a flexible and portable solution that allows you to print your labels on-site quickly and easily.

The **MCP Basic** is suited for printing small-scale labelling jobs, partial labels, or remaining quantities

- Small space-saving flat-bed plotter
- Positioning frame for 3 MultiCards
- Easily filled with MultiCard sheets
- Positioning frame for SlimFix, sizes 4 to 6 and a label positioning frame optionally available
- Works together with Weidmüller's **M-Print® PRO** software



Technical data

Type	MCP Basic
Application	Printing MultiCard markers and labels
Technology	plotting technique
Plotting speed	max. 40 mm/s
System requirements	Windows® 2000/XP/VISTA/7
Software	M-Print® PRO
Interfaces	USB
Voltage supply	100~240 V AC, 50-60 Hz
Voltage supply	Via external power supply unit with interchangeable adapters
Feed	manual
Location	office conditions
Ambient temperature	10°C – 35°C
Dimensions (L x W x H) mm	440 x 440 x 125
Weight	6 kg
Scope of supply	MCP Basic plotter, printer driver, power cord, USB cable, M-Print® PRO software, 0.25 P-Ink plotter pen, MultiCard positioning frame, power supply unit (100-240 V AC / 50-60 Hz), Euro and US plugs, user manual on CD, hand trolley-case

Ordering data

MCP Basic

Type	Order No.
MCP Basic	**1139400000**



MCP positioning frames

Ordering data

Type	for		Qty.	Order No.
MCP AP PLUS	MultiCards		1	**1924360000**
MCP AP BASIC	MultiCards		1	**1139880000**
MCP AP SF 4-6	SlimFix sizes 4 to 6		1	**1924310000**
MCP AP Labels	Labels		1	**1924370000**

MCP plotter pens

Type	for		Qty.	Order No.
Plotter Pen 0.18	Reusable pen		1	**1768570000**
Plotter Pen 0.25	Reusable pen		1	**1768540000**
Plotter Pen 0.25 P-Ink	Disposable pen 8 ml	Not for CLI T sleeves	1	**1920640000**
Plotter Pen 0.35	Reusable pen		1	**1768550000**
Plotter Pen 0.35 P-Ink	Disposable pen 8 ml	Not for CLI T sleeves	1	**1920650000**
Plotter Pen 0.50	Reusable pen		1	**1768560000**
Plotter Pen 0.50 P-Ink	Disposable pen 8 ml	Not for CLI T sleeves	1	**1005710000**
Plotter Pen 0.70	Reusable pen		1	**1011440000**
Plotter Pen 0.70 P-Ink	Disposable pen 8 ml	Not for CLI T sleeves	1	**1011450000**

MCP ink

Type	Contents		Qty.	Order No.
P- Ink	30 ml	Not for CLI T sleeves	1	**1924340000**
Ink 2000	25 ml		1	**1772120000**

MCP miscellaneous

Type	Contents	Qty.	Order No.
P cleaner	30 ml	1	**1924330000**
Cleaner Clean 2000	25 ml	1	**1772130000**
Inlay for MCP		1	**1935130000**
Inlay SFC 3		1	**1058090000**
MCP adhesive strips		5	**1924320000**
MCP Plus cover		1	**1924350000**
MCP TP-KOF Basic	Trolley MCP Basic	1	**1139890000**

The STI-S felt tip pen is suitable for labelling blank Weidmüller marking products. It can be used for handwritten labels or, in conjunction with the STI-S adapter, for a plotter printout. A black, waterproof ink is used.

Accessories - STI pen

Ordering data

Type		Qty	Order No.
Adapter aluminium STI pen		1	**1762440000**
STI pen SW	Not for CLI T sleeves	10	**0508401694**

MC-Mobilo

The MC-Mobilo allows users to work directly at place. There is no need for a PC and no need for a power supply so electrical equipment can be labelled anywhere, anytime. The rechargeable battery provides power for up to 3 hours. The universal inlay enables up to 120 different marker types of the MultiCard range to be processed.

Technical data

Type	Plotter
Application	Printing of MultiCard markers
Technology	Plotting technique
Print software	WM-Print
Interface	RS 232
Power supply	AC 230 / AC 115 V
Feed	manual
Location	can be used anywhere
Ambient temperature	15 – 30 °C
Dimensions (L x W x H)	380 x 190 x 68 mm
Weight	3 kg
Scope of supply	MC-Mobilo, universal power unit, including adapters (EURO, UK, USA), data cassette, operating instructions, PowerPack, PC connecting cable, WM-Print, universal MultiCard mounting frame, 0.25 plotter pen, carry case

Ordering data

MC-Mobilo

MC-Mobilo		Qty.	Order No.
MC-Mobilo 110/220 V		1	**1741260001**
MC-Mobilo Accessories			
Printkit (Ink 2000, Clean 2000, Plotter-Pen 0.25)		1	**1686920000**
Frame inlay SF 4-6		1	**1802180000**
Inlay SFC 3		1	**1058090000**
Accessories Plotter IP220/MC-Mobilo			
P-Ink 30 ml	Not suitable for CLI-T sleeves	1	**1924340000**
Ink 2000 25 ml		1	**1772120000**
P cleaner 30 ml		1	**1924330000**
Cleaner Clean 2000 25 ml		1	**1772130000**
Plotter Pen 0.18		1	**1768570000**
Plotter Pen 0.25		1	**1768540000**
Plotter Pen 0.25 P-Ink	Not suitable for CLI-T sleeves	1	**1920640000**
Plotter Pen 0.35		1	**1768550000**
Plotter Pen 0.35 P-Ink	Not suitable for CLI-T sleeves	1	**1920650000**
Plotter Pen 0.50		1	**1768560000**
Plotter Pen 0.50 P-Ink	Not suitable for CLI-T sleeves	1	**1005710000**
Plotter Pen 0.70		1	**1011440000**
Plotter Pen 0.70 P-Ink	Not suitable for CLI-T sleeves	1	**1011450000**
Accessories – STI pen			
Adapter aluminium STI pen		1	**1762440000**
STI pen SW	Not suitable for CLI-T sleeves	10	**0508401694**

M-Print® PRO Label Designer

Print and **ordering software** for markers and labels

M-Print® PRO is a professional software for printing and ordering Weidmüller markers and labels under Windows®. This software helps you to optimise your processes for marking electrical equipment. You can design, print and order your marking materials effortlessly, professionally and quickly: texts, frames, lines, graphics, barcodes, serial numbers and photos.



Technical data

Here is an overview of the main functions
Integrated product catalogue for all labels and markers, including images and links to the relevant web pages and product data sheets
Markers and labels can be designed in as many levels as required
Custom formatting of individual text characters (RTF)
Perform copy-and-paste functions with texts and their formats
Supports UNICODE for foreign-language texts, such as Russian, Chinese, Polish, etc.
Enter data on labels or worksheet
Permanent print preview: see how the printout will look during the design phase
Numeric and alphanumeric counts and sequences
Extensive range of image formats (*.bmp, *.wmf, *.png, *.ico, *.jpeg, *.tif, *.gif)
Image library including all the important symbols used in electrical engineering
Assign product to specific printer; for example, ESG 9/20 to PrintJet, LaserMark to laser printer, etc.
Output devices supported: PrintJet PRO, PrintJet I+II, SMark-Laser, ThermoCard, THM as well as standard printers with Windows® drivers, plotter MCP
Optimum and rapid adjustment of the output devices
Online update service via the Internet
Interface to RailDesigner®
Import assistant to create your own import filter for numerous file formats (*.txt, *.csv, *.xml etc.)
Imports data from CAE systems

Operating systems supported
WINDOWS® 2000/XP/VISTA/7

System requirements	
• RAM	> 64 MB
• Processor	> Pentium PIII or comparable model
• Graphics	> 800 x 600 pixels with 256 colours optimum: 1024 x 768 with 16-bit High Colour
• Hard drive	> 90 MB free storage
• Miscellaneous	mouse, keyboard, CD-ROM drive (to install the software)

M-Print® PRO is available in two editions:

- M-Print® PRO Standard Edition for professional printing results with all of Weidmüller's marking materials
- M-Print® PRO Advanced Edition for professional printing results with all of Weidmüller's marking materials plus labels to customer specification

Ordering data

M-Print® PRO

Type	Order No.
M-Print® PRO	1905490000
M-Print® PRO advanced	1905500000

CB cable ties provide fixings for cables and markers for special requirements. They are especially suitable for fixing CLI M, SFX, WKM and WKS cable markers. The material consists of unbreakable polyamide PA 6.6 with UL94 flammability rating V2.

Cable ties

Technical specification

Material:	Polyamide
Flammability class:	V2 acc. to UL 94
Colour:	natural and black

Temperature rage:

- Continuous operating temperature: (after assembly) –40 °C to +85 °C
- Installation temperature: (during assembly) –10 °C to +60 °C
- Short-term up to: +110 °C
- Melting point: +256 °C

Oxygen index (LOI): 27%

Approval according to EN 50 146
Halogen-free

Resistance to chemicals:

- Excellent resistance to alkalis, oils, grease, oil products, chlorate solvents
- Limited resistance to all acids
- No resistance to phenols

Approvals:

Ordering data

Type	Dimensions (LxW) mm	Qty.	Min. (mm) bundle-Ø	Max. (mm) bundle-Ø	Min. Tensile strength in N	Order No. natural	Order No. black
CB 98/2.5	98 x 2.5	100	1	21	80	**1278600000**	**1697890000**
CB 120/4.5	120 x 4.5	100	2,5	24	220	**7940006052**	**7940006053**
CB 120/7.8	120 x 7.8	100	3,5	24	540	**7940006062**	**7940006063**
CB 135/2.5	135 x 2.5	100	1	32	80	**7940006040**	**7940006047**
CB 140/3.6	140 x 3.6	100	2	35	130	**1278700000**	**1697900000**
CB 160/4.5	160 x 4.5	100	2,5	40	220	**1723540000**	**1723560000**
CB 160/2.6	160 x 2.6	100	1	40	80	**7940006048**	**7940006049**
CB 178/4.8	178 x 4.8	100	2	45	220	**1723550000**	**1723570000**
CB 200/4.8	200 x 4.8	100	3	50	220	**1278800000**	**1697910000**
CB 200/2.6	200 x 2.6	100	1	50	80	**7940006050**	**7940006051**
CB 200/3.6	200 x 3.6	100	2	50	130	**1720630000**	**1720660000**
CB 180/7.8	180 x 7.8	100	3,5	45	540	**7940006064**	**7940006065**
CB 225/12.5	225 x 12.5	100	7,5	57	1080	**7940006076**	**7940006077**
CB 240/7.8	240 x 7.8	100	3,5	63	540	**7940006066**	**7940006067**
CB 250/4.8	250 x 4.8	100	3	68	220	**7940006054**	**7940006055**
CB 290/3.6	290 x 3.6	100	2	80	130	**1720640000**	**1720650000**
CB 290/4.8	290 x 4.8	100	3,5	80	220	**1278900000**	**1697920000**
CB 300/7.8	300 x 7.8	100	4	80	540	**7940006068**	**7940006069**
CB 370/3.6	370 x 3.6	100	2	103	130	**7940006056**	**7940006057**
CB 360/4.8	360 x 4.8	100	3,5	103	220	**1279000000**	**1697930000**
CB 365/7.8	365 x 7.8	100	8	100	540	**1279100000**	**1697940000**
CB 390/4.8	390 x 4.8	100	3,5	106	220	**7940006058**	**7940006059**
CB 430/4.8	430 x 4.8	100	3,5	115	220	**7940006060**	**7940006061**
CB 450/7.8	450 x 7.8	100	35	130	540	**7940006070**	**7940006071**
CB 500/12.5	500 x 12,5	100	30	143	1080	**7940006078**	**7940006079**
CB 540/7.8	540 x 7,8	100	35	158	540	**7940006072**	**7940006073**
CB 750/7.8	750 x 7,8	100	35	220	540	**1720680000**	**1720670000**
CB 780/9.0	780 x 9,0	100	32	233	700	**7940006074**	**7940006075**
CB 850/12.5	850 x 12,5	100	40	255	1080	**7940006082**	
CB 1000/12.5	1000 x 12,5	100	40	302	1080	**7940006084**	**7940006085**





Accessories - holders

CBDM	Cable tie direct mounting for cable harness max. Ø 50 mm,total length: 200 mm
CBH 8.1/6.2	Cable tie retainer for use on mounting plate Max. plate thickness 3.2 mm, hole Ø max. 6.2 mm
CBH 19/19	Cable tie retainer for sticking on, surface: 19 x 19 mm
CBH 27/27	Cable tie retainer for sticking on, surface: 27 x 27 mm
CB-R	Releasable cable ties

Ordering data

Type	Dimensions (LxW) mm	Qty.	Min. (mm) bundle-Ø	Max. (mm) bundle-Ø	Min. Tensile strength in N	Order No. natural	Order No. black
CB-R 200/7.5	200 x 7.5mm	100	6	50	220	**1059200000**	**1059210000**
CB-R 250/7.5	250 x 7.5mm	100	6	65	220	**1059220000**	**1059230000**
CB-R 350/7.5	350 x 7.5mm	100	6	100	220	**1059240000**	**1059250000**
CBH 8.1/6.2	8.1 x 6.2	100				**1279200000**	
CBH 19/19	19 x 19	100				**1289200000**	**1697950000**
CBH 27/27	27 x 27	100				**1289400000**	**1697960000**
CBDM 200/4.5	200 x 4.5	100	50	220		**1279300000**	



The RT 1 is a compact, pistol-shaped tool for fastening and cutting cable-ties in one operation.
The tension is widely adjustable, ranging from short to standard cable-ties.
The RT 1 is designed for bundles with a diameter of 1.6 mm to 100 m

Accessories - tools

Ordering data

Type	Length	Weight	Qty	Order No.
RT 1	160 mm	260 g	1	**1296000000**

Addresses worldwide

AE United Arab Emirates
Weidmuller Middle East FZE
P.O. Box 8591
SAIF-Zone
Sharjah – U. A. E.
Phone +971 6 5572723
Fax +971 6 5572724
wme.info@weidmueller.com

AR Argentina
CPI SA
Bauness 2660
1431 Buenos Aires
Phone +54 11 45238008
Fax + 54 11 45220546
info@cpi.com.ar
www.cpi.com.ar

AT Austria
Weidmüller GmbH.
Industriezentrum Nö Süd
Straße 2, Objekt M2
2355 Wiener Neudorf
Phone +43 2236 6708-0
Fax +43 2236 6708-199
office.at@weidmueller.com

AU Australia
Weidmüller Pty. Ltd.
P.O.Box 6944
Huntingwood Drive 43
Huntingwood,
NSW, 2148
Phone +61 2 9671-9999
Fax +61 2 9671-9911
info@weidmuller.com.au
www.weidmuller.com.au

AZ Azerbaijan
West Industries Ltd.
Caspian Plaza, 5-th Floor
44 J. Jabbarly Str., Baku
Phone +99412 499 15 15
Fax +99412 499 14 93
sales@west-i.com

BA Bosnia and Herzegovina
BH ES ELEKTROSISTEM d.o.o.
Bul. Vojvode S.
Stepanovica kod br. 272
78000 BiH - Banja Luka
Phone +387 51 420-340
Fax +387 51 420-341
elsist@inecco.net
www.elektrosistem.ba

BE Belgium
Weidmüller Benelux B.V.
Mechelsesteenweg 519 bus 6 en 7
1930 Nossegem
Phone +32 2 752 4070
Fax +32 2 751 3606
info@weidmueller.be
www.weidmueller.be

BG Bulgaria
Weid-Bul EOOD
1756 Sofia
13, bul. "Kliment Ohridski"
Phone +359 2 9632560
Fax +359 2 9631098
sofia@weidbul.com
www.weidbul.com

BH Bahrain
Khayber Trading Company
P.O. Box 1976 Manama,
Phone +973 720747
Fax +973 720331
khayber@batelco.com.bh

BR Brazil
Conexel Conexoes Elétricas Ltda.
Rua Garcia Lorca, 176
09695-900, Sao Paulo SP
Phone +55 11 43669600
Fax +55 11 43621677
vendas@conexel.com.br
www.conexel.com.br

BY Belarus
TECHNIKON Ltd.
Oktyabrskaya Str. 16/5
Apt. 704, Minsk 220801
Phone +375 17 2275830
Fax +375 17 2275830
technikon@belsonet.net

CA Canada
W Interconnections CANADA Ltd.
10 Spy Court, Markham,
Ontario L3 R5 H6
Phone +1 905 475-1507
Fax +1 905 475-2798
info1@weidmuller.ca
www.weidmuller.ca

CH Switzerland
Weidmüller Schweiz AG
Rundbuckstraße 2
8212 Neuhausen am Rheinfall
Phone +41 52 6740707
Fax +41 52 6740708
info@weidmueller.ch
www.weidmueller.ch

CL Chile
Felipe Bahamondes S.A./ATS AGRO
Maria Luisa Santander 0475
Casilla 3425
Santiago
Phone +56 2 341-1271
Fax +56 2 341-1275
felipe@atsintech.com

CN China
Weidmüller Interface International
Trading (Shanghai) Co., Ltd.
25F, BM Intercontinental Business
Center,
100 Yutong Road,Shanghai 200070
P.R. China
Phone +86 21 22195008
Fax +86 21 22195009
www.cnweidmuller.com

CO Colombia
Automatización Avanzada S. A.
Carrera 97 No.24c, 23 B4
4 Bogotá D. C.
Phone +57 1 5478510
Fax +57 1 4223044
comercial@
automatizacionavanzada.com
www.automatizacionavanzada.com

CR Costa Rica
ELVATRON S.A.
la Uruca 400 Norte
Banco Costa Rica
San José Costa Rica
Phone +506 2 961060
Fax +506 5 200609
dirk.haase@elvatron.com
www.elvatron.com

CZ Czech Republic
Weidmüller s. r. o.
Lomnického 5/1705
14000 Praha 4
Phone +420 2 44001400
Fax +420 2 44001499
office@weidmueller.cz
www.weidmueller.cz

DE Germany
Weidmüller GmbH & Co. KG
P.O. Box 3054
32720 Detmold
Ohmstraße 9
32758 Detmold
Phone +49 5231 1428-0
Fax +49 5231 1428-116
weidmueller@weidmueller.de
www.weidmueller.de

DK Denmark
Wexøe A/S
Lejrvej 31
3500 Vaerloese
Phone +45 45465800
Fax +45 45465801
wexoe@wexoe.dk
www.wexoe.dk

EC Ecuador
Elsystec S. A. Electricidad
Sistemas y Tecnología
Vasco de Contreras N35-25
y Mañosca, Quito
Phone +593 2 2456510
Fax+593 2 2456755
Elsystec@uio.satnet.net

EE Estonia
Soots Interface OÜ
Pärnu mnt 142
11317 Tallinn
Phone +372 5296177
Fax +372 6096933
info@sootsinterface.ee
www.sootsinterface.ee

EG Egypt
Standard Electric (OMEGA)
87, Mohamed Farid Street
Heliopolis, Cairo
Phone +20 26422977
Fax +20 26422955
stdelec@rite.com

ES Spain
Weidmüller S. A.
Narcis Monturiol 11-13
Pol. Ind. Sudoeste
08960 Sant Just Desvern
Barcelona
Phone +34 93 4803386
Fax +34 93 3718055
weidmuller@weidmuller.es
www.weidmuller.es

FI Finland
JUHA-ELEKTRO OY
P. O. Box 57, 641 Helsinki
Kylvöpolku 6, 680 Helsinki
Phone +358 10 8328 100
Fax +358 10 8328 109
info@juha-elektro.fi
www.juha-elektro.fi

FR France
Weidmüller E. U. R. L.
12, Chaussée Jules César
B.P. 263 Osny
95523 Cergy Pontoise Cedex
Phone +33 1 34245500
Fax +33 1 34245501
mail@weidmuller.fr

GB Great Britain
Weidmüller Ltd.
1 Abbey Wood Road
Kings, West Malling
ME19 4YT
Phone +44 1732 877000
Fax +44 1732 874296
marketing@weidmuller.co.uk

GR Greece
Electrorama S.A.
1 An. Martali Str.
41335 Larissa
Phone +30 2410 552533188
Fax +30 2410 283463189
valvizos@electrorama.com.gr

Greece
GA Contact Solutions
11, Ippokratous Str.
14452 Metamorfosi Attika
Phone +30 210 2823233
Fax +30 210 2823233
gasaless@gmail.com

HK Hong Kong
United Equity Limited
Suite B, 11/F International Industrial
Centre
2-8 Kwei Tei Street, Fotan, Shatin
Phone +852 26876739
Fax +852 26876735
united_equity@sinatown.com

HR Croatia
Elektro Partner d.o.o.
Slavonska Avenija 24/6
10000 Zagreb
Phone +385 1 6184793
Fax +385 1 6184795
elektropartner@zg.t-com.hr

HU Hungary
Weidmüller Kft
Gubacsi út 6
1097 Budapest
Phone +36 1 3827700
Fax +36 1 3827701
info@weidmueller.hu

ID Indonesia
PT. Nego Electrindo
Ruko Mega Grosir Cempaka Mas,
Blok I No 20 – 22
Jl. Let.Jend. Suprato –
Jakarta 10640
Phone +62 21 42882255
Fax +62 21 42882266
sales@negoelectrindo.co.id

IE Ireland
Please contact Weidmüller Ltd. in
Great Britain

IL Israel
A.U.Shay Ltd.
P.O. Box 10049
Embar Street 23/25
Petch-Tikwa 49222
Phone +972 3 9233601
Fax +972 3 9234601

Israel
ATEKA Ltd.
23 Hayetzira St.
Kiryat Aryeh
49130 Petach-Tikva, Israel
Phone +972 3 9392344
Fax +972 3 9243273
marketing@ateka.co.il
www.ateka.co.il

IN India
Weidmuller Electronics India Pvt. Ltd
Plot # 32, 3rd Floor, North Court
Lane North Avenue, Opp Jogger's Park
Kalyani Nagar, Maharastra
411006 Pune
Phone +91 9049800960
Nitish.Rajan@weidmueller.de

IR Iran
Tamin Ehtiajat Fani Tehran (TAF Co.)
72, Iranshahr Ave.(Unit # 5)
15816 Tehran
Phone +98 21 8831-7851
Fax +98 21 8882-0268
tafco@safineh.net

IS Iceland
Samey Automation Center
Lyngas 13, 210 Garoabaer,
Phone +354 510 5200
Fax +354 510 5201
samey@samey.is

IT Italy
Weidmüller S.R.L.
Via Albert Einstein 4
20092 Cinisello Balsamo
Milano
Phone +39 02 660681
Fax +39 02 6124945
weidmuller@weidmuller.it
www.weidmuller.it

JO Jordan
HORIZONS
P.O.Box: 330607
Amman Jordan 11133
Phone +962 6 4882114
Fax +962 6 4882115
horizons@go.com.jo

JP Japan
Nihon Weidmüller Co. Ltd.
Sphere Tower Tennoz,
2-2-8 Higashi-Shinagawa,
Shinagawa-Ku, Tokyo 140-0002
Phone +81 3 6711-5300
Fax +81 3 6711-5333
www.weidmuller.co.jp

KR Korea
Weidmüller Korea Co., Ltd.
6floor, Sukyoung building, 242-54
Nonhyun-dong, Kangnam-Gu
Seoul, Korea
Zip: 135-830
Phone +82 2 5160003
Fax +82 2 5160090
info@weidmuller.co.kr

KW Kuwait
KANA CONTROLS General
Trading & Cont. CO. W.L.L.
Al Rai Industrial Area,
Plot 28-30, St. 31
P.O.Box: 25593
Safat, 13016
Phone +966-474 1373/4
Fax +966-474 1537
info@kanacontrols.com

Group companies DE

Agency abroad DE

Without own Agency DE

LB Lebanon
Progress Engineering & Trading Enterprises
Al Nahr Street
Beirut
Phone +961 1 444664
Fax +961 1 561880
progress@inco.com.lb

LT Lithuania
ELEKTROS IRANGA
Tinklu g.29a, 5319 Panevezys
Phone +370 45582828
Fax +370 45582727
info@eliranga.lt

LU Luxembourg
Please contact Weidmüller Benelux B.V. in the Netherlands

LV Latvia
SIA "ABI4"
56A Daugavgrivas str.
1007 Riga
Phone +371 67470999
Fax +371 67465637
abi_4@tvnet.lv

MD Moldova
BERHORD A&D srl
44, srt. Sarmizegetusa 37/3
Off 414. b-dul Decebal, 3,
Chisinau, MD 2001
Phone +373 22 507137
Fax +373 22 507134
atiuleanu@berhord.com

ME Montenegro
Please contact
ES-YU Elektrosistem in Serbia

MK Macedonia
ELEKTRO – SMK dooel
UL. III Makedonska brigada b.b.
1000 Skopje
Phone +389 22 460 295
Fax +389 22 460 298
Elektro-smk@telekabel.net.mk

MT Malta
E. S. S., Electrical Supplies & Services Ltd
104 J. Sciberras Str.
Hamrun HMR 08
Phone +356 21 255 777
Fax +356 21 255 999
robert@ess.com.mt

MU Mauritius
MUBELO Electrical Ltd
Office 26, Gateway building,
St Jean Road, Quatre Bornes
Phone +230 467 0989
Fax +230 465 4051
richard.mubelo@orange.mu

MX Mexico
W Interconnections, S.A. DE C.V.
Blvd. Hermanos Serdán No. 698
Col. San Rafael Oriente
Puebla, C.P. 72029
Phone +52 222 22686227
clientes@weidmuller.com.mx

MY Malaysia
Connect Plus Technology Sdn Bhd
No. 43, Jalan PJS 11/22,
Bandar Sunway, 46150 Petaling Jaya
Selangor Darul Ehsan
Phone +60 3 5633 7363
Fax +60 3-5633 6562
paul@cptech.com.my
www.cptech.com.my

NL Netherlands
Weidmüller Benelux B.V.
Franciscusweg 221
1216 SE Hilversum
Postbus 1505
1200 BM Hilversum
Phone +31 35 6261261
Fax +31 35 6232044
info@weidmuller.nl

NO Norway
Siv. Ing. J. F. Knudtzen A/S
Billingstadsletta 97
P.O. Box 160
1378 Nesbru
Phone +47 66 983350
Fax +47 66 980955
firmapost@jfknudtzen.no
www.jfknudtzen.no

NZ New Zealand
Cuthbert S. Steward Limited
27 Te Puni Street
POB 38496
Petone, Wellington
Phone +64 4 5686156
Fax +64 4 5686056
info@weidmueller.de

OM Oman
DAN INTERNATIONAL LLC.
PO.BOX 2901
111 Seeb
Phone +968 503 677
Fax +968 503 755
yedu@danintl.com

PE Peru
TECNOLOGÍA ELÉCTRICA Y SOLUCIONES S.A.C.
Calle Huandoy 501, Lima 32, Peru
Phone / Fax +51 1 562-0004
info@tecsol-peru.com

Peru
IMGEPRO DEL PERU S.A.C.
Jr. Arequipa 3410, Lima 31, Peru
Phone / Fax +51 1 569-7678
dbernardo@imgepro.com.pe
www.imgepro.pe

PH Philippines
Enclosure Systems Specialists Inc
W-15 La Fuerza Compound
2241 Don Chino Roces Avenue
Makati City 1231
Phone +63 2 813 8580
Fax +63 2 813 8596
sales_encsys@pldtdsl.net

PK Pakistan
Kana Controls (Pak)
Apartment No. 33 C III
Chenab Block,
Allama Iqbal Town
Lahore, Pakistan
Phone +92 42 5419948
+92 42 7845160
Fax +92 42 5422895
nadeem@kanapak.com
www.kanapak.com

PL Poland
Weidmüller Sp. z o.o.
Ul. Goledzinowska 10
03-302 Warszawa
Phone +48 22 5100940
Fax +48 22 5100941
biuro@weidmuller.com.pl
www.weidmuller.pl

PT Portugal
Weidmüller Sistemas de Interface S. A.
Estrada Outeiro Polima, R. Augusto Dias da Silva, Lote B, Esct. 2
2785-515 Abóboda -São Domingos de Rana
Phone +351 21 4459191
Fax +351 21 4455871
www.weidmueller.pt

QA Qatar
Doha Motors Trading Co.
(Technical Division)
Post Box No. 145
Airport Road
Doha - Qatar
Phone +974 465 1441
Fax +974 465 0925
dmtctech@qatar.net.qa

RO Romania
Rominterface Impex SRL
Str. Gh. Dem Teodorescu 30 A
30916 Bucuresti - sector 3
Phone +40 21 3220230
Fax + 40 21 3228857
office@rominterface.ro

RS Serbia
ES-YU Elektrosistem
Pariske komune 41
11070 Novi Beograd, Serbia
Phone +381 11 3018660
Fax +381 11 2693608
esyu@eunet.rs
www.elektrosistem.co.rs

RU Russia
Weidmüller Interface GmbH & Co. KG
Representative Office
Warshavskoye highway, 25A, bld. 6
117105 Moscow
Phone +7 4 95 771-6940
Fax +7 4 95 771-6941
info@weidmueller.ru
www.weidmueller.rus

SA Saudi Arabia
Al Abdulkarim Holding Co.
P.O Box. 4
Dammam 31411
Phone +9668337110
Fax +9668338242
salehsk@akh.com.sa
www.akte.com.sa

Saudi Electric Supply Co.
P.O. Box 3298
Al Khobar 31952
Phone +966 3 882 9546227
Fax +966 3 882 9547
Safdar.malik@sesco-ge.com

SE Sweden
Weidmüller AB
Axel Daniessons väg 271
P.O. box 31025
200 49 Malmö
Phone +46 (0) 7 71 43 00 44
Fax +46 (0) 40 37 48 60
info@weidmuller.se
www.weidmuller.se

SG Singapore
Weidmüller Pte. Ltd.
70 Bendemeer Road
#04-03 Luzerne
Singapore 339940
Phone +65 6841 5311
Fax +65 6841 5377
info@weidmuller.com.sg
www.weidmuller.com.sg

SI Slovenia
ELEKTROSPOJI d.o.o.
Stegne 25, 1000 Ljubljana
Phone +386 15113810
Fax +386 15111604
info@elektrospoji.si
www.elektrospoji.si

SK Slovakia
ELEKTRIS s.r.o.
Elektrárenská 1
83104 Bratislava
Phone +421 2 49200113
Fax +421 2 49200119
weidmueller@computel.sk

TH Thailand
Pisanu Engineering Co., Ltd
800/43-45 Soi Trakulsuk
Asoke-dindaeng Road,
Dindaeng, Bangkok 10400
Phone +66 2 245 9113
Fax +66 2 6429220
jayasankar@pisanu.co.th
www.pisanu.co.th

TN Tunisia
Please contact
Weidmüller E.U.R.L. in France

TR Turkey
Weidmüller Elektronik Ticaret Ltd.
Sirketi
Kavacik Mah. Orhan Veli Kanik
Caddesi 9/1
34810 Beykoz – İstanbul
Phone +90 216 5371070 (Pbx)
Fax +90 216 5371077
info@weidmuller.com.tr
www.weidmuller.com.tr

TW Taiwan
Fittatek Co., Ltd.
12F No. 185 Fu-Kuo Road,
Tso Ying Dist, Kaohsiung
Phone +886 7 556 0858
Fax +886 7 556 3279
stanley@fittatek.com.tw
www.fittatek.com.tw

Taiwan
Eucan Enterprise Ltd.
No. 145 He Ping 2nd Rd
Kaohsiung
Phone +886 7 715 6610
Fax +886 7 715 8748
mark@eucan.com.tw
www.eucan.com.tw

UA Ukraine
TEKO INTERFACE ooo
ul. Lewanewskogo 6
03058 Kiev
Phone +38 044 401 09 90
Fax +38 044 401 08 64
weidmueller@tekointerface.com
www.tekointerface.com.ua

US United States
W-Interconnections Inc.
821 Southlake Boulevard,
Virginia - Richmond 23236
Phone +1 804 7942877
Fax +1 804 3792593
info@weidmuller.com
www.weidmuller.com

UY Uruguay
REWO Uruguay S.A
Av. Bolivia 2001 Esq Rocafuerte
Carrasco Montevideo 11300
Phone / Fax +598 260 48439
clorda@rewouruguay.com.uy

UZ Uzbekistan
OOO "Elektro Potential"
Gani Mavljanova str., 2B
100084 Tashkent
Phone +998 98-3003821
Fax +998 71-1249286
mz1958@yandex.ru

VE Venezuela
Somerinca C.A.
Quinta Sagrado Corazon de Jesus - 3ra Transversal - Los Dos Caminos,
Caracas 1070 - A
Phone +58 212 2352748
Fax +58 212 2399341
klocmoeller@cantv.net
www.kmsomerinca.com.ve

VN Vietnam
AUMI Co., Ltd
E1, La Thanh Hotel,
218 Doi Can Street,
Lieu Giai Ward, Ba Dinh District,
Hanoi City
Phone +84 4762 8601
Fax +84 4266 1391
aumi@aumi.com.vn

Linh Kim Hai Co,. Ltd
78 Hoa Cuc Street Ward 7,
Phu Bhuan District,
Ho Chi Minh City
Phone +84 8517 1717
Fax +84 8517 1818
lkh@linhkimhai.com.vn

New Sky Co., Ltd
44/28 Tan Hai Street,
Ward 13, Tan Binh District,
Ho Chi Minh City
Phone +84 8812 6593
Fax +84 8812 6594
newsky-e@hcm.vnn.vn
www.newsky-e.com

ZA South Africa
Phambili Interface (Pty) Ltd
P.O. Box 193, 1609 Johannesburg
5 Bundo Road, Sebenza
1610 Johannesburg, Endenvale
Phone +27 11 452 1930
Fax +27 11 452 6455
sales@weidmuller.co.za
www.radinterface.co.za

DE Other countries
Weidmüller Interface GmbH & Co. KG
Postfach 3030
32720 Detmold
Klingenbergstraße 16
32758 Detmold
Phone +49 5231 14-0
Fax +49 5231 14-2083
info@weidmueller.de
www.weidmueller.com

www.weidmueller.com

Argentina
Australia
Austria
Azerbaijan
Bahrain
Belarus
Belgium
Bosnia and Herzegovina
Brazil
Bulgaria
Canada
Chile
China
Colombia
Costa Rica
Croatia
Czech Republic
Denmark
Ecuador
Egypt
Estonia
Finland
France
Germany
Great Britain
Greece
Hong Kong
Hungary
Iceland
India
Indonesia
Iran
Ireland
Israel
Italy
Japan
Jordan
Kazakhstan
Korea
Kuwait
Latvia
Lebanon
Lithuania
Luxembourg
Macedonia
Malaysia
Malta
Mexico
Moldova
Netherlands
New Zealand
Norway
Oman
Pakistan
Peru
Philippines
Poland
Portugal
Qatar
Romania
Russia
Saudi Arabia
Serbia
Singapore
Slovakia
Slovenia
South Africa
Spain
Sweden
Switzerland
Taiwan
Thailand
Tunisia
Turkey
Ukraine
United Arab Emirates
United States
Uruguay
Uzbekistan
Venezuela
Vietnam

Weidmüller is a leading international provider of solutions for electrical connectivity, transmission and conditioning of power, signal and data in industrial environments.

The company with headquarters in Detmold/Germany develops, produces and sells products in the field of electrical connectivity and electronics all over the world. Via a network of application specialists Weidmüller offers engineering services and develops application specific solutions.

The complete product and service portfolio consistently assures both Weidmüller and its customers of competitive advantages and an increase in value.

We cannot guarantee that there are no mistakes in the publications or software provided by us to the customer for the purpose of making orders. We try our best to quickly correct errors in our printed media.

All orders are based on our general terms of delivery, which can be reviewed on the websites of our group companies where you place your order. On demand we can also send the general terms of delivery to you.

Order number:
1272650000/03/2011/SMMD

4 050118 061840